

Date: November 13, 2024

Request for Modular Approval for

FCC ID: C3K2108

1. The radio elements must have the radio frequency circuitry shielded. Physical components and tuning capacitor(s) may be located external to the shield, but must be on the module assembly 2. The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal 3. The module must contain power supply regulation on the module 4. The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per §§ 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b) 5. The module must demonstrate compliance in a stand-alone configuration The module contains a metal shield which covers RF components and circuitry. The module has buffer modulation / data inputs. The module has its own power supply regulation. The module contains a metal shield which covers RF components and circuitry. The module has buffer modulation / data inputs. The module has its own power supply regulation. The module connects to its antenna using an UFL connector which is considered a non-standard connector. The antenna and connector specification provided with this filing. The module contains a metal shield which covers RF components and circuitry.	FCC ID. CSR2106		
circuitry shielded. Physical components and tuning capacitor(s) may be located external to the shield, but must be on the module assembly 2. The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal 3. The module must contain power supply regulation on the module 4. The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per §§ 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b) 5. The module must demonstrate compliance in a stand-alone configuration 6. The module must be labeled with its permanently affixed FCC ID label, or use an electronic display	Item	Requirements	EUT
tuning capacitor(s) may be located external to the shield, but must be on the module assembly 2. The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal 3. The module must contain power supply regulation on the module 4. The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per §§ 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b) 5. The module must demonstrate compliance in a stand-alone configuration 6. The module must be labeled with its permanently affixed FCC ID label, or use an electronic display The module has buffer modulation / data inputs.	1.	•	The module contains a metal shield which covers all
shield, but must be on the module assembly 2. The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal 3. The module must contain power supply regulation on the module 4. The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per §§ 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b) 5. The module must demonstrate compliance in a stand-alone configuration 6. The module must be labeled with its permanently affixed FCC ID label, or use an electronic display The module has buffer modulation / data inputs.		circuitry shielded. Physical components and	RF components and circuitry.
2. The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal 3. The module must contain power supply regulation on the module 4. The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per §§ 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b) 5. The module must demonstrate compliance in a stand-alone configuration 6. The module must be labeled with its permanently affixed FCC ID label, or use an electronic display The module has buffer modulation / data inputs.		tuning capacitor(s) may be located external to the	
inputs to ensure that the device will comply with Part 15 requirements with any type of input signal 3. The module must contain power supply regulation on the module 4. The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per §§ 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b) 5. The module must demonstrate compliance in a stand-alone configuration 6. The module must be labeled with its permanently affixed FCC ID label, or use an electronic display The module has its own power supply regulation. The module connects to its antenna using an UFL connector which is considered a non-standard connector. The antenna and connector specification provided with this filing. The module was tested in stand-alone mode.		shield, but must be on the module assembly	
Part 15 requirements with any type of input signal 3. The module must contain power supply regulation on the module 4. The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per §§ 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b) 5. The module must demonstrate compliance in a stand-alone configuration 6. The module must be labeled with its permanently affixed FCC ID label, or use an electronic display The module has its own power supply regulation. The module connects to its antenna using an UFL connector which is considered a non-standard connector. The antenna and connector specification provided with this filing. The module was tested in stand-alone mode.	2.	The module must have buffered modulation/data	The module has buffer modulation / data inputs.
3. The module must contain power supply regulation on the module 4. The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per §§ 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b) 5. The module must demonstrate compliance in a stand-alone configuration 6. The module must be labeled with its permanently affixed FCC ID label, or use an electronic display The module has its own power supply regulation. The module connects to its antenna using an UFL connector which is considered a non-standard connector. The antenna and connector specification provided with this filing. The module was tested in stand-alone mode.		inputs to ensure that the device will comply with	
on the module 4. The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per §§ 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b) 5. The module must demonstrate compliance in a stand-alone configuration 6. The module must be labeled with its permanently affixed FCC ID label, or use an electronic display The module connects to its antenna using an UFL connector which is considered a non-standard connector. The antenna and connector specification provided with this filing. The module was tested in stand-alone mode.		Part 15 requirements with any type of input signal	
 The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per §§ 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b) The module must demonstrate compliance in a stand-alone configuration The module must be labeled with its permanently affixed FCC ID label, or use an electronic display The module connects to its antenna using an UFL connector which is considered a non-standard connector. The antenna and connector specification provided with this filing. The module was tested in stand-alone mode. The module transmitter will be labeled with its ow FCC ID, and for OEM integration the integration 	3.	The module must contain power supply regulation	The module has its own power supply regulation.
antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per §§ 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b) 5. The module must demonstrate compliance in a stand-alone configuration 6. The module must be labeled with its permanently affixed FCC ID label, or use an electronic display connector which is considered a non-standard connector. The antenna and connector specification provided with this filing. The module was tested in stand-alone mode. The module transmitter will be labeled with its ow FCC ID, and for OEM integration the integration		on the module	
and be marketed and operated only with specific antenna(s), per §§ 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b) 5. The module must demonstrate compliance in a stand-alone configuration 6. The module must be labeled with its permanently affixed FCC ID label, or use an electronic display The module transmitter will be labeled with its own FCC ID, and for OEM integration the integration	4.	The module must contain a permanently attached	The module connects to its antenna using an UFL
antenna(s), per §§ 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b) The module must demonstrate compliance in a stand-alone configuration The module must be labeled with its permanently affixed FCC ID label, or use an electronic display The module transmitter will be labeled with its ow FCC ID, and for OEM integration the integration		antenna, or contain a unique antenna connector,	connector which is considered a non-standard
15.212(a), 2.929(b) The module must demonstrate compliance in a stand-alone configuration The module was tested in stand-alone mode. The module must be labeled with its permanently affixed FCC ID label, or use an electronic display The module transmitter will be labeled with its ow FCC ID, and for OEM integration the integration		and be marketed and operated only with specific	connector. The antenna and connector specification are
 The module must demonstrate compliance in a stand-alone configuration The module was tested in stand-alone mode. The module must be labeled with its permanently affixed FCC ID label, or use an electronic display FCC ID, and for OEM integration the integration 		antenna(s), per §§ 15.203, 15.204(b), 15.204(c),	provided with this filing.
stand-alone configuration 6. The module must be labeled with its permanently affixed FCC ID label, or use an electronic display FCC ID, and for OEM integration the integration		15.212(a), 2.929(b)	
6. The module must be labeled with its permanently affixed FCC ID label, or use an electronic display FCC ID, and for OEM integration the integration	5.	The module must demonstrate compliance in a	The module was tested in stand-alone mode.
affixed FCC ID label, or use an electronic display FCC ID, and for OEM integration the integration		stand-alone configuration	
	6.	The module must be labeled with its permanently	The module transmitter will be labeled with its own
manual contains labeling instructions for the host		affixed FCC ID label, or use an electronic display	FCC ID, and for OEM integration the integration
			manual contains labeling instructions for the host
device per Part 15.212 (vi)			device per Part 15.212 (vi)
7. The module must comply with all specific rules The module approved transmitter complies with all	7.	The module must comply with all specific rules	The module approved transmitter complies with all
applicable to the transmitter, including all the applicable rules and the integration manual contain		applicable to the transmitter, including all the	applicable rules and the integration manual contains
conditions provided in the integration instructions any specific requirements addressed to the integral		conditions provided in the integration instructions	any specific requirements addressed to the integrator
by the grantee and/or to the end-user of the final end-product.		by the grantee	and/or to the end-user of the final end-product.
8. The module must comply with RF exposure The module meets mobile/portable conditions level.	8.	The module must comply with RF exposure	The module meets mobile/portable conditions levels as
requirements shown in the RF exposure test report.		requirements	shown in the RF exposure test report.

Nawrin Islam Natasha

Natasle

Nawrin.Natasha@microsoft.com