

# **Nemko Korea Co., Ltd.**

300-2, Osan-Ri, Mohyun-Myun, Cheoin-Gu, Yongin-City, Gyeonggi-Do, KOREA

TEL:+ 82 31 330 1700 FAX:+ 82 31 330 1702

## **FCC PART 18 Class II Permissive Change**

### Applicant :

Daewoo Electronics Corporation  
Kitchen Appliances Div. R&D Center,  
412-2, Cheongcheon2-Dong, Bupyeong-Gu,  
Incheon, 403-032, KOREA  
Attn : Mr. Seongok Kim

Dates of Issue : May 11, 2011  
Test Report No. : NK-11-E-253  
Test Site : Nemko Korea Co., Ltd.  
EMC site, Korea

FCC ID

**C5F7NF6LMO700N**

Brand Name

**DAEWOO**

Contact Person

**Daewoo Electronics Corporation  
Kitchen Appliances Div. R&D Center,  
412-2, Cheongcheon2-Dong, Bupyeong-Gu,  
Incheon, 403-032, KOREA  
Mr. Seongok Kim  
Telephone No. : + 82 32 510 7919**

Applied Standard:

Part 18 & 2

Classification :

Consumer ISM equipment

EUT Type:

Microwave Oven

**Remark : This Class II Permissive change test report was based on test report no. NK09E864 which was issued on Oct. 08 2009.**

The device bearing the brand name and FCC ID specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in MP-5:1986.

I attest to the accuracy of data and all measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

May 11, 2011  
Tested By : Kiwang Kim  
Engineer

May 11, 2011  
Reviewed By : Changsoo Choi  
Manager & Chief Engineer

## TABLE OF CONTENTS

---

<b>SCOPE</b>	<b>3</b>
<b>INTRODUCTION (Site Description)</b>	<b>4</b>
<b>EUT INFORMATION</b>	<b>5</b>
<b>DESCRIPTION OF TESTS (Radiation Hazard)</b>	<b>6</b>
<b>DESCRIPTION OF TESTS (Input Power Measurement)</b>	<b>6</b>
<b>DESCRIPTION OF TESTS (RF Output Power Measurement)</b>	<b>6</b>
<b>DESCRIPTION OF TESTS (Operating Frequency Measurements)</b>	<b>6</b>
<b>DESCRIPTION OF TESTS (Conducted Emissions)</b>	<b>7</b>
<b>DESCRIPTION OF TESTS (Radiated Emissions)</b>	<b>8</b>
<b>TEST DATA (Radiation Hazard)</b>	<b>9</b>
<b>TEST DATA (Input Power Measurement)</b>	<b>9</b>
<b>TEST DATA (RF Output Power Measurement)</b>	<b>9</b>
<b>TEST DATA (Operating Frequency Measurements)</b>	<b>10</b>
<b>TEST DATA (Conducted Emissions)</b>	<b>12</b>
<b>TEST DATA (Radiated Emissions)</b>	<b>13</b>
<b>PLOT OF EMISSIONS (Operating Frequency Measurements)</b>	<b>16</b>
<b>PLOT OF EMISSIONS (Conducted Emissions Diagram)</b>	<b>34</b>
<b>PLOT OF EMISSIONS (Radiated Emissions Diagram)</b>	<b>36</b>
<b>ACCURACY OF MEASUREMENT</b>	<b>41</b>
<b>LIST OF TEST EQUIPMENT</b>	<b>42</b>
<b>APPENDIX A - SAMPLE LABEL</b>	<b>43</b>
<b>APPENDIX B - PHOTOGRAPHS OF TEST SET-UP</b>	<b>44</b>
<b>APPENDIX C - EUT PHOTOGRAPHS</b>	<b>48</b>
<b>APPENDIX D - SCHEMATIC DIAGRAM</b>	<b>64</b>
<b>APPENDIX E - USER'S MANUAL</b>	<b>65</b>
<b>APPENDIX F - BLOCK DIAGRAM</b>	<b>66</b>

## SCOPE

*Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission under FCC part 18.*

**Responsible Party :** Daewoo Electronics Corporation

**Contact Person :** Mr. Seongok Kim

Tel No.: + 82 32 510 7919

**Manufacturer :** Daewoo Electronics Corporation

Kitchen Appliances Div. R&D Center, 412-2,

Cheongcheon2-Dong, Bupyeong-Gu, Incheon, 403-032,

KOREA

**Factory :** Daewoo Microwave Oven Co., Ltd.

Dagang, District, Development Area Tianjin, China

- FCC ID: C5F7NF6LMO700N
- Model: KOR-6L0B3
- Variant Model : KOR-6L\*\*3
- Brand Name: DAEWOO
- EUT Type: Microwave Oven
- Applied Standard: FCC Part 18 & Part 2
- Test Procedure(s): MP-5:1986
- Dates of Test: April 14, 2011 to May 08, 2011
- Place of Tests: Nemko Korea Co., Ltd. EMC Site
- Test Report No.: NK-11-E-253

※The model KOR-6L653 was tested for the representative model.

## INTRODUCTION

The measurement procedure described in MP5:1986 for Methods of Measurement of radiated, powerline conducted radio noise, frequency and power output was used in determining emissions emanating from **Daewoo Electronics Corporation**.

FCC ID : **C5F7NF6LMO700N**, Microwave Oven.


These measurement tests were conducted at **Nemko Korea Co., Ltd. EMC Laboratory**.

The site address is 300-2, Osan-Ri, Mohyun-Myun, Cheoin-Gu, Yongin-City, Gyeonggi-Do, KOREA

The area of Nemko Korea Corporation Ltd. EMC Test Site is located in a mountain area at 80 kilometers (48 miles) southeast and Incheon International Airport (Incheon Airport), 30 kilometers (18miles) south-southeast from central Seoul.

It is located in the valley surrounded by mountains in all directions where ambient radio signal conditions are quiet and a favorable area to measure the radio frequency interference on open field test site for the computing and ISM devices manufactures.

The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2003



Nemko Korea Co., Ltd.  
OPEN AREA TEST SITE  
300-2, Osan-Ri, Mohyun-Myun,  
Cheoin-Gu, Yongin-City  
Gyeonggi-Do, KOREA 449-852  
Tel) + 82 31 330 1700

Fig. 1. The map above shows the Seoul in Korea vicinity area.  
The map also shows Nemko Korea Corporation Ltd. EMC Lab and Incheon Airport.

## ***EUT INFORMATION***

---

### **EUT Information**

Electric Rating :	a.c. 120 V , 60 Hz
Clock :	60 Hz
Magnetron Type :	RM228 (Daewoo)
Operating Frequency :	2.45 GHz

### **Description of the Changes according to FCC part 2.1043**

- ※ KOR-6L\*\*3 is identical with basic model KOR-6L0B3 except for model name, control type and front design.

Note 1) First “\*\*” : 0~9 or A~Z (enclosure design difference)

Note 2) Second “\*\*” : 0~9 (mechanical type) or A~Z (electrical type)

## ***DESCRIPTION OF TESTS***

---

### **Radiation Hazard**

A 700 ml water load was placed in the center of the oven.

The power setting was set to maximum power.

While the oven was operating, the Microwave Survey Meter probe was moved slowly around the door seams to check for leakage.

### **Input Power Measurement**

The EUT was placed on a wooden table 0.8 m at 1 m distance Horn antenna.

A 700ml water load was placed in the center of the oven and the oven set to maximum power. A 700 ml water load was chosen for its compatibility.

Input power and current were measured using a Power Analyzer.

Manufacturers to determine their input ratings commonly use this procedure.

### **Output Power Measurement**

The Caloric Method was used to determine maximum output power.

The initial temperature of a 1000 ml water load was measured. The water load was placed in the center of the oven. The oven was operated at maximum output power for 120 seconds. Then the temperature of the water re-measured.

### **Frequency Measurements**

Following the above test, after operating the oven long enough to assure that stable operating temperature were obtained, the operating frequency was monitored as the input voltage was varied between 80 to 125 percent of the nominal rating.

And the load quantity was reduced by evaporation to approximately 20 % of the original quantity with nominal rating.

## DESCRIPTION OF TESTS

### Conducted Emissions

The Line conducted emission test facility is located inside a 4 x 7 x 2.5 meter shielded enclosure.

It is manufactured by EM engineering. The shielding effectiveness of the shielded room is in accordance with MIL-STD-285 or NSA 65-6.

A 1 m X 1.5 m wooden table 0.4 m height is placed 0.4 m away from the vertical wall and 1.5 m away from the side of wall of the shielded room

Rohde & Schwarz (ESH2-Z5) of the 50 ohm/50 uH Line Impedance Stabilization Network (LISN) is bonded to the shielded room.

The EUT is powered from the Rohde & Schwarz LISN.

Power to the LISN is filtered by high-current high insertion loss Power line filters.

The purpose of filter is to attenuate ambient signal interference and this filter is also bonded to shielded enclosure.

All electrical cables are shielded by tinned copper zipper tubing with inner diameter of 1 / 2 ".

If DC power device, power will be derived from the source power supply it normally will be powered from and this supply lines will be connected to the LISN,

All interconnecting cables more than 1 meter were shortened by non inductive bundling (serpentine fashion) to a 1 meter length.

Sufficient time for EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME from the EUT.

The spectrum was scanned from 150 kHz to 30 MHz with 20 m sec sweep time.

The frequency producing the maximum level was re-examined using the EMI test receiver. (Rohde & Schwarz ESCS30).

The detector function were set to CISPR quasi-peak mode & average mode.

The bandwidth of receiver was set to 9 kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission.

Each EME reported was calibrated using the R&S signal generator.




Fig. 2. LISN Schematic Diagram

## DESCRIPTION OF TESTS

### Radiated Emissions

Preliminary measurement were made indoors at 3 meter using broad band antennas, broadband amplifier, and spectrum analyzer to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The Technology configuration, clock speed, mode of operation or video resolution, turntable azimuth with respect to the antenna was note for each frequency found. The spectrum was scanned from 0.15 to 30 MHz using Loop Antenna (EMCO/6502) and from 30 to 1000 MHz using Biconical log Antenna(ARA, LPB-2520/A).

Above 1 GHz, Double Ridged Broadband Horn antenna (Schwarzbeck, BBHA 9120 D) was used.

Final Measurements were made indoors at 3 m using Loop Antenna (EMCO/6502) for measurement from 0.15 to 30 MHz with RBW 9 kHz & VBW 9 kHz and made indoors at 3 m using Trilog-Broadband Antenna (Shwarzbeck, VULB9168) for measurement from 30 MHz to 1000 MHz with RBW 100 kHz & VBW 100 kHz and made indoors at 3 m using Double Ridged Broadband Horn antenna (Schwarzbeck, BBHA 9120 D) for measurement from 1 GHz to 25 GHz with RBW 1 MHz & VBW 1 MHz.

Each frequency found during pre-scan measurements was reexamined and investigated using EMI test receiver. (FSP40)

The detector function were set to CISPR quasi peak mode and the bandwidth of the receiver were set to 9 kHz, 100 kHz and peak mode 1 MHz depending on the frequency or type of signal.

The Double Ridged Broadband Horn antenna was tuned to the frequency found during preliminary radiated measurements.

The EUT support equipment and interconnecting cables were re-configured to the setup producing the maximum emission for the frequency and were placed on top of a 0.8 m high non- metallic 1.0 X 1.5 meter table.

The EUT, support equipment and interconnecting cables were re-arranged and manipulated to maximize each EME emission.

The EUT is rotated about its vertical axis on the turntable, and the polarization and height of the receiving antenna are varied to obtain the highest field strength on the particular frequency under observation.

Each EME reported was calibrated using the R/S signal generator.




Fig. 3. Dimensions of Outdoor Test Site

## TEST DATA

---

### Radiation Hazard

Probe Location	Maximum Leakage [mW/Cm <sup>2</sup> ]	Limit [mW/Cm <sup>2</sup> ]
A	0.30	1.00
B	0.20	1.00
C	0.20	1.00
D	0.20	1.00
All others	0.20	1.00

### Input Power Measurement

Operation mode	P rated (W)	P (W)	dP (%)	Required dP (%)
Power Input	1100	1107	0.63	+ 15 %

### RF Output Power Measurement

Quantity of Water [ml]	Starting Temperature [Centigrade]	Final Temperature [Centigrade]	Temp. Rise	Elapsed Time [seconds]	RF Power [watts]
1000	10.0	27.3	17.3	120	604

$$\text{RF Power} = \frac{(4.187 \text{ Joules/Cal}) \times (\text{Volume in ml}) \times (\text{Temp. Rise})}{\text{Time in seconds}}$$



---

Tested by : K. W. Kim

## TEST DATA

---

### Operating Frequency measurements

#### ► Frequency vs Line Voltage Variation Test

[ Room Temperature : 25.0 °C ]			
Line Voltage Variation (a.c. V)	*)Pole	Frequency [MHz]	Allowed Tolerance for the ISM Band
96 (80%)	H	Lower : 2439.2	
	H	Upper : 2468.0	
	V	Lower : 2439.2	
	V	Upper : 2457.6	
108 (90%)	H	Lower : 2437.6	
	H	Upper : 2466.0	
	V	Lower : 2430.8	
	V	Upper : 2467.2	
132 (110%)	H	Lower : 2443.6	
	H	Upper : 2466.4	
	V	Lower : 2436.4	
	V	Upper : 2463.6	
150 (125%)	H	Lower : 2431.6	
	H	Upper : 2467.6	
	V	Lower : 2430.4	
	V	Upper : 2467.2	

#### NOTE :

1. \*Pol. H = Horizontal V = Vertical
2. Initial load : 1000 ml of water in the beaker.
3. Line voltage varied from a.c. 96 V to a.c. 150 V.
4. ISM Frequency : 2450 MHz, Tolerance : ± 50 MHz

**RESULT :** Pass



Tested by : K. W. Kim

## TEST DATA

---

### ► Frequency vs Load Variation Test

[ Room Temperature : 25.0 °C ]			
Volume of water (ml)	*)Pole	Frequency [MHz]	Allowed Tolerance for the ISM Band
1000	H	Lower : 2430.8	
	H	Upper : 2464.0	
	V	Lower : 2431.2	
	V	Upper : 2465.6	
800	H	Lower : 2434.4	
	H	Upper : 2464.4	
	V	Lower : 2431.6	
	V	Upper : 2466.8	
600	H	Lower : 2430.8	
	H	Upper : 2463.2	
	V	Lower : 2430.0	
	V	Upper : 2467.2	
400	H	Lower : 2440.8	
	H	Upper : 2469.2	
	V	Lower : 2442.8	
	V	Upper : 2465.2	
200	H	Lower : 2436.8	
	H	Upper : 2471.2	
	V	Lower : 2433.6	
	V	Upper : 2471.6	

#### NOTE :

1. \*Pol. H = Horizontal, V = Vertical
2. The water load was varied between 200 ml to 1000 ml.
3. Frequency was measured by using nominal voltage (a.c. 120 V).
4. ISM Frequency : 2450 MHz, Tolerance : ± 50 MHz

**RESULT :** Pass



Tested by : K. W. Kim

## TEST DATA

---

### Conducted Emissions

FCC ID : C5F7NF6LMO700N

[Room Temperature : 22.0 °C]

Frequency (MHz)	Level(dB $\mu$ V)		Factor (dB)	Line	Limit(dB $\mu$ V)		Margin(dB)	
	Q-Peak	Average			Q-Peak	Average	Q-Peak	Average
0.15	56.2	28.0	0.2	L	66.0	56.0	9.8	28.0
0.16	55.1	27.0	0.2	L	65.5	55.5	10.4	28.5
0.17	53.5	27.1	0.2	L	65.0	55.0	11.5	27.9
0.19	52.4	26.5	0.2	L	64.0	54.0	11.6	27.5
0.25	48.9	20.3	0.2	N	61.8	51.8	12.9	31.5
0.43	41.7	12.0	0.1	L	57.3	47.3	15.6	35.3

### NOTES:

1. Measurements using CISPR quasi-peak mode & average mode.
2. If no frequencies are specified in the tables, no measurement for quasi-peak or average was necessary.
3. See attached Plots.
4. Line : L = Line , N = Neutral
5. The limit for consumer device is on the FCC Part section 18.307(b).



---

Tested by : K. W. Kim

## TEST DATA

---

### Radiated Emissions

FCC ID : C5F7NF6LMO700N

► 0.15 MHz ~ 30 MHz

[Room Temperature : 23.0 °C]

Frequency (MHz)	Reading (dB $\mu$ V)	Pol* (H/V)	AF+CL+Amp (dB)**	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
The level was under 20 dB below limit.						

<Radiated Measurements at 3 meters>

### **NOTES:**

1. \*Pol. H = Horizontal      V = Vertical
2. \*\*AF + CL + Amp. = Antenna Factor + Cable Loss + Amplifier.
3. Distance Correction factor :  $20 * \log (300 / 3) = 40 \text{ dBuV/m}$
4. The limit at 300 meters is  $20 * \log (25 * \text{SQRT (RF Power / 500)})$
5. All other emissions were measured while a 700 ml load was placed in the center of the oven.
6. See attached Plots.
7. The limit for consumer device is on the FCC Part section 18.305.



---

Tested by : K. W. Kim

## TEST DATA

### Radiated Emissions

FCC ID : C5F7NF6LMO700N

► 30 MHz ~ 1 GHz

[Room Temperature : 23.0 °C]

Frequency (MHz)	Reading (dB $\mu$ V/m)	Pol* (H/V)	Antena Heights(cm)	Turntable Angles (°)	AF+CL+Amp (dB)**	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
467.47	30.2	V	130	270	-11.3	18.9	68.8	49.9
517.91	28.1	V	130	300	-8.9	19.2	68.8	49.6
694.45	28.9	H	190	210	-7.4	21.5	68.8	47.3
983.51	27.8	V	130	135	-2.0	25.8	68.8	43.0
985.45	27.9	H	160	135	-2.0	25.9	68.8	42.9
992.24	28.1	H	190	0	-2.0	26.1	68.8	42.7

### **<Radiated Measurements at 3 meters>**

#### **NOTES:**

1. \*Pol. H = Horizontal      V = Vertical
2. \*\*AF + CL + Amp. = Antenna Factor + Cable Loss + Amplifier.
3. Distance Correction factor :  $20 * \log (300/3) \approx 40 \text{ dBuV/m}$
4. The limit at 300 meters is  $20 * \log (25 * \text{SQRT (RF Power/500)})$
5. All other emissions were measured while a 700 ml load was placed in the center of the oven.
6. If no frequencies are specified in the tables, no measurement for peak with RBW 120 kHz & VBW 10 Hz.
7. The limit for consumer device is on the FCC Part section 18.305.



Tested by : K. W. Kim

## TEST DATA

### Radiated Emissions

FCC ID : C5F7NF6LMO700N

► Above 1 GHz

[Room Temperature : 23.0 °C]

Frequency (MHz)	Pol* (H/V)	Antena Heights (cm)	Turntable Angles (°)	Reading Level (dB $\mu$ V)	Total Loss** (dB)	Result at 3 m		K	Results at 300 m ( $\mu$ V/m)	Limits at 300 m ( $\mu$ V/m)
						(dB $\mu$ V/m)	( $\mu$ V/m)			
4286.42	V	160	270	29.9	6.7	36.6	67.6	0.01	0.7	27.5
4919.75	H	130	15	39.2	8.5	47.7	242.7	0.01	2.4	27.5
8402.50	H	130	330	31.6	16.3	47.9	248.3	0.01	2.5	27.5
9838.12	H	130	330	37.3	19.0	56.3	653.1	0.01	6.5	27.5
10109.57	V	160	345	28.1	19.5	47.6	239.9	0.01	2.4	27.5
14760.32	H	160	0	34.6	26.1	60.7	1083.9	0.01	10.8	27.5

**<Radiated Measurements at 3 meters>**

**NOTES:**


1. \* Pol. H =Horizontal      V=Vertical
2. \*\* Total Loss = Antenna Factor + Cable Loss + Amplifier + HPF (High Pass Filter)
3. Field Strength (at 300 m) ( $\mu$ V/m) = K \* 10 [Fieldstrength at 3 m (dBuV/m) / 20]
4. The limit at 300 meters is 25 \* SQRT (RF Power/500)
5. Load for measurement of radiation on second and third harmonic : Two loads, one of 700 ml and the other of 300 ml, of water were used. Each load was tested both with the beaker located in the center of the oven and with it in the corner.
6. The test was performed at peak detector mode with average.
7. If no frequencies are specified in the tables, no measurement for peak with RBW 1 MHz & VBW 10 Hz.
8. The limit for consumer device is on the FCC Part section 18.305.




Tested by : K. W. Kim

## ***PLOTS OF EMISSIONS***

- ***Frequency vs Line Voltage Variation Test***




**Horizontal (96 V, 1000 ml)**




Vertical (96 V, 1000 ml)

## ***PLOTS OF EMISSIONS***

- ***Frequency vs Line Voltage Variation Test***




**Horizontal (108 V, 1000 ml)**




**Vertical (108 V, 1000 ml)**

## ***PLOTS OF EMISSIONS***

- ***Frequency vs Line Voltage Variation Test***




**Horizontal (132 V, 1000 ml)**




**Vertical (132 V, 1000 m)**

## **PLOTS OF EMISSIONS**

- **Frequency vs Line Voltage Variation Test**




**Horizontal (150 V, 1000 ml)**




**Vertical (150 V, 1000 mV)**

## ***PLOTS OF EMISSIONS***

- ***Frequency vs Load Variation Test***




**Horizontal (120 V, 1000 ml)**




**Vertical (120 V, 1000 mV)**

## **PLOTS OF EMISSIONS**

- **Frequency vs Load Variation Test**



**Horizontal (120 V, 800 ml)**




**Vertical (120 V, 800 ml)**

## **PLOTS OF EMISSIONS**

- **Frequency vs Load Variation Test**




**Horizontal (120 V, 600 ml)**




**Vertical (120 V, 600 ml)**

## **PLOTS OF EMISSIONS**

- **Frequency vs Load Variation Test**



**Horizontal (120 V, 400 ml)**


**Vertical (120 V, 400 ml)**

## **PLOTS OF EMISSIONS**

- **Frequency vs Load Variation Test**




**Horizontal (120 V, 200 ml)**



**Vertical (120 V, 200 ml)**


## PLOTS OF EMISSIONS

- Conducted Emission at the Mains port (Line)




## PLOTS OF EMISSIONS

- Conducted Emission at the Mains port (Neutral)



## PLOTS OF EMISSIONS


### • Radiated Emission (0.15 MHz ~ 30 MHz)



(Horizontal)

## PLOTS OF EMISSIONS


### ● Radiated Emission (0.15 MHz ~ 30 MHz)



(Vertical)

## PLOTS OF EMISSIONS

- **Radiated Emission (30 MHz ~ 1 GHz)**



## **ACCURACY OF MEASUREMENT**

---

The Measurement Uncertainties stated were calculated in accordance with the requirements of measurement uncertainty contained in CISPR 16-4-2 with the confidence level of 95%

### **1. Conducted Uncertainty Calculation**

Source of Uncertainty	$Xi$	Uncertainty of $Xi$		Coverage factor $k$	$u(Xi)$ (dB)	$Ci$	$Ci u(Xi)$ (dB)
		Value (dB)	Probability Distribution				
Receiver reading	$RI$	$\pm 0.1$	normal 1	1.000	0.1	1	0.1
Attenuation AMN–Receiver	$LC$	$\pm 0.08$	normal 2	2.000	0.04	1	0.04
AMN Voltage division factor	$LAMN$	$\pm 0.8$	normal 2	2.000	0.4	1	0.4
Sine wave voltage	$dVSW$	$\pm 2.00$	normal 2	2.000	1.00	1	1.00
Pulse amplitude response	$dVPA$	$\pm 1.50$	rectangular	1.732	0.87	1	0.87
Pulse repetition rate response	$dVPR$	$\pm 1.50$	rectangular	1.732	0.87	1	0.87
Noise floor proximity	$dVNF$	$\pm 0.00$			0.00	1	0.00
AMN Impedance	$dZ$	$\pm 1.80$	triangular	2.449	0.73	1	0.73
ⓐ Mismatch	$M$	+ 0.70	U-Shaped	1.414	0.49	1	0.49
ⓑ Mismatch	$M$	- 0.80	U-Shaped	1.414	- 0.56	1	- 0.56
Measurement System Repeatability	$RS$	0.05	normal 1	1.000	0.05	1	0.05
Remark	ⓐ: AMN–Receiver Mismatch : + ⓑ: AMN–Receiver Mismatch : -						
Combined Standard Uncertainty	Normal			$\pm 1.88$			
Expended Uncertainty U	Normal ( $k = 2$ )			$\pm 3.76$			

## 2. Radiation Uncertainty Calculation

Source of Uncertainty	$\chi_i$	Uncertainty of $\chi_i$		Coverage factor $k$	$u(\chi_i)$ (dB)	$C_i$	$C_i u(\chi_i)$ (dB)
		Value (dB)	Probability Distribution				
Receiver reading	$Ri$	$\pm 0.10$	normal 1	1.000	0.10	1	0.10
Sine wave voltage	$dVsw$	$\pm 2.00$	normal 2	2.000	1.00	1	1.00
Pulse amplitude response	$dVpa$	$\pm 1.50$	rectangular	1.732	0.87	1	0.87
Pulse repetition rate response	$dVpr$	$\pm 1.50$	rectangular	1.732	0.87	1	0.87
Noise floor proximity	$dVnf$	$\pm 0.50$	normal 2	2.000	0.25	1	0.25
Antenna Factor Calibration	$AF$	$\pm 1.50$	normal 2	2.000	0.75	1	0.75
Attenuation Antenna-receiver	$CL$	$\pm 0.52$	normal 2	2.000	0.26	1	0.26
Antenna Directivity	$AD$	$\pm 1.00$	rectangular	1.732	0.58	1	0.58
Antenna Factor Height Dependence	$AH$	$\pm 0.50$	rectangular	1.732	0.29	1	0.29
Antenna Phase Centre Variation	$AP$	$\pm 0.30$	rectangular	1.732	0.17	1	0.17
Antenna Factor Frequency Interpolation	$AI$	$\pm 0.30$	rectangular	1.732	0.17	1	0.17
Site Imperfections	$SI$	$\pm 4.00$	triangular	2.449	1.63	1	1.63
Measurement Distance Variation	$DV$	$\pm 0.10$	rectangular	1.732	0.06	1	0.06
Antenna Balance	$Dbal$	$\pm 0.90$	rectangular	1.732	0.52	1	0.52
Cross Polarisation	$DCross$	$\pm 0.90$	rectangular	1.732	0.52	1	0.52
④ Mismatch	$M$	+ 0.25	U-Shaped	1.414	0.18	1	0.18
⑤ Mismatch	$M$	- 0.26	U-Shaped	1.414	- 0.18	1	- 0.18
⑥ Mismatch	$M$	+ 0.98	U-Shaped	1.414	0.69	1	0.69
⑦ Mismatch	$M$	- 1.11	U-Shaped	1.414	- 0.79	1	- 0.79

Measurement System Repeatability	<i>RS</i>	0.09	normal 1	1.000	0.09	1	0.09
Remark	①: Biconical Antenna-receiver Mismatch : + (< 200 MHz) ②: Biconical Antenna-receiver Mismatch : - (< 200 MHz) ③: Log Periodic Antenna-receiver Mismatch : + ( $\geq$ 200 MHz) ④: Log Periodic Antenna-receiver Mismatch : - ( $\geq$ 200 MHz)						
Combined Standard Uncertainty	Normal		$\pm$ 2.63 (< 200 MHz) $\pm$ 2.74 ( $\geq$ 200 MHz)				
Expended Uncertainty U	Normal ( $k = 2$ )		$\pm$ 5.26 (< 200 MHz) $\pm$ 5.48 ( $\geq$ 200 MHz)				

## ***LIST OF TEST EQUIPMENT***

---

No.	Instrument	Manufacturer	Model	Serial No.	Calibration Date	Calibration Interval
1	*Test Receiver	R & S	ESCS 30	833364/020	Jan. 14 2011	1 year
2	*Test Receiver	R & S	ESCS 30	100302	Nov. 10 2010	1 year
3	*Amplifier	HP	8447F	2805A03351	Oct. 06 2010	1 year
4	*Amplifier	Sonoma Instrument	310N	291916	July 20 2010	1 year
5	*Pre Amplifier	HP	8449B	3008A00107	Jan. 13 2011	1 year
6	Spectrum Analyzer	ADVANTEST	R3265A	45060401	July 20 2010	1 year
7	*Spectrum Analyzer	R & S	FSP40	100361	Sep. 02 2010	1 year
8	PSA Series Spectrum Analyzer	Agilent	E4440A	MY44022567	June. 03 2010	1 year
9	*Microwave Survey Meter	ETS-LINDGEN	HI-1801	33549	Jan. 11 2010	2 years
10	*Loop Antenna	EMCO	EMCO/6502	8911-2436	Jan. 19 2010	2 years
11	*Biconical Log Antenna	ARA	LPB-2520/A	1209	Dec. 21 2010	2 years
12	*Trilog-Broadband Antenna	SCHWARZBECK	VULB 9168	9168-257	Apr. 14 2010	2 years
13	*Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA 9120 D	9120D-474	July 14 2010	2 years
14	Signal Generator	R & S	SMP02	833286/003	July 20 2010	1 year
15	LISN	R & S	ESH3-Z5	833874/006	Nov. 11 2010	1 year
16	*LISN	R & S	ESH2-Z5	100227	Apr. 06 2011	1 year
17	*Position Controller	DAEIL EMC	N/A	N/A	N/A	N/A
18	*Turn Table	DAEIL EMC	N/A	N/A	N/A	N/A
19	*Antenna Mast	DAEIL EMC	N/A	N/A	N/A	N/A
20	*Anechoic Chamber	EM Eng.	N/A	N/A	N/A	N/A
21	*Shielded Room	EM Eng.	N/A	N/A	N/A	N/A
22	*Anechoic Chamber	SY Corporation	N/A	N/A	N/A	N/A
23	Shielded Room	SY Corporation	N/A	N/A	N/A	N/A

*\*) Test equipment used during the test*

## APPENDIX D – SCHEMATIC DIAGRAM

---

## APPENDIX E – USER'S MANUAL

---

## ***APPENDIX F – BLOCK DIAGRAM***

---