
FCC Test Report

Report No.: AGC05U120502F1

FCC ID : C89BLIZZARDIII
PRODUCT DESIGNATION : GSM Mobile Phone
BRAND NAME : Ice Mobile
MODEL NAME : Blizzard III
CLIENT : Dynamics Hong Kong Limited
DATE OF ISSUE : June 06, 2012
STANDARD(S) : FCC Part 15 Rules
REPORT VERSION : V1.0

Attestation of Global Compliance Co., Ltd.

CAUTION: This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

TABLE OF CONTENTS

1. VERIFICATION OF COMPLIANCE	2
2. PRODUCT INFORMATION	3
3. TEST FACILITY	4
4. SUPPORT EQUIPMENT LIST	5
5. SYSTEM DESCRIPTION	5
6. TEST MODE	5
7. SUMMARY OF TEST RESULTS	6
8. MEASUREMENT UNCERTAINTY	6
9. FCC LINE CONDUCTED EMISSION TEST	7
9.1 TEST EQUIPMENT OF LINE CONDUCTED EMISSION TEST	7
9.2 LIMITS OF LINE CONDUCTED EMISSION TEST	7
9.3 BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	7
9.4 PROCEDURE OF LINE CONDUCTED EMISSION TEST	8
9.5 TEST RESULT OF LINE CONDUCTED EMISSION TEST	9
10. FCC RADIATED EMISSION TEST	11
10.1 TEST EQUIPMENT OF RADIATED EMISSION	11
10.2 LIMITS OF RADIATED EMISSION TEST	11
10.3 BLOCK DIAGRAM OF RADIATED EMISSION TEST	11
10.4 PROCEDURE OF RADIATED EMISSION TEST	12
10.5 TEST RESULT OF RADIATED EMISSION TEST	13
APPENDIX 1	15
PHOTOGRAPHS OF TEST SETUP	15
APPENDIX 2	16
PHOTOGRAPHS OF EUT	16

1. VERIFICATION OF COMPLIANCE

Applicant:	Dynamics Hong Kong Limited
	Room A4, 3/F, Friend's House, No.6A Carnarvon Road, Tsim Sha Tsui, Kowloon, Hong Kong
Manufacturer:	Dynamics Hong Kong Limited
	Room A4, 3/F, Friend's House, No.6A Carnarvon Road, Tsim Sha Tsui, Kowloon, Hong Kong
Product Designation:	GSM Mobile Phone
Brand name:	Ice Mobile
Test Model:	Blizzard III
FCC ID:	C89BLIZZARDIII
Measurement Procedure:	ANSI C63.4: 2003
File Number:	AGC05U120502F1
Date of test:	June 01, 2012 to June 05, 2012
Deviation:	None
Condition of Test Sample:	Normal

The above equipment was tested by Attestation Of Global Compliance Co., Ltd. for compliance with the requirements set forth in the FCC Rules and Regulations Part 15, the measurement procedure according to ANSI C63.4:2003. This said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment are within the compliance requirements.

The test results of this report relate only to the tested sample identified in this report.

Tested By : Leo Lee
Leo Lee June 06, 2012

Reviewed By : Forrest Lei
Forrest Lei June 06, 2012

Approved By: Solger Zhang
Solger Zhang June 06, 2012

2. PRODUCT INFORMATION

Housing Type: Plastic and Metal
EUT Rating Voltage: DC 3.7V by battery
Adapter Input AC100~240V,50/60Hz,0.15A
Adapter Output DC5.0V,500mA

I/O Port Information (☒Applicable ☐Not Applicable)

I/O Port of EUT			
I/O Port Type	Q'TY	Cable	Tested with
USB port	1	1.0 m, unshielded	1

3. TEST FACILITY

Facility	Attestation of Global Compliance Co., Ltd.
Location:	2F, No.2 Building, Huafeng No.1 Technical, Industrial Park, Sanwei, Xixiang, Baoan District, Shenzhen, China
Description:	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2003.
Site Filing:	The FCC Registration Number is 259865
Instrument Tolerance:	All measuring equipment is in accord with ANSI C63.4 requirements that meet industry regulatory agency and accreditation agency requirement.

4. SUPPORT EQUIPMENT LIST

Device Type	Manufacturer	Model Name	Serial No.	Data Cable	Power Cable
PC	DELL	INSPIRON	--	N/A	1.5m unshielded

**Note: All the above equipment/cables were placed in worse case positions to maximize emission signals during emission test.

5. SYSTEM DESCRIPTION

EUT test procedure:

1. Connect EUT and peripheral devices (PC) through USB port.
2. Power on the EUT, use the software to transfer data between EUT and PC.
3. Make sure the EUT operates normally during the test.

6. TEST MODE

USB (connection for data transferring)

Other modes have been tested via the procedure of Verification of Conformity.

7. SUMMARY OF TEST RESULTS

FCC Rules	Description Of Test	Result
§15.107	Conduction Emission	Compliant
§15.109	Radiated Emission	Compliant

8. MEASUREMENT UNCERTAINTY

The uncertainty is calculated using the methods suggested in the “Guide to the Expression of Uncertainty in Measurement” (GUM) published by ISO.

- Uncertainty of Conducted Emission, $U_c = \pm 2.75\text{dB}$
- Uncertainty of Radiated Emission, $U_c = \pm 3.2\text{dB}$

9. FCC LINE CONDUCTED EMISSION TEST

9.1 TEST EQUIPMENT OF LINE CONDUCTED EMISSION TEST

Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
EMI Test Receiver	H.P.	8546A	N/A	06/27/2011	06/26/2012
LISN	EMCO	3825/2	N/A	06/27/2011	06/26/2012


9.2 LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P.(dBuV)	Average(dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

**Note: 1. The lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

9.3 BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST




9.4 PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2) Support equipment, if needed, was placed as per ANSI C63.4.
- 3) All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4) The EUT connect to PC which received 120V/60Hz power from a LISN.
- 5) The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 6) Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 7) During the above scans, the emissions were maximized by cable manipulation.
- 8) A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions.
- 9) Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.

The test data of the worst case condition(s) was reported on the Summary Data page.

9.5 TEST RESULT OF LINE CONDUCTED EMISSION TEST

LINE CONDUCTED EMISSION - L



Site: Conduction

Phase: **L1**

Temperature: 26

Limit: FCC Class B Conduction(QP)

Power: AC 120V/60Hz

Humidity: 60 %

EUT: GSM Mobile Phone


M/N: Blizzard III

Mode: USB

Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.2379	40.22		30.11	10.26	50.48		40.37	62.17	52.17	-11.69	-11.80	P	
2	0.4660	36.76		29.27	10.38	47.14		39.65	56.58	46.58	-9.44	-6.93	P	
3	0.7459	36.36		22.96	10.32	46.68		33.28	56.00	46.00	-9.32	-12.72	P	
4	0.9418	35.70		21.32	10.39	46.09		31.71	56.00	46.00	-9.91	-14.29	P	
5	1.6818	35.58		22.79	10.32	45.90		33.11	56.00	46.00	-10.10	-12.89	P	
6	16.8379	39.75		27.17	10.13	49.88		37.30	60.00	50.00	-10.12	-12.70	P	

LINE CONDUCTED EMISSION – N



Site: Conduction Phase: **N** Temperature: 26
Limit: FCC Class B Conduction(QP) Power: AC 120V/60Hz Humidity: 60 %
EUT: GSM Mobile Phone
M/N: Blizzard III
Mode:
Note: USB

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.2340	41.46		30.32	10.25	51.71		40.57	62.30	52.30	-10.59	-11.73	P	
2	0.3180	37.63		18.77	10.30	47.93		29.07	59.76	49.76	-11.83	-20.69	P	
3	0.5699	35.73		18.74	10.34	46.07		29.08	56.00	46.00	-9.93	-16.92	P	
4	0.9340	35.13		20.36	10.40	45.53		30.76	56.00	46.00	-10.47	-15.24	P	
5	2.4660	33.09		23.56	10.42	43.51		33.98	56.00	46.00	-12.49	-12.02	P	
6	15.7538	38.78		24.44	10.11	48.89		34.55	60.00	50.00	-11.11	-15.45	P	

10. FCC RADIATED EMISSION TEST

10.1 TEST EQUIPMENT OF RADIATED EMISSION


Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
PSA SERIES SPECTRUM ANALYZER	AGILENT	E4440A	US41421290	06/27/2011	06/26/2012
ANTENNA	A.H.	SAS-521-4	128	06/27/2011	06/26/2012
HORN ANTENNA	EM	EM-AH-10180	N/A	06/27/2011	06/26/2012
AMPLIFIER	EM	EM30180	0607030	06/27/2011	06/26/2012
POSITIONING CONTROLLER	MF	MF-7802	MF780208147	06/27/2011	06/26/2012

10.2 LIMITS OF RADIATED EMISSION TEST

Frequency (MHz)	Distance (m)	Maximum Field Strength Limit (dBuV/m/ Q.P.)
30~88	3	40.0
88~216	3	43.5
216~960	3	46.0
Above 960	3	54.0

**Note: The lower limit shall apply at the transition frequency.

10.3 BLOCK DIAGRAM OF RADIATED EMISSION TEST




10.4 PROCEDURE OF RADIATED EMISSION TEST

- 1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2) Support equipment, if needed, was placed as per ANSI C63.4.
- 3) All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4) The EUT connect to PC which received 120V/60Hz power from socket under the turntable.
- 5) The antenna was placed at 3 meter away from the EUT as stated in FCC Part 15. The antenna connected to the Analyzer via a cable and at times a pre-amplifier would be used.
- 6) The Analyzer / Receiver quickly scanned from 30MHz to 1000MHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- 7) The test mode(s) were scanned during the test.
- 8) Recorded at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and Q.P./Peak reading is presented.

10.5 TEST RESULT OF RADIATED EMISSION TEST

Radiated Emission Test –Horizontal -3m



Site: site #1

Polarization: **Horizontal**

Temperature: 26

Limit: FCC Class B 3M Radiation

Power: AC 120V/60Hz

Humidity: 60 %

EUT: GSM Mobile Phone

Distance: 3m


M/N: Blizzard III

Mode: USB

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		60.7167	29.33	4.06	33.39	40.00	-6.61	peak			
2	*	96.2833	23.76	14.16	37.92	43.50	-5.58	peak			
3		180.3500	25.07	12.05	37.12	43.50	-6.38	peak			
4	!	240.1667	28.21	12.18	40.39	46.00	-5.61	peak			
5		288.6666	22.42	17.11	39.53	46.00	-6.47	peak			
6		432.5500	18.61	21.09	39.70	46.00	-6.30	peak			

Radiated Emission Test –Vertical -3m



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: GSM Mobile Phone
M/N: Blizzard III
Mode: USB
Note:

Polarization: **Vertical**
Power: AC 120V/60Hz
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	60.7167	33.28	1.66	34.94	40.00	-5.06	peak			
2	!	156.1000	21.84	15.83	37.67	43.50	-5.83	peak			
3		240.1667	25.47	14.23	39.70	46.00	-6.30	peak			
4	!	288.6666	23.45	17.11	40.56	46.00	-5.44	peak			
5	!	395.3667	21.52	18.92	40.44	46.00	-5.56	peak			
6		479.4333	17.05	21.67	38.72	46.00	-7.28	peak			

APPENDIX 1 PHOTOGRAPHS OF TEST SETUP

FCC LINE CONDUCTED EMISSION TEST SETUP



FCC RADIATED EMISSION TEST SETUP



APPENDIX 2 PHOTOGRAPHS OF EUT

TOP VIEW OF SAMPLE



BOTTOM VIEW OF SAMPLE



LEFT VIEW OF SAMPLE



RIGHT VIEW OF SAMPLE



FRONT VIEW OF SAMPLE



BACK VIEW OF SAMPLE



ALL VIEW OF SAMPLE




OPEN VIEW OF SAMPLE-1




OPEN VIEW OF SAMPLE-2




OPEN VIEW OF SAMPLE-3




INTERNAL VIEW OF SAMPLE-1




INTERNAL VIEW OF SAMPLE-2



INTERNAL VIEW OF SAMPLE-3



INTERNAL VIEW OF SAMPLE-4



----END OF REPORT----