

FCC PART 15.247


TEST REPORT

For

Dynamics Hong Kong Limited

Room F, 16/F, Block1, Golden Dragon Industrial Center, 152-160 Tai Lin Pai Road, Kwai Chung, N.T.

FCC ID: C89MASH

Report Type: Original Report	Product Type: Mobile Phone
Test Engineer: Lion Xiao	
Report Number: RDG150326001-00A	
Report Date: 2015-04-10	
Reviewed By: Sula Huang RF Leader	
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
EUT EXERCISE SOFTWARE	5
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
EXTERNAL CABLE.....	5
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE	8
APPLICABLE STANDARD	8
FCC §15.203 - ANTENNA REQUIREMENT.....	9
APPLICABLE STANDARD	9
ANTENNA CONNECTOR CONSTRUCTION	9
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	10
APPLICABLE STANDARD	10
MEASUREMENT UNCERTAINTY	10
EUT SETUP	10
EMI TEST RECEIVER SETUP.....	11
TEST PROCEDURE	11
CORRECTED AMPLITUDE & MARGIN CALCULATION	11
TEST EQUIPMENT LIST AND DETAILS.....	12
TEST RESULTS SUMMARY	12
TEST DATA	12
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	15
APPLICABLE STANDARD	15
MEASUREMENT UNCERTAINTY	15
EUT SETUP	15
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	16
TEST PROCEDURE	16
TEST EQUIPMENT LIST AND DETAILS.....	17
CORRECTED AMPLITUDE & MARGIN CALCULATION	17
TEST RESULTS SUMMARY	17
TEST DATA	17
FCC §15.247(a) (1) - CHANNEL SEPARATION TEST	26
APPLICABLE STANDARD	26
TEST EQUIPMENT LIST AND DETAILS.....	26
TEST PROCEDURE	26
TEST DATA	26
FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING.....	32

APPLICABLE STANDARD	32
TEST PROCEDURE	32
TEST EQUIPMENT LIST AND DETAILS.....	32
TEST DATA	32
FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST	38
APPLICABLE STANDARD	38
TEST PROCEDURE	38
TEST EQUIPMENT LIST AND DETAILS.....	38
TEST DATA	38
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	42
APPLICABLE STANDARD	42
TEST PROCEDURE	42
TEST EQUIPMENT LIST AND DETAILS.....	42
TEST DATA	42
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	58
APPLICABLE STANDARD	58
TEST PROCEDURE	58
TEST EQUIPMENT LIST AND DETAILS.....	58
TEST DATA	58
FCC §15.247(d) - BAND EDGES TESTING	64
APPLICABLE STANDARD	64
TEST PROCEDURE	64
TEST EQUIPMENT LIST AND DETAILS.....	64
TEST DATA	64
DECLARATION LETTER.....	68

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Dynamics Hong Kong Limited*'s product, model number: *MASH (FCC ID: C89MASH)* (the "EUT") in this report was a *Mobile Phone*, which was measured approximately: 11 cm (L) x 6.3 cm (W) x 1.3 cm (H), rated input voltage: DC 3.7V rechargeable Li-ion battery or DC5V charging from adapter.

Adapter information:

Model: RING MASH

Input: AC100-240V, 50-60Hz, 150mA

Output: DC5V, 500mA

Note: The series product, model MASH, RING MASH are electrically identical, the difference between them is just the model name, we selected MASH for fully testing, the details was explained in the attached declaration letter.

All measurement and test data in this report was gathered from production sample serial number: 150326001 (Assigned by BACL, Dongguan). The EUT was received on 2015-03-27.

Objective

This report is prepared on behalf of *Dynamics Hong Kong Limited* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules

The tests were performed in order to determine the Bluetooth BDR and EDR mode of EUT compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: C89MASH.

FCC Part 22H, 24E PCE submissions with FCC ID: C89MASH.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

EUT Exercise Software

Test Software Version		Engineering Mode		
Test Frequency		2402MHz	2441MHz	2480MHz
Power Level Setting	GFSK	N/A	N/A	N/A
	$\pi/4$ -DQPSK	N/A	N/A	N/A
	8DPSK	N/A	N/A	N/A

Equipment Modifications

No modification was made to the EUT.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

External Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From	To
Adapter Cable	No	No	0.75	Adapter	EUT
Earphone Cable	No	No	1.20	Audio port of EUT	Earphone

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(1)	20 dB Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band Edges	Compliance

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v05r02:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

The maximum conducted output power = -2.73dBm (0.53 mW) at 2441 MHz
 $[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})] [\sqrt{f(\text{GHz})}]$
 $= 0.53/5 \cdot (\sqrt{2.441}) = 0.166 < 3.0$

So the stand-alone SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one integral antenna arrangement, which was permanently attached and the antenna gain is 0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.46 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cisp}

Measurement	U_{cisp}
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

V_C : corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF : voltage division factor of AMN or ISN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2014-10-20	2015-10-20
R&S	L.I.S.N	ESH2-Z5	892107/021	2014-06-09	2015-06-09
R&S	Two-line V-network	ENV 216	3560.6550.12	2014-12-11	2015-12-11
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

12.1 dB at 0.450448 MHz in the **Neutral** conducted mode


Test Data**Environmental Conditions**

Temperature:	23.8 °C
Relative Humidity:	60 %
ATM Pressure:	101.7 kPa

The testing was performed by Lion Xiao on 2015-03-27.


Test Mode: Charging&Transmitting

AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.429420	34.3	9.000	L1	10.2	23.0	57.3	Compliance
0.454052	37.3	9.000	L1	10.2	19.5	56.8	Compliance
0.681699	28.7	9.000	L1	10.4	27.3	56.0	Compliance
0.952654	29.2	9.000	L1	10.4	26.8	56.0	Compliance
1.239175	32.5	9.000	L1	10.4	23.5	56.0	Compliance
1.310256	32.7	9.000	L1	10.4	23.3	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.429420	24.5	9.000	L1	10.2	22.8	47.3	Compliance
0.450448	30.0	9.000	L1	10.2	16.9	46.9	Compliance
1.239175	26.5	9.000	L1	10.4	19.5	46.0	Compliance
1.310256	27.7	9.000	L1	10.4	18.3	46.0	Compliance
1.331304	26.0	9.000	L1	10.4	20.0	46.0	Compliance
1.407671	23.3	9.000	L1	10.4	22.7	46.0	Compliance

AC120 V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.429420	42.6	9.000	N	10.2	14.7	57.3	Compliance
0.450448	44.8	9.000	N	10.2	12.1	56.9	Compliance
0.720803	33.7	9.000	N	10.4	22.3	56.0	Compliance
0.922769	33.7	9.000	N	10.4	22.3	56.0	Compliance
1.430284	34.1	9.000	N	10.4	21.9	56.0	Compliance
2.538519	30.6	9.000	N	10.5	25.4	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.429420	32.5	9.000	N	10.2	14.8	47.3	Compliance
0.450448	33.7	9.000	N	10.2	13.2	46.9	Compliance
0.676289	23.4	9.000	N	10.4	22.6	46.0	Compliance
0.975701	25.6	9.000	N	10.4	20.4	46.0	Compliance
1.239175	29.0	9.000	N	10.4	17.0	46.0	Compliance
1.310256	29.7	9.000	N	10.4	16.3	46.0	Compliance

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:

30M~200MHz: 5.0 dB

200M~1GHz: 6.2 dB

1G~6GHz: 4.45 dB


6G~18GHz: 5.23 dB


Table 1 – Values of U_{cisp}

Measurement	U_{cisp}
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

EUT Setup

Below 1GHz:



Above 1GHz:

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2014-05-09	2015-05-09
Sunol Sciences	Antenna	JB3	A060611-3	2014-11-06	2017-11-05
HP	Amplifier	8447E	2434A02181	2014-09-01	2015-09-01
Agilent	Spectrum Analyzer	E4440A	SG43360054	2014-12-04	2015-12-04
ETS-Lindgren	Horn Antenna	3115	000 527 35	2012-09-06	2015-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2015-02-19	2016-02-19
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2014-06-16	2017-06-15
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2014-09-06	2015-09-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, and section 15.205, 15.209 and 15.247, with the worst margin reading of:

4.98 dB at 2390 MHz in the Horizontal polarization of EDR Mode ($\pi/4$ -DQPSK)

Test Data**Environmental Conditions**

Temperature:	23.6 °C
Relative Humidity:	66 %
ATM Pressure:	101.3 kPa

The testing was performed by Lion Xiao on 2015-04-10.

Test Mode: Transmitting

BDR Mode (GFSK):


Frequency	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	FCC 15.247	
(MHz)	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBμV/m)	Margin (dB)
Low Channel: 2402 MHz									
2402	59.36	PK	H	25.65	3.66	0.00	88.67	N/A	N/A
2402	49.17	AV	H	25.65	3.66	0.00	78.48	N/A	N/A
2402	57.36	PK	V	25.65	3.66	0.00	86.67	N/A	N/A
2402	46.38	AV	V	25.65	3.66	0.00	75.69	N/A	N/A
2390	33.35	PK	H	25.61	3.63	0.00	62.59	74.00	11.41
2390	18.65	AV	H	25.61	3.63	0.00	47.89	54.00	6.11
4804	34.38	PK	H	30.59	5.06	27.41	42.62	74.00	31.38
4804	22.17	AV	H	30.59	5.06	27.41	30.41	54.00	23.59
7206	31.48	PK	H	34.09	6.61	25.91	46.27	74.00	27.73
7206	19.37	AV	H	34.09	6.61	25.91	34.16	54.00	19.84
9608	30.46	PK	H	35.96	8.53	27.55	47.40	74.00	26.60
9608	18.21	AV	H	35.96	8.53	27.55	35.15	54.00	18.85
1369	34.47	PK	H	23.26	3.14	26.97	33.90	74.00	40.10
1369	21.58	AV	H	23.26	3.14	26.97	21.01	54.00	32.99
267.2	40.57	QP	H	13.53	2.01	21.50	34.61	46.00	11.39
Middle Channel: 2441 MHz									
2441	60.03	PK	H	25.75	3.76	0.00	89.54	N/A	N/A
2441	49.62	AV	H	25.75	3.76	0.00	79.13	N/A	N/A
2441	57.83	PK	V	25.75	3.76	0.00	87.34	N/A	N/A
2441	46.96	AV	V	25.75	3.76	0.00	76.47	N/A	N/A
4882	34.95	PK	H	30.79	5.19	27.42	43.51	74.00	30.49
4882	22.64	AV	H	30.79	5.19	27.42	31.20	54.00	22.80
7323	32.1	PK	H	34.38	6.75	25.88	47.35	74.00	26.65
7323	20.02	AV	H	34.38	6.75	25.88	35.27	54.00	18.73
9764	31.06	PK	H	36.33	8.62	27.20	48.81	74.00	25.19
9764	18.63	AV	H	36.33	8.62	27.20	36.38	54.00	17.62
1369	34.89	PK	H	23.26	3.14	26.97	34.32	74.00	39.68
1369	22.07	AV	H	23.26	3.14	26.97	21.50	54.00	32.50
2534	33.48	PK	H	25.99	4.09	27.39	36.17	74.00	37.83
2534	21.17	AV	H	25.99	4.09	27.39	23.86	54.00	30.14
267.2	40.66	QP	H	13.53	2.01	21.50	34.70	46.00	11.30
High Channel: 2480 MHz									
2480	60.58	PK	H	25.85	3.68	0.00	90.11	N/A	N/A
2480	50.14	AV	H	25.85	3.68	0.00	79.67	N/A	N/A
2480	58.25	PK	V	25.85	3.68	0.00	87.78	N/A	N/A
2480	47.58	AV	V	25.85	3.68	0.00	77.11	N/A	N/A
2483.5	27.54	PK	H	25.86	3.67	0.00	57.07	74.00	16.93
2483.5	15.28	AV	H	25.86	3.67	0.00	44.81	54.00	9.19
4960	35.37	PK	H	31.00	5.34	27.43	44.28	74.00	29.72
4960	23.25	AV	H	31.00	5.34	27.43	32.16	54.00	21.84
7440	32.79	PK	H	34.66	6.89	25.97	48.37	74.00	25.63
7440	20.5	AV	H	34.66	6.89	25.97	36.08	54.00	17.92
9920	31.69	PK	H	36.71	8.71	26.66	50.45	74.00	23.55
9920	19.27	AV	H	36.71	8.71	26.66	38.03	54.00	15.97
1369	35.45	PK	H	23.26	3.14	26.97	34.88	74.00	39.12
1369	22.63	AV	H	23.26	3.14	26.97	22.06	54.00	31.94
267.2	40.5	QP	H	13.53	2.01	21.50	34.54	46.00	11.46

EDR Mode ($\pi/4$ -DQPSK):


Frequency	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	FCC 15.247	
(MHz)	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBμV/m)	Margin (dB)
Low Channel: 2402 MHz									
2402	60.41	PK	H	25.65	3.66	0.00	89.72	N/A	N/A
2402	48.22	AV	H	25.65	3.66	0.00	77.53	N/A	N/A
2402	58.47	PK	V	25.65	3.66	0.00	87.78	N/A	N/A
2402	46.32	AV	V	25.65	3.66	0.00	75.63	N/A	N/A
2390	34.53	PK	H	25.61	3.63	0.00	63.77	74.00	10.23
2390	19.78	AV	H	25.61	3.63	0.00	49.02	54.00	4.98
4804	35.51	PK	H	30.59	5.06	27.41	43.75	74.00	30.25
4804	23.36	AV	H	30.59	5.06	27.41	31.60	54.00	22.40
7206	32.45	PK	H	34.09	6.61	25.91	47.24	74.00	26.76
7206	20.39	AV	H	34.09	6.61	25.91	35.18	54.00	18.82
9608	31.59	PK	H	35.96	8.53	27.55	48.53	74.00	25.47
9608	19.38	AV	H	35.96	8.53	27.55	36.32	54.00	17.68
2534	35.41	PK	H	25.99	4.09	27.39	38.10	74.00	35.90
2534	22.68	AV	H	25.99	4.09	27.39	25.37	54.00	28.63
267.2	40.39	QP	H	13.53	2.01	21.50	34.43	46.00	11.57
Middle Channel: 2441 MHz									
2441	61.06	PK	H	25.75	3.76	0.00	90.57	N/A	N/A
2441	49.52	AV	H	25.75	3.76	0.00	79.03	N/A	N/A
2441	58.82	PK	V	25.75	3.76	0.00	88.33	N/A	N/A
2441	46.88	AV	V	25.75	3.76	0.00	76.39	N/A	N/A
4882	36.08	PK	H	30.79	5.19	27.42	44.64	74.00	29.36
4882	23.56	AV	H	30.79	5.19	27.42	32.12	54.00	21.88
7323	33.16	PK	H	34.38	6.75	25.88	48.41	74.00	25.59
7323	21.13	AV	H	34.38	6.75	25.88	36.38	54.00	17.62
9764	32.02	PK	H	36.33	8.62	27.20	49.77	74.00	24.23
9764	19.64	AV	H	36.33	8.62	27.20	37.39	54.00	16.61
2534	35.93	PK	H	25.99	4.09	27.39	38.62	74.00	35.38
2534	23.24	AV	H	25.99	4.09	27.39	25.93	54.00	28.07
2535	34.68	PK	H	25.99	4.10	27.39	37.38	74.00	36.62
2535	22.09	AV	H	25.99	4.10	27.39	24.79	54.00	29.21
267.2	40.27	QP	H	13.53	2.01	21.50	34.31	46.00	11.69
High Channel: 2480 MHz									
2480	61.66	PK	H	25.85	3.68	0.00	91.19	N/A	N/A
2480	48.06	AV	H	25.85	3.68	0.00	77.59	N/A	N/A
2480	59.44	PK	V	25.85	3.68	0.00	88.97	N/A	N/A
2480	46.72	AV	V	25.85	3.68	0.00	76.25	N/A	N/A
2483.5	28.58	PK	H	25.86	3.67	0.00	58.11	74.00	15.89
2483.5	16.46	AV	H	25.86	3.67	0.00	45.99	54.00	8.01
4960	36.46	PK	H	31.00	5.34	27.43	45.37	74.00	28.63
4960	24.21	AV	H	31.00	5.34	27.43	33.12	54.00	20.88
7440	33.92	PK	H	34.66	6.89	25.97	49.50	74.00	24.50
7440	21.51	AV	H	34.66	6.89	25.97	37.09	54.00	16.91
9920	32.76	PK	H	36.71	8.71	26.66	51.52	74.00	22.48
9920	20.3	AV	H	36.71	8.71	26.66	39.06	54.00	14.94
2534	36.48	PK	H	25.99	4.09	27.39	39.17	74.00	34.83
2534	23.57	AV	H	25.99	4.09	27.39	26.26	54.00	27.74
267.2	40.17	QP	H	13.53	2.01	21.50	34.21	46.00	11.79

EDR Mode (8DPSK):

Frequency	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	FCC 15.247	
(MHz)	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBμV/m)	Margin (dB)
Low Channel: 2402 MHz									
2402	60.06	PK	H	25.65	3.66	0.00	89.37	N/A	N/A
2402	48.02	AV	H	25.65	3.66	0.00	77.33	N/A	N/A
2402	58.26	PK	V	25.65	3.66	0.00	87.57	N/A	N/A
2402	46.04	AV	V	25.65	3.66	0.00	75.35	N/A	N/A
2390	34.4	PK	H	25.61	3.63	0.00	63.64	74.00	10.36
2390	19.57	AV	H	25.61	3.63	0.00	48.81	54.00	5.19
4804	35.35	PK	H	30.59	5.06	27.41	43.59	74.00	30.41
4804	23.26	AV	H	30.59	5.06	27.41	31.50	54.00	22.50
7206	32.17	PK	H	34.09	6.61	25.91	46.96	74.00	27.04
7206	20.18	AV	H	34.09	6.61	25.91	34.97	54.00	19.03
9608	31.34	PK	H	35.96	8.53	27.55	48.28	74.00	25.72
9608	19.02	AV	H	35.96	8.53	27.55	35.96	54.00	18.04
5241	35.14	PK	H	31.58	5.28	27.07	44.93	74.00	29.07
5241	22.41	AV	H	31.58	5.28	27.07	32.20	54.00	21.80
267.2	40.64	QP	H	13.53	2.01	21.50	34.68	46.00	11.32
Middle Channel: 2441 MHz									
2441	60.93	PK	H	25.75	3.76	0.00	90.44	N/A	N/A
2441	49.34	AV	H	25.75	3.76	0.00	78.85	N/A	N/A
2441	58.65	PK	V	25.75	3.76	0.00	88.16	N/A	N/A
2441	46.5	AV	V	25.75	3.76	0.00	76.01	N/A	N/A
4882	35.93	PK	H	30.79	5.19	27.42	44.49	74.00	29.51
4882	23.22	AV	H	30.79	5.19	27.42	31.78	54.00	22.22
7323	33.04	PK	H	34.38	6.75	25.88	48.29	74.00	25.71
7323	20.77	AV	H	34.38	6.75	25.88	36.02	54.00	17.98
9764	31.87	PK	H	36.33	8.62	27.20	49.62	74.00	24.38
9764	19.44	AV	H	36.33	8.62	27.20	37.19	54.00	16.81
5241	35.55	PK	H	31.58	5.28	27.07	45.34	74.00	28.66
5241	23.12	AV	H	31.58	5.28	27.07	32.91	54.00	21.09
3762	34.49	PK	H	29.38	4.57	27.36	41.08	74.00	32.92
3762	21.69	AV	H	29.38	4.57	27.36	28.28	54.00	25.72
267.2	40.72	QP	H	13.53	2.01	21.50	34.76	46.00	11.24
High Channel: 2480 MHz									
2480	61.33	PK	H	25.85	3.68	0.00	90.86	N/A	N/A
2480	47.88	AV	H	25.85	3.68	0.00	77.41	N/A	N/A
2480	59.21	PK	V	25.85	3.68	0.00	88.74	N/A	N/A
2480	46.37	AV	V	25.85	3.68	0.00	75.90	N/A	N/A
2483.5	28.46	PK	H	25.86	3.67	0.00	57.99	74.00	16.01
2483.5	16.13	AV	H	25.86	3.67	0.00	45.66	54.00	8.34
4960	36.28	PK	H	31.00	5.34	27.43	45.19	74.00	28.81
4960	23.82	AV	H	31.00	5.34	27.43	32.73	54.00	21.27
7440	33.57	PK	H	34.66	6.89	25.97	49.15	74.00	24.85
7440	21.24	AV	H	34.66	6.89	25.97	36.82	54.00	17.18
9920	32.37	PK	H	36.71	8.71	26.66	51.13	74.00	22.87
9920	19.91	AV	H	36.71	8.71	26.66	38.67	54.00	15.33
5241	36.26	PK	H	31.58	5.28	27.07	46.05	74.00	27.95
5241	23.38	AV	H	31.58	5.28	27.07	33.17	54.00	20.83
267.2	40.91	QP	H	13.53	2.01	21.50	34.95	46.00	11.05


Conducted Spurious Emissions at Antenna Port*BDR Mode (GFSK):***Low Channel**

Date: 10.APR.2015 03:45:41


Middle Channel

Date: 10.APR.2015 03:46:21


High Channel

EDR Mode ($\pi/4$ -DQPSK):


Low Channel



Middle Channel




High Channel




EDR Mode (8DPSK):


Low Channel



Middle Channel



High Channel



FCC §15.247(a) (1) - CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another trace
3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	25.1 °C
Relative Humidity:	51 %
ATM Pressure:	101.4 kPa

* The testing was performed by Lion Xiao on 2015-04-10.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting


Mode	Channel	Frequency MHz	Channel Separation MHz	Limit MHz	Result
BDR (GFSK)	Low	2402	1.002	0.561	Pass
	Adjacent	2403			
	Middle	2441	1.002	0.561	Pass
	Adjacent	2442			
	High	2480	1.002	0.561	Pass
	Adjacent	2479			
EDR ($\pi/4$ -DQPSK)	Low	2402	1.002	0.759	Pass
	Adjacent	2403			
	Middle	2441	1.002	0.759	Pass
	Adjacent	2442			
	High	2480	1.002	0.759	Pass
	Adjacent	2479			
EDR (8DPSK)	Low	2402	1.002	0.783	Pass
	Adjacent	2403			
	Middle	2441	1.002	0.783	Pass
	Adjacent	2442			
	High	2480	1.002	0.783	Pass
	Adjacent	2479			

Note: Limit= (2/3)*20 dB Bandwidth


BDR Mode (GFSK):



Middle Channel




High Channel




EDR Mode ($\pi/4$ -DQPSK):


Low Channel



Middle Channel




High Channel




EDR Mode (8DPSK):


Low Channel



Middle Channel



High Channel



FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING**Applicable Standard**

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	25.1 °C
Relative Humidity:	51 %
ATM Pressure:	101.4 kPa

* The testing was performed by Lion Xiao on 2015-04-10.

Test Result: Compliance.


Please refer to following tables and plots

Mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
BDR Mode (GFSK)	Low	2402	0.842
	Middle	2441	0.842
	High	2480	0.842
EDR Mode ($\pi/4$ -DQPSK):	Low	2402	1.138
	Middle	2441	1.134
	High	2480	1.134
EDR Mode (8DPSK):	Low	2402	1.174
	Middle	2441	1.174
	High	2480	1.174


BDR Mode (GFSK):



Middle Channel




High Channel




EDR Mode ($\pi/4$ -DQPSK):

Low Channel




Date: 10.APR.2015 02:46:25

Middle Channel




Date: 10.APR.2015 02:47:37

High Channel




EDR Mode (8-DPSK):


Low Channel



Middle Channel



High Channel



FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST**Applicable Standard**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	25.1 °C
Relative Humidity:	51 %
ATM Pressure:	101.4 kPa

* The testing was performed by Lion Xiao on 2015-04-10.


Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting


BDR Mode (GFSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15




EDR Mode ($\pi/4$ -DQPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥ 15



EDR Mode (8DPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15



FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as $0.4 \times \text{channel no. (s)}$, the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell Time= time slot length * hope rate/ number of hopping channels * 31.6s

Hop rate=1600/s

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	25.1 °C
Relative Humidity:	51 %
ATM Pressure:	101.4 kPa

* The testing was performed by Lion Xiao on 2015-04-10.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting


BDR Mode (GFSK):

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH1	Low	0.389	0.124	0.4	Pass
	Middle	0.389	0.124	0.4	Pass
	High	0.389	0.124	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s				
DH3	Low	1.651	0.264	0.4	Pass
	Middle	1.651	0.264	0.4	Pass
	High	1.651	0.264	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/4/79) $\times$ 31.6 s				
DH5	Low	2.914	0.311	0.4	Pass
	Middle	2.914	0.311	0.4	Pass
	High	2.914	0.311	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/6/79) $\times$ 31.6 s				


DH1: Low Channel




DH1: Middle Channel




DH1: High Channel




DH3: Low Channel




DH3: Middle Channel




DH3: High Channel




DH5: Low Channel



DH5: Middle Channel




DH5: High Channel



EDR Mode ($\pi/4$ -DQPSK):

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH1	Low	0.395	0.126	0.4	Pass
	Middle	0.395	0.126	0.4	Pass
	High	0.395	0.126	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s				
DH3	Low	1.651	0.264	0.4	Pass
	Middle	1.651	0.264	0.4	Pass
	High	1.651	0.264	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/4/79) $\times$ 31.6 s				
DH5	Low	2.914	0.311	0.4	Pass
	Middle	2.914	0.311	0.4	Pass
	High	2.914	0.311	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/6/79) $\times$ 31.6 s				

DH1: Low Channel



[illegible]

Ref Lvl 10 dBm

Delta 1 [T1] -1.58 dB

RBW 1 MHz

VBW 3 MHz

SWT 1 ms

RF Att 20 dB

Unit dBm

1 dB Offset

1 [T1] -62.62 dBm


394.789579 μs

Center 2.48 GHz


100 μs

Date: 10.APR.2015 04:10:20


DH3: Low Channel




DH3: Middle Channel




DH3: High Channel




DH5: Low Channel



DH5: Middle Channel




DH5: High Channel




EDR Mode (8-DPSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH1	Low	0.395	0.126	0.4	Pass
	Middle	0.395	0.126	0.4	Pass
	High	0.395	0.126	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s				
DH3	Low	1.651	0.264	0.4	Pass
	Middle	1.651	0.264	0.4	Pass
	High	1.651	0.264	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/4/79) $\times$ 31.6 s				
DH5	Low	2.914	0.311	0.4	Pass
	Middle	2.914	0.311	0.4	Pass
	High	2.914	0.311	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/6/79) $\times$ 31.6 s				

DH1: Low Channel


DH1: Middle Channel




DH1: High Channel



DH3: Low Channel



DH3: Middle Channel



[illegible]

Ref Lvl 10 dBm

Delta 1 [T1] -0.05 dB

RBW 1 MHz

VBW 3 MHz

SWT 5 ms

RF Att 20 dB

Unit dBm

1 dB Offset

TR

Center 2.402 GHz

500 μ s

1 [T1] -60.11 dBm

1 [T1] -35.470942 μ s

1 [T1] -0.05 dB

1 [T1] 2.913828 ms


SGL

TRG


IMA

Date: 10.APR.2015 04:24:46

DH5: Middle Channel



DH5: High Channel



FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT**Applicable Standard**

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI test receiver.
3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	25.1 °C
Relative Humidity:	51 %
ATM Pressure:	101.4 kPa

* *The testing was performed by Lion Xiao on 2015-04-10.*


Test Result: Compliance.

Test Mode: Transmitting


Mode	Channel	Frequency (MHz)	Output power (dBm)	Limit (dBm)
BDR Mode (GFSK)	Low	2402	-2.95	30
	Middle	2441	-2.73	30
	High	2480	-2.79	30
EDR Mode ($\pi/4$ -DQPSK)	Low	2402	-3.52	30
	Middle	2441	-3.28	30
	High	2480	-3.32	30
EDR Mode (8-DPSK)	Low	2402	-3.43	30
	Middle	2441	-3.09	30
	High	2480	-3.15	30

Note: The data above was tested in conducted mode.


BDR Mode (GFSK):



Output Power, Middle Channel




Output Power, High Channel




EDR Mode ($\pi/4$ -DQPSK):

Output Power, Low Channel




Date: 10.APR.2015 02:39:15

Output Power, Middle Channel




Date: 10.APR.2015 02:38:44

Output Power, High Channel




EDR Mode (8DPSK):


Output Power, Low Channel



Output Power, Middle Channel



Output Power, High Channel



FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25.1 °C
Relative Humidity:	51 %
ATM Pressure:	101.4 kPa

* The testing was performed by Lion Xiao on 2015-04-10.

BDR Mode (GFSK):

Ref Lvl 10 dBm

Marker 1 [T1] -3.10 dBm

RBW 100 kHz RF Att 20 dB

VBW 300 kHz

SWT 6 ms Unit dBm

Marker	Type	Freq (GHz)	Power (dBm)
T1	[T1]	2.40186874	-3.10
T2	[T1]	2.40000000	-59.98
T3	[T1]	2.40000000	-64.26
T4	[T1]	2.39997495	-58.57

D1 -3.1 dBm

D2 -23.1 dBm

Start 2.38 GHz Stop 2.4025 GHz

Date: 10.APR.2015 03:13:42

Ref Lvl 10 dBm

Marker 1 [T1] -2.90 dBm

RBW 100 kHz

VBW 300 kHz

SWT 8 ms

RF Att 20 dB

Unit dBm

1 dB Offset

01 -2.9 dBm

02 -22.9 dBm

11A

11A

1 [T1] -2.90 dBm 2.47980561 GHz

2 [T1] -63.87 dBm 2.48350000 GHz

3 [T1] -65.82 dBm 2.50000000 GHz

4 [T1] -60.97 dBm 2.48426754 GHz

F1



F2

Start 2.4795 GHz

3.05 MHz

Stop 2.51 GHz

Date: 10.APR.2015 03:11:24

*EDR Mode ($\pi/4$ -DQPSK):***Band Edge, Left Side****Band Edge, Right Side**

Band Edge, Left Side



DECLARATION LETTER**Dynamics Hong Kong Limited****Declaration of Alteration**

To Whom It May Concern,

We, Dynamics Hong Kong Limited hereby declare that there are some differences between our Multiple Models and testing model. Details as below:

Products	Name	Mobile Phone	
Description	Project No.	RDG150326001, RDG150326001-20	
Differences Description			
Testing model	Multiple Models	Differences Items	Details
MASH	RING MASH	Model name	The multiple model just have different model name from the testing model

Notes: Testing model-the product's model tested by BACL

Multiple Model- have the same or similar appearance, structure, PCB, Material and function to the testing product's model, and only are different for model name.

Besides the differences in the table above, we declare the products are identical

We guarantee all the information provided above is true, and notice that we'll bear all the consequences caused by any false information or concealing.

Best Regards,

Signature

Print Name: Rajendra Kumar Thapa

Title: Director

Add: Room F, 16/F, Block1, Golden Dragon Industrial Center, 152-160 Tai Lin Pai Road, Kwai Chung, N.T.
Tel. 00852-23111980 and Fax. 00852-23111979

QPDG004R32 Version1.0 (20140717)

***** END OF REPORT *****