

TEST REPORT

Report Number: 101941214LEX-003
Project Number: G101941214

Report Issue Date: 3/10/15

Product Name: Qollector Activity Monitor

Standards: FCC Part 22H & Part 24E


Tested by:
Intertek Testing Services NA, Inc.
731 Enterprise Drive
Lexington, KY 40510

Client:
SRAM
1333 North Kingsbury
4th Floor
Chicago, IL 60622

Report prepared by


Jason Centers, Staff Engineer

Report reviewed by


Bryan Taylor, Team Leader

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.



TABLE OF CONTENTS

1	<i>Introduction and Conclusion</i>	3
2	<i>Test Summary</i>	3
3	<i>Description of Equipment Under Test</i>	4
4	<i>Radiated Spurious Emissions (Transmitter).....</i>	6
5	<i>Measurement Uncertainty</i>	10
6	<i>Revision History.....</i>	11

1 Introduction and Conclusion

The tests indicated in section 2 were performed on the product constructed as described in section 3. The remaining test sections are the verbatim text from the actual data sheets used during the investigation. These test sections include the test name, the specified test method, a list of the actual test equipment used, documentation photos, results and raw data. No additions, deviations, or exclusions have been made from the standard(s) unless specifically noted.

Based on the results of our investigation, we have concluded the product tested complied with the requirements of the standard(s) indicated. The results obtained in this test report pertain only to the item(s) tested.

The INTERTEK-Lexington is located at 731 Enterprise Drive, Lexington Kentucky, 40510. The radiated emission test site is a 10-meter semi-anechoic chamber. The chamber meets the characteristics of CISPR 16-1 and ANSI C63.4. For measurements, a remotely controlled flush-mount metal-top turntable is used to rotate the EUT a full 360 degrees. A remote controlled non-conductive antenna mast is used to scan the antenna height from one to four meters. The test site is listed with the FCC under registration number 485103. The test site is listed with Industry Canada under site number IC 2042M-1.

2 Test Summary

Page	Test full name	FCC Reference	IC Reference	Result
-	Radiated Power	§ 22.913(a) and § 24.232(c)	RSS-132 (4.4), RSS-133 (4.1) RSS-133 (6.4)	Note ¹
6	Radiated Spurious Emissions (Transmitter)	§2.1053, §22.917(a)(b), and §24.238(a)(b)	RSS-132 (4.5), RSS-133 (6.5)	Pass
-	Conducted Output Power	§2.1046 §24.232(d)	RSS-129 (9.2.2) RSS-133 (4.1) RSS-133 (6.4)	Note ²
-	Occupied Bandwidth	§2.1049, §22.917(b)(d), and §24.238(a)	RSS-GEN (4.6.1) RSS-133 (2.3)	Note ²
-	Conducted Spurious Emissions at Antenna Terminals	§2.1049, §2.1051, §22.917(a)(b), and § 24.238(a)(b)	RSS-129 (8.1.1), RSS-129 (9.3), RSS-129 (9.4), RSS-133 (6.5.1)	Note ²
-	Frequency Stability	§2.1055, §22.355, and §24.235	RSS-129 (9.2.1), RSS-133 (6.3)	Note ²
-	Receiver Spurious Emissions	§ 15.109	RSS-129 (10), RSS-Gen (7.2.3.2) RSS-129 (10)	Note ²
-	AC Powerline Conducted Emissions	§ 15.107	RSS-Gen (7.2.2)	Note ²

¹ See module test report exhibit.

² See module test report exhibit.

3 Description of Equipment Under Test

Equipment Under Test	
Manufacturer	SRAM
Model Number	Qollector2
Serial Number	Not Labeled
Receive Date	12/17/14
Test Start Date	12/17/14
Test End Date	12/31/14
Device Received Condition	Good
Test Sample Type	Production
Frequency Band	824MHz - 849MHz (CDMA Cell Band) 1850MHz – 1910MHz (CDMA PCS Band)
Modulation Type	CDMA
Transmission Control	Base Station Simulator
Test Channels	1013, 384, and 777 (CDMA Cell Band) 25, 600, and 1075 (CDMA PCS Band)
Antenna Type	PCB
Antenna Gain	1.49 dBi – Cell Band 2.3 dBi – PCS Band
Operating Voltage	12Vdc


Description of Equipment Under Test
Activity Monitor.

Operating modes of the EUT:

No.	Descriptions of EUT Exercising
1	Transmitting a CDMA signal
2	Receive / idle mode

3.1 System setup including cable interconnection details, support equipment and simplified block diagram

3.2 EUT Block Diagram:



Block Diagram for Radiated Tests

3.3 Cables:

Cables					
Description	Length	Shielding	Ferrites	Connection	
				From	To
USB Cable	6ft	Yes	Yes	EUT	USB-AC Power Adapter

3.4 Support Equipment:

No support equipment was used during the evaluation. The Collector Activity Monitor was tested in a stand-alone configuration.

4 Radiated Spurious Emissions (Transmitter)

4.1 Test Limits

§ 2.1053

- (a) Measurements shall be made to detect spurious emissions that may be radiated directly from the cabinet, control circuits, power leads, or intermediate circuit elements under normal conditions of installation and operation. Curves or equivalent data shall be supplied showing the magnitude of each harmonic and other spurious emission. For this test, single sideband, independent sideband, and controlled carrier transmitters shall be modulated under the conditions specified in paragraph (c) of §2.1049, as appropriate. For equipment operating on frequencies below 890 MHz, an open field test is normally required, with the measuring instrument antenna located in the far-field at all test frequencies. In the event it is either impractical or impossible to make open field measurements (e.g. a broadcast transmitter installed in a building) measurements will be accepted of the equipment as installed. Such measurements must be accompanied by a description of the site where the measurements were made showing the location of any possible source of reflections which might distort the field strength measurements. Information submitted shall include the relative radiated power of each spurious emission with reference to the rated power output of the transmitter, assuming all emissions are radiated from halfwave dipole antennas.

§ 22.917

- (a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.
- (b) Measurement procedure. Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 100 kHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

§ 24.238

- (a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.
- (b) Measurement procedure. Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 1 MHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

4.2 Test Procedure

The EUT was placed on a non-conductive turntable. The measurement antenna was placed at a distance of 3 meters from the EUT. The EUT was forced to transmit at its maximum output power setting. During the tests, the antenna height and EUT azimuth were varied in order to identify the maximum level of emissions from the EUT.

The frequency range up to tenth harmonic was investigated in order to identify the spurious emission. Once the spurious emissions were identified, the power of the emission was determined using the substitution method described in TIA-603-C. The spurious emissions attenuation was calculated as the difference between radiated power at the fundamental frequency and at the spurious emissions frequency.

4.3 Test Equipment Used:

Description	Serial Number	Manufacturer	Model	Cal. Date	Cal. Due
EMI Test Receiver	1302.6005.40	Rohde&Schwarz	ESU40	9/17/2014	9/17/2015
Preamplifier	122005	Rohde&Schwarz	TS-PR18	11/26/2014	11/26/2015
Horn Antenna	00156319	ETS	3117	5/2/2014	5/2/2015
Bilog Antenna	2564	Schaffner	CBL6111C	4/21/2014	4/21/2015
System Controller	121701-1	Sunol Sciences	SC99V	Time of Use	Time of Use
High Pass Filter	1	Wainwright	WHKX12-2533.85-2710-18000-40SS	Time of Use	Time of Use
High Pass Filter	25	Wainwright	WHKX12-1028.5-1100-1500-40SS	Time of Use	Time of Use
Base Station Simulator	2522	Rohde&Schwarz	CMU200	9/19/2014	9/19/2015

4.4 Results:

All radiated spurious emissions were attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB which is equivalent to -13dBm. Each operational mode was investigated and the RC3/SO55 configuration yielded the highest measurement.

Worst Case Spurious Measurements (Cell Band)

Radiated Spurious Emissions Measurement								
Test Engineer: Bryan Taylor								
Test Date: 12/29/2014								
Temp. / Humidity / Pressure: 23.7C/27.4%/988.9mBar								
Bandwidth Settings: RBW = VBW = 1MHz								
Notes:			Results represent the worst case from 3 orthogonal axis positions. Spurious emissions not reported here were below the measurement noise floor.					
			A	B	C	D	E	F
Band/Channel	Spurious Frequency (MHz)	Polarity	Device Reading (dBm)	Signal Generator Level (dBm)	Cable Loss (dB)	Tx Antenna Gain (dBd)	Limit (dBm)	Radiated Spurious Emission Level (dBm)
CDMA Cell Band; Low Channel (1013)	1649.4	H	-72.09	-64.56	3.26	5.64	-13	-62.18
	1649.4	V	-71.82	-63.39	3.26	5.64	-13	-61.01
	2474.1	H	-74.1	-62.67	4.17	5.87	-13	-60.97
	2474.1	V	-74.68	-61.8	4.17	5.87	-13	-60.10
	3298.8	H	-65.01	-52.59	4.58	7.32	-13	-49.86
	3298.8	V	-65.22	-52.41	4.58	7.32	-13	-49.68
	4123.5	H	-79.75	-66.08	5.33	8.91	-13	-62.50
	4123.5	V	-79.81	-66.13	5.33	8.91	-13	-62.55
	4948.2	H	-81.21	-65.44	5.82	9.90	-13	-61.36
CDMA Cell Band; Mid Channel (384)	4948.2	V	-81.16	-65.41	5.82	9.90	-13	-61.33
	1673.04	H	-73.82	-65.47	3.30	5.64	-13	-63.13
	1673.04	V	-71.98	-62.87	3.30	5.64	-13	-60.53
	2509.56	H	-74.75	-62.78	3.97	5.65	-13	-61.10
	2509.56	V	-74.6	-61.03	3.97	5.65	-13	-59.35
	3346.08	H	-69.25	-56.64	4.63	7.67	-13	-53.60
	3346.08	V	-68.91	-55.89	4.63	7.67	-13	-52.85
	4182.6	H	-79.72	-65.93	5.19	8.91	-13	-62.21
	4182.6	V	-79.61	-65.73	5.19	8.91	-13	-62.01
CDMA Cell Band; High Channel (777)	5019.12	H	-81.16	-65.81	6.19	9.99	-13	-62.01
	5019.12	V	-81.05	-65.66	6.19	9.99	-13	-61.86
	1696.62	H	-73.13	-64.35	3.48	5.64	-13	-62.19
	1696.62	V	-72.08	-62.14	3.48	5.64	-13	-59.98
	2544.93	H	-75.13	-63.24	4.09	5.65	-13	-61.68
	2544.93	V	-74.71	-61.55	4.09	5.65	-13	-59.99
	3393.24	H	-65.86	-53.01	4.84	7.67	-13	-50.18
	3393.24	V	-62.72	-49.34	4.84	7.67	-13	-46.51
	4241.55	H	-80.17	-66.03	5.00	9.01	-13	-62.02
	4241.55	V	-80.27	-66.06	5.00	9.01	-13	-62.05
	5089.86	H	-81.36	-65.9	6.25	9.99	-13	-62.16
	5089.86	V	-81.42	-65.58	6.25	9.99	-13	-61.84
								F=B-C+D

Worst Case Spurious Measurements (PCS Band)

Radiated Spurious Emissions Measurement								
Test Engineer: Bryan Taylor								
Test Date: 12/29/2014								
Temp. / Humidity / Pressure: 23.7C/27.4%/988.9mBar								
Bandwidth Settings: RBW = VBW = 1MHz								
Notes: Results represent the worst case from 3 orthogonal axis positions. Spurious emissions not reported here were below the measurement noise floor.								
			A	B	C	D	E	F
Band/Channel	Spurious Frequency (MHz)	Polarity	Device Reading (dBm)	Signal Generator Level (dBm)	Cable Loss (dB)	Tx Antenna Gain (dBd)	Limit (dBm)	Radiated Spurious Emission Level (dBm)
CDMA PCS Band; Low Channel (25)	3702.5	H	-61.79	-47.64	4.85	8.26	-13	-44.23
	3702.5	V	-69.71	-55.86	4.85	8.26	-13	-52.45
	5553.75	H	-72.55	-56.69	6.91	10.40	-13	-53.21
	5553.75	V	-75.04	-59.13	6.91	10.40	-13	-55.65
	7405	H	-73.8	-55.47	7.75	11.84	-13	-51.38
	7405	V	-75.94	-57.96	7.75	11.84	-13	-53.87
	9256.25	H	-82.33	-62.75	9.21	13.19	-13	-58.77
	9256.25	V	-82.62	-62.96	9.21	13.19	-13	-58.98
	11107.5	H	-83.67	-60.08	10.47	13.23	-13	-57.32
CDMA PCS Band; Mid Channel (600)	11107.5	V	-83.41	-60.02	10.47	13.23	-13	-57.26
	3760	H	-60.64	-45.59	5.20	8.26	-13	-42.53
	3760	V	-65.53	-50.73	5.20	8.26	-13	-47.67
	5640	H	-73.71	-58.49	7.09	10.56	-13	-55.02
	5640	V	-75.31	-59.99	7.09	10.56	-13	-56.52
	7520	H	-73.59	-54.98	8.01	11.93	-13	-51.07
	7520	V	-77.32	-58.97	8.01	11.93	-13	-55.06
	9400	H	-83.25	-62.72	9.15	13.12	-13	-58.76
	9400	V	-83.41	-62.81	9.15	13.12	-13	-58.85
CDMA PCS Band; High Channel (1175)	11280	H	-84.13	-59.8	10.16	13.26	-13	-56.70
	11280	V	-83.9	-59.82	10.16	13.26	-13	-56.72
	3817.5	H	-53.26	-38.55	5.00	8.25	-13	-35.30
	3817.5	V	-54.65	-40.3	5.00	8.25	-13	-37.05
	5726.25	H	-76.48	-59.35	7.06	10.66	-13	-55.75
	5726.25	V	-79.93	-62.87	7.06	10.66	-13	-59.27
	7635	H	-73.47	-55.48	8.15	11.98	-13	-51.65
	7635	V	-76.24	-58.27	8.15	11.98	-13	-54.44
	9543.75	H	-83.18	-62.37	8.41	13.09	-13	-57.70
	9543.75	V	-83.31	-62.28	8.41	13.09	-13	-57.61
	11452.5	H	-84.45	-59.36	9.51	13.25	-13	-55.62
	11452.5	V	-83.77	-59.03	9.51	13.25	-13	-55.29
								F=B-C+D

5 Measurement Uncertainty

The measured value related to the corresponding limit will be used to decide whether the equipment meets the requirements.

The measurement uncertainty figures were calculated and correspond to a coverage factor of $k = 2$, providing a confidence level of respectively 95.45 % in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian).

Measurement uncertainty Table

Parameter	Uncertainty	Notes
Radiated emissions, 30 to 1000 MHz	+3.9dB	
Radiated emissions, 1 to 18 GHz	+4.2dB	
Radiated emissions, 18 to 40 GHz	+4.3dB	
Power Port Conducted emissions, 150kHz to 30 MHz	+2.8dB	

6 Revision History

Revision Level	Date	Report Number	Notes
0	3/10/15	101941214LEX-003	Original Issue