

8. RADIO FREQUENCY EXPOSURE

8.1. Limit

According to §1.1310 and §2.1091 RF exposure is calculated.

Table: Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Power Density (S) (mW/cm²)
0.3–1.34	*(100)
1.34–30	*(180/f ²)
30–300	0.2
300–1500	f/1500
1500–100,000	1.0

F = frequency in MHz

* = Plane-wave equivalent power density

Maximum Permissible Exposure

The MPE was calculated at 20cm to show compliance with the power density limit.

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna.

Note:

1. Manufacturer declared that the maximum antenna gain is 0.0dBi(Max.).
2. Manufacturer declared that the nearest distance between human and the EUT is 20cm.
3. Only record worst case data.

Bluetooth

Test Mode	Channel	Frequency (MHz)	ANT Power (dBm)	ANT Power Tune Up (dBm)
GFSK	Low	2402	-1.21	-2.0±1.0
	Middle	2441	-1.25	-2.0±1.0
	High	2480	-1.18	-2.0±1.0
$\pi/4$ -DQPSK	Low	2402	-2.24	-3.0±1.0
	Middle	2441	-2.35	-3.0±1.0
	High	2480	-2.29	-3.0±1.0
8-DPSK	Low	2402	-3.14	-4.0±1.0
	Middle	2441	-3.38	-4.0±1.0
	High	2480	-3.25	-4.0±1.0

8.2 Test Results**Bluetooth**

Test Mode	Channel	ANT Max. Tune Up Power (mW)	ANT MPE (mW/cm ²)	Limit (mW/cm ²)
GFSK	Low	0.7943	0.000158	1.0
	Middle	0.7943	0.000158	1.0
	High	0.7943	0.000158	1.0
$\pi/4$ -DQPSK	Low	0.6310	0.000126	1.0
	Middle	0.6310	0.000126	1.0
	High	0.6310	0.000126	1.0
8-DPSK	Low	0.5012	0.000100	1.0
	Middle	0.5012	0.000100	1.0
	High	0.5012	0.000100	1.0

Antenna Gain (typical): 0 dBi, 1.0(numeric)

Prediction distance: >=20cm

The power density level worst case at 20 cm is below the uncontrolled exposure limit.