

LABORATORY TEST REPORT

RADIO PERFORMANCE MEASUREMENTS

for the

TBCB1E BASE STATION Transceiver

Tested in accordance with:

FCC 47 CFR Parts 22, 74 and 90

RSS-119 Issue 12
RSS-Gen Issue 4

Report Revision:

1

Issue Date:

01 June 2016

PREPARED BY:

Aaron Fan

Test Technician

CHECKED & APPROVED BY:

M. C. James

Laboratory Technical Manager



OATS FCC LISTING REGISTRATION: 837095
OATS IC LISTING REGISTRATION: SITE# 737A-1

All tests reported herein have been performed in accordance with the laboratory's scope of accreditation.

This document must not be reproduced except in full, without the written permission of the Compliance Laboratory Manager

TELTEST Laboratories (A Division of Tait Communications)
PO Box 1645, 558 Wairakei Road, Christchurch, New Zealand.

Telephone: 64 3 358 3399
FAX: 64 3 359 4632

TABLE OF CONTENTS

REVISION	3
INTRODUCTION	4
STATEMENT OF COMPLIANCE	5
MODULATION TYPES, NECESSARY BANDWIDTH & EMISSION DESIGNATORS	6
TEST RESULTS.....	7
TRANSMITTER OCCUPIED BANDWIDTH AND SPECTRUM MASKS	7
TEST EQUIPMENT LIST.....	15
ANNEX A – TEST SETUP DETAILS.....	16

REVISION

Date	Revision	Comments
1 June 2016	1	Initial test report

INTRODUCTION

Type approval testing of the TBCB1E, 100 Watt, BASE STATION transceiver in order to demonstrate compliance with FCC 47 Parts 22, 74 & 90, and RSS-119 Issue 12 & RSS-Gen Issue 4. This Class-2 Permissive Change report adds FFSK to the list of modulations supported. The original test report is TARF 3377. This report only applies to frequencies covered by the TBCB3Y reciter (148MHz to 174MHz)

in accordance with:

FCC 47 CFR Parts 22, 74 and 90
RSS-119 Issue 12 & RSS-Gen Issue 4

REPORT PREPARED FOR

Tait Ltd
245 Wooldridge Road
Harewood
Christchurch 8051
New Zealand

DESCRIPTION OF SAMPLE

Manufacturer: Tait Limited
Equipment: BASE STATION Transceiver
Type: TBCB1E
Quantity: 1

FFSK tests were performed using a 511 bit pseudo-random sequence.
Data rate: 1200 bits/second

HARDWARE & SOFTWARE

Description	Product Code	Serial Number	Firmware Version	Hardware Version
Reciter	T01-01105-DAZY	18221342	dmr-trunk.20160523T175409	0
Power Amplifier	T01-01136-CBAA	18218549	314	1
PMU	TBA30A0-0100	18217789	316	1
Front Panel	T01-01110-CCAA	18218672	0.01.00.trunk.408941.20160413 T151044.0002	0.04

TEST CONDITIONS

All testing was performed on 1 June 2016, and under the following conditions:

Ambient temperature: 15°C → 30°C
Relative Humidity: 20% → 75%
Standard Test Voltage 120 V_{AC}

STATEMENT OF COMPLIANCE

We, TELTEST LABORATORIES of 558 Wairakei Road, Christchurch, New Zealand, declare under our sole responsibility that the product:

Equipment: BASE STATION Transceiver
Type: TBCB1E
With reciter: TBCB3Y (148 to 174 MHz)
Quantity: 1 of each

Consisting Of:

HARDWARE & SOFTWARE

Description	Product Code	Serial Number	Firmware Version	Hardware Version
Reciter	T01-01105-DAZY	18221342	dmr-trunk.20160523T175409	0
Power Amplifier	T01-01136-CBAA	18218549	314	1
PMU	TBA30A0-0100	18217789	316	1
Front Panel	T01-01110-CCAA	18218672	0.01.00.trunk.408941.20160413 T151044.0002	0.04

to which this declaration relates, is in conformity with the following standards:

FCC 47 CFR Parts 22, 74 and 90

RSS-119 Issue 12 & RSS-Gen Issue 4

Signature: _____

Mike James
Technical Manager

Date: _____

MODULATION TYPES, NECESSARY BANDWIDTH & EMISSION DESIGNATORS

MODULATION TYPES:

F2D Fast Frequency Shift Keying 1200 symbols/sec 1200 bps

EMISSION DESIGNATORS:

Channel Spacing 12.5 kHz	
FFSK	7K60F2D

CALCULATIONS

Fast Frequency Shift Keying (FFSK – 1200 bps) 12.5 kHz Channel Spacing

Necessary bandwidth

M = 1.8 kHz

D = 2.0 kHz

$$B_n = (2 \times 1.8) + (2 \times 2.0) \times 1 \\ = 7.6 \text{ kHz}$$

Emission Designator

7K60F2D

F2D represents a FM data transmission with the use of a modulating sub carrier

TEST RESULTS

TRANSMITTER OCCUPIED BANDWIDTH AND SPECTRUM MASKS

SPECIFICATION: FCC 47 CFR 2.1049 (c) RSS-119 5.5

GUIDE: TIA/EIA-603D 2.2.11

MEASUREMENT PROCEDURE:

1. Refer Annex A for Equipment Set up.
2. For analogue measurements: The EUT was modulated by a 2500 Hz tone at an input level 16 dB above a level that produced 50% deviation. The input level was established at the frequency of maximum response of the audio modulating circuit.
3. The Occupied Bandwidth was measured on the Spectrum Analyser, with bandwidth settings as follows.

Emission Mask D – Resolution Bandwidth = 100 Hz, Video Bandwidth = 1 kHz

MEASUREMENT RESULTS:

See the plots on the following pages for 12.5 kHz channel spacing.

LIMIT CLAUSE: FCC 47 CFR 90.210 RSS-119 5.5

EMISSION MASKS


Emission Mask D 12.5 kHz Channel Spacing FFSK

Occupied Bandwidth and Spectrum Masks


FFSK

SPECIFICATION: FCC CFR 2.1049 (c) Mask- D RSS-119 5.5 Mask-D

Tx FREQUENCY: 148.1 MHz 100W & 10 W 12.5 kHz Channel Spacing



FFSK 148.1000MHz Mask D 100W
RBW=100Hz, VBW=1000Hz, Detector Mode=Peak
Result=Pass




FFSK 148.1000MHz Mask D 10W
RBW=100Hz, VBW=1000Hz, Detector Mode=Peak
Result=Pass


Occupied Bandwidth and Spectrum Masks

FFSK

SPECIFICATION: FCC CFR 2.1049 (c) Mask- D RSS-119 5.5 Mask-D
Tx FREQUENCY: 149.8 MHz 100W & 10 W 12.5 kHz Channel Spacing



FFSK 149.8000MHz Mask D 100W
RBW=100Hz, VBW=1000Hz, Detector Mode=Peak
Result=Pass




FFSK 149.8000MHz Mask D 10W
RBW=100Hz, VBW=1000Hz, Detector Mode=Peak
Result=Pass


Occupied Bandwidth and Spectrum Masks

FFSK

SPECIFICATION: FCC CFR 2.1049 (c) Mask- D RSS-119 5.5 Mask-D
Tx FREQUENCY: 151.1 MHz 100W & 10 W 12.5 kHz Channel Spacing



FFSK 151.1000MHz Mask D 100W
RBW=100Hz, VBW=1000Hz, Detector Mode=Peak
Result=Pass




FFSK 151.1000MHz Mask D 10W
RBW=100Hz, VBW=1000Hz, Detector Mode=Peak
Result=Pass


Occupied Bandwidth and Spectrum Masks

FFSK

SPECIFICATION: FCC CFR 2.1049 (c) Mask- D RSS-119 5.5 Mask-D
Tx FREQUENCY: 153.1 MHz 100W & 10 W 12.5 kHz Channel Spacing



FFSK 153.1000MHz Mask D 100W
RBW=100Hz, VBW=1000Hz, Detector Mode=Peak
Result=Pass




FFSK 153.1000MHz Mask D 10W
RBW=100Hz, VBW=1000Hz, Detector Mode=Peak
Result=Pass


Occupied Bandwidth and Spectrum Masks

FFSK

SPECIFICATION: FCC CFR 2.1049 (c) Mask- D RSS-119 5.5 Mask-D
Tx FREQUENCY: 155.1 MHz 100W & 10 W 12.5 kHz Channel Spacing



FFSK 155.1000MHz Mask D 100W
RBW=100Hz, VBW=1000Hz, Detector Mode=Peak
Result=Pass




FFSK 155.1000MHz Mask D 10W
RBW=100Hz, VBW=1000Hz, Detector Mode=Peak
Result=Pass


Occupied Bandwidth and Spectrum Masks

FFSK

SPECIFICATION: FCC CFR 2.1049 (c) Mask- D RSS-119 5.5 Mask-D
Tx FREQUENCY: 159.1 MHz 100W & 10 W 12.5 kHz Channel Spacing



FFSK 159.1000MHz Mask D 100W
RBW=100Hz, VBW=1000Hz, Detector Mode=Peak
Result=Pass




FFSK 159.1000MHz Mask D 10W
RBW=100Hz, VBW=1000Hz, Detector Mode=Peak
Result=Pass


Occupied Bandwidth and Spectrum Masks

FFSK

SPECIFICATION: FCC CFR 2.1049 (c) Mask- D RSS-119 5.5 Mask-D
Tx FREQUENCY: 173.1 MHz 100W & 10 W 12.5 kHz Channel Spacing



FFSK 173.1000MHz Mask D 100W
RBW=100Hz, VBW=1000Hz, Detector Mode=Peak
Result=Pass



FFSK 173.1000MHz Mask D 10W
RBW=100Hz, VBW=1000Hz, Detector Mode=Peak
Result=Pass

TEST EQUIPMENT LIST

Equipment Type	Information	Manufacturer	Model No	Serial No#	Tait ID	Cal Due
Power Supply	AC Variac	Yamabishi	S-260-5	TX-533	E1737	
Spectrum Analyser	13.2GHz	Hewlett Packard	HP8562E	3821A00779	E3715	15-Oct-16
RF Attenuator	30dB 350W	Weinschel	67-30-33	BR0531	E4280	18-Oct-16
Coax Cable	2m Black	Suhner	RG214HF/Nm/Nm/2000	TeltestBlack5	E4850	16-Oct-16
Coax Cable	2m Black	Suhner	RG214HF/Nm/Nm/2000	TeltestBlack6	E4849	16-Oct-16

NOTE: Items without calibration dates are calibrated immediately before use, or set using calibrated instruments.

ANNEX A – TEST SETUP DETAILS

All testing is performed using the Teltest Radio **EVAL**uation system (TREVA), which is configured as shown below. The Spectrum Analyser is connected to the EUT via the attenuator network for Conducted Emissions testing, and Occupied Bandwidth.

