


Transmitter Audio Frequency Response – Pre-emphasis


SPECIFICATION: FCC CFR 2.1047 (a)

Tx FREQUENCY: 460.0 MHz 12.5 kHz Channel Spacing



SPECIFICATION: FCC CFR 2.1047 (a)

Tx FREQUENCY: 468.0 MHz 12.5 kHz Channel Spacing




Transmitter Audio Frequency Response – Pre-emphasis

SPECIFICATION: FCC CFR 2.1047 (a)

Tx FREQUENCY: 469.9 MHz


12.5 kHz Channel Spacing



SPECIFICATION: FCC CFR 2.1047 (a)

Tx FREQUENCY: 479.9 MHz

12.5 kHz Channel Spacing



TRANSMITTER MODULATION LIMITING

SPECIFICATION: FCC 47 CFR 2.1047 (b)

GUIDE: TIA/EIA-603E 2.2.3

MEASUREMENT PROCEDURE:

1. Refer Annex A for Equipment set up.
2. The modulation response was measured at three audio frequencies while varying the input level.
3. Measurements were made for both Positive and Negative Deviation.

MEASUREMENT RESULTS:

See the plots on the following pages for 12.5 kHz channel spacing.

LIMIT CLAUSE: TIA/EIA-603E 1.3.4.4


MEASUREMENT UNCERTAINTY: $\pm 1.5 \%$

Transmitter Modulation Limiting

SPECIFICATION: FCC CFR 2.1047 (b)

Tx FREQUENCY: 440.1 MHz


12.5 kHz Channel Spacing



SPECIFICATION: FCC CFR 2.1047 (b)

Tx FREQUENCY: 450.1 MHz

12.5 kHz Channel Spacing




Transmitter Modulation Limiting

SPECIFICATION: FCC CFR 2.1047 (b)

Tx FREQUENCY: 454.9 MHz

12.5 kHz Channel Spacing



SPECIFICATION: FCC CFR 2.1047 (b)

Tx FREQUENCY: 456.1 MHz

12.5 kHz Channel Spacing

