


### Transmitter Modulation Limiting

SPECIFICATION: FCC CFR 2.1047 (b)

Tx FREQUENCY: 460.0 MHz


12.5 kHz Channel Spacing



SPECIFICATION: FCC CFR 2.1047 (b)

Tx FREQUENCY: 468.0 MHz

12.5 kHz Channel Spacing




### Transmitter Modulation Limiting

SPECIFICATION: FCC CFR 2.1047 (b)

Tx FREQUENCY: 469.9 MHz


12.5 kHz Channel Spacing



SPECIFICATION: FCC CFR 2.1047 (b)

Tx FREQUENCY: 479.9 MHz

12.5kHz Channel Spacing



## TRANSMITTER 99% EMISSION BANDWIDTH

SPECIFICATION: RSS-119 5.5

GUIDE: RSS-Gen 6.7

### MEASUREMENT PROCEDURE:

1. Refer Annex A for Equipment Set up.
2. For analog measurements: The EUT was modulated by a 2500 Hz tone at an input level 16 dB above a level that produced 50% deviation. The input level was established at the frequency of maximum response of the audio modulating circuit.  
For Data measurements: The EUT was modulated with an internally generated pseudo random bit sequence at the appropriate Baud rates.
3. The Occupied Bandwidth was measured on the Spectrum Analyser.

### MEASUREMENT RESULTS:

Channel Spacing (MHz)	Channel Spacing (kHz)	Bandwidths (kHz)		
		Analog	FFSK 1200 bps	DMR
440.1	12.5	9.97	6.95	7.42
450.1	12.5	9.97	6.92	7.35
454.9	12.5	9.97	7.07	7.43
456.1	12.5	9.97	6.98	7.47
460.0	12.5	9.97	6.95	7.42
468.0	12.5	9.97	7.02	7.43
469.9	12.5	9.97	6.97	7.47
479.9	12.5	9.97	7.00	7.40
Limit Authorized Bandwidth 47 CFR 90.209 RSS 119 5.5		11.25	11.25	11.25
Necessary BW used in emission designator		11.0	7.6	7.6
Result		Pass	Pass	Pass