

LABORATORY TEST REPORT

TEST: FCC 47 CFR 1.1310 Maximum Permissible Exposure (MPE)

MPE ASSESSMENT

For the 30 Watt Mobile Transceiver Type TMBL3B
FCC ID: CASTMBL3B
IC: 737A-TMBL3B

In accordance with

ANSI/IEEE Std C95.1

KDB 447498 v05

DATE:	30 June 2015	
PREPARED BY:	L. M. White	<i>Test Technician</i>
CHECKED & APPROVED BY:	M. C. James	<i>Laboratory Technical Manager</i>

*This document must not be reproduced except in full, without the written permission
of the Compliance Laboratory Manager.*

Contents

CONTENTS	2
REVISION HISTORY	2
DESCRIPTION OF SAMPLE:	3
SUMMARY OF RESULTS:	3
OPERATING AND EXPOSURE CONDITIONS:	3
LIMITS:	4
RECOMMENDED ANTENNAS:	4
MEASUREMENT GUIDANCE:	4
TEST RESULTS:	5
TEST EQUIPMENT USED:	7
INFORMATION TO BE PLACED IN USER/INSTALLATION MANUAL:	8
APPENDIX 1	10

Revision History

Date	Revisio	Comments
30 June 2015	1	Initial test report

Description of Sample:

Manufacturer: Tait Limited
Equipment: Mobile Transceiver
Type: TMBL3B
Product Code: T02-00012-YPAA
Serial Number(s): 20288278
Frequency Range: 896-901 / 935-940 MHz
Quantity: 1

Summary of Results:

Limit: 47 CFR 1.1310
RSS-102 issue 5

Antenna Gain	Antenna Position	Measurement Position	Result-USA	Result-Canada
2.15 dBi	Roof	A External: Side	COMPLIES	COMPLIES
8 dBi	Roof	A External: Side	COMPLIES	COMPLIES
2.15 dBi	Trunk	C External: Rear	COMPLIES	COMPLIES
8 dBi	Trunk	C External: Rear	COMPLIES	COMPLIES
2.15 dBi	Trunk	B External: 45 degrees	COMPLIES	COMPLIES
8 dBi	Trunk	B External: 45 degrees	COMPLIES	COMPLIES
2.15 dBi	Roof	Internal: Front Seat	COMPLIES	COMPLIES
8 dBi	Roof	Internal: Front Seat	COMPLIES	COMPLIES
2.15 dBi	Roof	Internal: Back Seat	COMPLIES	COMPLIES
8 dBi	Roof	Internal: Back Seat	COMPLIES	COMPLIES

See Appendix A for details of the measurement positions.

Operating and Exposure Conditions:

Operating Conditions: Mobile transmitter using vehicle mounted antennas only.
Exposure conditions: Occupational/Controlled Exposure (operator).
General Population/Uncontrolled (passengers and bystanders)
Safe Distance: Recommended minimum lateral safe distance from the antenna: 90 cm

Limits:

47 CFR 1.1310

	896MHz	916.5MHz (Test Frequency)	940MHz
Occupational/Controlled Exposure: $f/300 \text{ mW/cm}^2$	3.0mW/cm ²	3.1mW/cm ²	3.1mW/cm ²
General population/Uncontrolled Exposure: $f/1500 \text{ mW/cm}^2$	0.6mW/cm ²	0.6mW/cm ²	0.6mW/cm ²

RSS-102 issue 5

	896MHz	916.5MHz (Test Frequency)	940MHz
Occupational/Controlled Exposure: $0.6455f^{0.5} \text{ W/m}^2$	19W/m ² 1.9mW/cm ²	20W/m ² 2.0mW/cm ²	20W/m ² 2.0mW/cm ²
General population/Uncontrolled Exposure: $0.0.619f^{0.6834} \text{ W/cm}^2$	3W/m ² 0.3mW/cm ²	3W/m ² 0.3mW/cm ²	3W/m ² 0.3mW/cm ²

Recommended Antennas:

Antenna Type	Antenna Gain
Monopole ($\lambda/4$ antenna)	2.15 dBi
Monopole (Co-linear antenna)	8 dBi

Measurement Guidance:

Federal Communications Commission OET Laboratory Division
KDB 447498 v05.

Per definition of a mobile device a minimum separation distance of 20 cm is required.

The minimum separation distances required to install an antenna on a vehicle must be larger than those tested for compliance and must be disclosed separately to antenna installers and radio operators to ensure compliance. A separation distance based on MPE evaluation (measurement or computer modelling) that is smaller than the estimated MPE distance may be used if it is applicable for the antenna installation conditions.

A mid-sized sedan was used for the testing so that the results can be applied to a larger vehicle resulting in conservative exposure conditions. The roof antenna position tested is closer to bystanders than if it were mounted centrally (as recommended in the installation instructions) in order to ensure that even on small vehicle the separation distance is more conservative than the tested distance.

Test Results:

NAME OF TEST: TRANSMITTER OUTPUT POWER (CONDUCTED)
SPECIFICATION: FCC 47 CFR 2.1046
GUIDE: TIA/EIA-603D 2.2.1

TRANSMITTER POWER MEASUREMENT:

1. The Equipment Under Test (EUT) was connected to an RF power meter using a coaxial attenuator with an impedance of 50 Ohms.
2. The unmodulated output power was measured.

MEASUREMENT RESULTS:

Transmit Frequency:	916.5	MHz
Supply Voltage:	13.8	Volts
Measured Output Power:	2.43	Watts
Measurement Uncertainty (dB):	± 0.5	dB

The MPE results are scaled to simulate results from a 30 watt transmitter. A margin of 20% is added to the rated power output of 30 watts giving 36 watts and a 50% duty cycle is applied (ref KDB 447498v05).

NAME OF TEST: MPE ASSESSMENT
SPECIFICATION: FCC 47 CFR 1.1310

MEASUREMENT METHOD:

Field strength measurements were performed for two antenna positions on a representative vehicle (Toyota Camry 2004 four door sedan). See Appendix A for details of antenna and external test positions.

External Field strength readings were taken at 20 cm intervals vertically over a height of 2 metres.

Internal field strength readings were recorded in the front and back seat locations in the areas where the highest field strength was found.

Passenger exposure was evaluated at 10 cm from the surface of seats and back of head position in the rear seat. Measurements were made in an area 40cm wide representing the head and upper and lower torso.

Spatial averaging is carried out to determine the MPE result (IEEE C95.1 3.29).

MEASUREMENT RESULTS: See appendix A for antenna positions.

Calculations of average power (sum of results/number of results):

External to vehicle:

		Power Density (mW/cm ²)					
Antenna pos.		Roof	Trunk	Trunk	Roof	Trunk	Trunk
Test pos. (Appendix A)		A	B	C	A	B	C
		2.15 dBi antenna			8 dBi antenna		
Test Height (m)	0.2	0.006	0.009	0.014	0.002	0.009	0.009
	0.4	0.004	0.017	0.022	0.002	0.015	0.009
	0.6	0.008	0.024	0.022	0.003	0.012	0.005
	0.8	0.015	0.038	0.065	0.004	0.023	0.022
	1.0	0.019	0.090	0.157	0.007	0.065	0.087
	1.2	0.037	0.151	0.206	0.011	0.290	0.202
	1.4	0.066	0.137	0.157	0.058	0.187	0.102
	1.6	0.109	0.082	0.102	0.148	0.015	0.006
	1.8	0.140	0.040	0.043	0.100	0.047	0.029
	2.0	0.120	0.033	0.035	0.012	0.046	0.028
Average		0.052	0.062	0.082	0.035	0.071	0.050

Inside Vehicle:

Roof Mounted Antenna		
Internal Front Seat	Power Density (mW/cm ²)	
	2.15 dBi antenna	8 dBi antenna
Head	0.001	0.003
Upper torso	0.001	0.003
Lower torso	0.000	0.005
Average	0.001	0.004
Internal Back Seat	Power Density (mW/cm ²)	
	2.15 dBi antenna	8 dBi antenna
Head	0.005	0.004
Upper torso	0.006	0.003
Lower torso	0.009	0.003
Average	0.007	0.004

Trunk Mounted Antenna		
Internal Front Seat	Power Density (mW/cm ²)	
	2.15 dBi antenna	8 dBi antenna
Head	0.027	0.019
Upper torso	0.027	0.023
Lower torso	0.028	0.028
Average	0.028	0.023
Internal Rear Centre Seat	Power Density (mW/cm ²)	
	2.15 dBi antenna	8 dBi antenna
Head	0.065	0.073
Upper torso	0.032	0.069
Lower torso	0.015	0.009
Average	0.037	0.051

Measurement Uncertainty:

Field Probe: ± 1 dB

Test Equipment Used:

Equipment Type	Information	Manufacturer	Model No	Serial No	Tait ID	Cal Due
Field Strength Meter	10kHz 9.25GHz RF Field Probe	Narda	EP601	401WX01247	E4856	21-Apr-16
Modulation Analyser	TREVA1	Hewlett Packard	HP8901B (Opt 002)	2441A00393	E3073	18-Oct-15
Power Supply		Rohde & Schwarz	NGS M32/10 192.0810.31	FNr 434	E3556	22-Mar-16
Power Meter	TREVA1 Power Head for HP8901	Hewlett Packard	HP11722A	3111A05573	E7054	18-Oct-15
RF Combiner	TREVA1	Minicircuits	ZFSC-4-1	-	E4083	

NOTE: Items without calibration dates are calibrated immediately before use, or set using calibrated instruments.

Information to be placed in User/Installation manual:

§2.1033(c)(3) requires device operating and installation instructions to be submitted during equipment certification; instructions should include the minimum separation distance and other constraints required for the device and its antenna(s) to meet MPE limits.

Warning: RF Exposure Hazard

To comply with FCC and Industry Canada RF exposure limits, mount the antenna at a location such that no person or persons can come closer than 35 inches (0.9m) to the antenna:

For radios with a transmit power >25W:

VHF radios must be installed using an antenna mounted centrally on the vehicle roof, with a gain of 2.15dBi or 5.15dBi.

UHF and 800 MHz radios must be installed using an antenna mounted either centrally on the vehicle roof with a gain of 2.15 dBi or 5.65 dBi, or centrally mounted on the trunk with a gain of 5.65 dBi.

900 MHz radios must be installed using an antenna mounted either centrally on the vehicle roof or centrally mounted on the trunk with a gain of 2.15 dBi or 8 dBi.

For radios with a transmit power of 25W:

The radio must be installed using an externally mounted antenna with a gain of either 2.15 or 5.15 dBi.

Safety Training Information:

Radio frequency exposure information:

For your own safety and to ensure you comply with the United States Federal Communication Commission's (FCC), Industry Canada's radio frequency (RF) exposure guidelines, and those from other administrations, please read the following information before using this radio.

Using this radio

You should use this radio only for work-related purposes (it is not authorized for any other use) and if you are fully aware of, and can exercise control over, your exposure to RF energy. To prevent exceeding RF exposure limits, you must control the amount and duration of RF that you and other people are exposed to.

It is also important that you:

- Do not remove the RF exposure label from the radio.
- Ensure this RF exposure information accompanies the radio when it is transferred to other users.
- Do not use the radio if you do not adhere to the guidelines on controlling your exposure to RF.

Controlling your exposure to RF energy

This radio emits radio frequency (RF) energy or radio waves primarily when calls are made. RF is a form of electromagnetic energy (as is sunlight), and there are recommended levels of maximum RF exposure.

To control your exposure to RF and comply with the maximum exposure limits for occupational/controlled environments, follow these guidelines:

- Do not talk (transmit) on the radio more than the rated transmit duty cycle. This is important because the radio radiates more energy when it is transmitting than when it is receiving.

Mobile radios only:

- While you are transmitting (talking or sending data) on the radio, you must ensure that there is always a distance of 35 inches (0.9 m) between people and the antenna. This is the minimum safe distance. For 110 W mobiles, the minimum safe distance is 44 inches (1.1 m).
- Use the radio only with Tait-approved antennas and attachments, and make only authorized modifications to the antenna otherwise you could damage the radio and violate FCC regulations.

TELTEST Laboratories
Tait Limited
Report Number 3662

Please refer to the following website for more information on what RF energy is and how to control your exposure to assure compliance with established RF exposure limits.

Website: <http://www.fcc.gov/oet/rfsafety/rf-faqs.html>

Appendix 1

Antenna Location and Test Positions:

Test Vehicle:

Toyota Camry 2004 four door sedan, dimensions 4.8m long, 1.7m wide and 1.5m high.

Each test position must satisfy the following requirements (ref KDB643646 DR02 p13):

Criteria for bystanders:

- ≤ 90 cm from antenna.
- ≥ 20 cm from side of car.
- 15 cm multiple from antenna position.

Criteria for passengers:

- Passenger exposure must be evaluated at ≤ 10 cm from surface of seats.

Azimuth: Radials are referenced to 0 degrees, which is the bearing of the location with the shortest distance to the bystander.

External Measurement Positions:

Roof top Antenna Position:

Antenna mounted 70 cm from side of vehicle.

Bystander exposure:

Radial	Distance from antenna (including ≥ 20 cm clearance to side of car and rounded to 15 cm multiples)	Required distance from antenna	TEST REQUIRED
0 degrees	90 cm	≤ 90 cm	YES see A Fig 1
45 deg	120 cm	≤ 90 cm	NO (> 90 cm)
90 deg	200 cm to front of car	≤ 90 cm	NO (> 90 cm)
270 deg	220 cm to rear of car	≤ 90 cm	NO (> 90 cm)
315 deg	120 cm	≤ 90 cm	NO (> 90 cm)

Trunk mounted Antenna Position:

Antenna mounted 30 cm from rear of car on the centre of the trunk lid.

Bystander exposure:

Radial	Distance from antenna (including ≥ 20 cm clearance to side of car rounded to 15 cm multiples)	Required distance from antenna	TEST REQUIRED
0 degrees	60 cm to rear of car	≤ 90 cm	YES see C Fig 2
180 deg	470 cm to front of car	≤ 90 cm	NO (> 90 cm)
45 deg	75 cm to side of car	≤ 90 cm	YES see B Fig2
90 deg	105 cm to side of car	≤ 90 cm	NO (> 90 cm)

