

Standalone SAR test exclusion considerations: **BLE**

Date: October 19, 2018

RF feature	Mode	Transmitting Frequency(MHz)	Test separation distance (mm) ^{Note1}	Max. power with tune-up tolerance (dBm) ^{Note2}	ANT Gain (dBi)	Max. power with tune-up tolerance (mW)	Power thresholds	SAR test exclusion thresholds
BLE	-	2402.00	5.0	-3.50	3.14	0.4467	0.14	3.00

Note1. The minimum separation distance between antenna and user is 5 mm.

Exact antenna dimensions and separation distances are shown in the "Attestation letter"

Note2. Please refer to the operation description for Max.tune-up power.

KDB 447498 D01 clause 4.3.1 Step 1) SAR test exclusion thresholds for 100MHz to 6GHz at test separation distances \leq 50 mm[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] \cdot [$\sqrt{f(\text{GHz})}$] \leq 3.0 for 1g SAR and \leq 7.5 for 10g extremity SAR**Sample Calculation**

$$= [(0.4467 \text{mW} / 5 \text{mm})] \times [\sqrt{2.402 \text{GHz}}] = 0.14$$

Note. The calculation result was rounded to two decimal places for comparison.

Conclusion : SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required