

# Assessment report

**443812-2TRFWL**

Date of issue: June 28, 2021

Applicant:

**Fujitsu Network Communications**

Product:

**Dual Band RU for North America**

Model

**DB 5G RU**

FCC ID:

**CFD5GRUDB3**

Type of assessment:

**MPE Exemption Report**

Specifications:

- ◆ FCC 47 CFR Part 1 Subpart I, §§1.1307, 1.1310
- ◆ FCC 47 CFR Part 2 Subpart J, §2.1091
- ◆ KDB 447498 D01 General RF Exposure Guidance v06

---

**Lab and test locations**

---

Company name	Nemko USA, Inc.
Address	1110 Faraday Ave, Suite 150
City	Carlsbad
State	California
Postal code	92008
Country	USA
Telephone	+1 760 444 3500
Website	<a href="http://www.nemko.com">www.nemko.com</a>

Prepared by	Martha Espinoza, Wireless Test Engineer
Reviewed by	Chip Fleury, Wireless & Certification Supervisor
Review date	June 29, 2021
Reviewer signature	

---

**Limits of responsibility**

---

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contained in this report are within Nemko USA's ISO/IEC 17025 accreditation.

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government

---

**Copyright notification**

---

Nemko USA Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties.

Nemko USA Inc. accepts no responsibility for damages, if any, suffered by any third party because of decisions made or actions based on this report.

© Nemko USA Inc.

## Table of Contents

---

<b>Table of Contents .....</b>	<b>3</b>
<b>Section 1      Evaluation summary .....</b>	<b>4</b>
1.1    MPE exemption for stand-alone transmission .....	4

## Section 1 Evaluation summary

---

### 1.1 MPE exemption for stand-alone transmission

---

#### 1.1.1 References, definition, and limits

---

FCC §2.1091(c)

- (1) Mobile devices that operate in the Commercial Mobile Radio Services pursuant to part 20 of this chapter; the Cellular Radiotelephone Service pursuant to part 22 of this chapter; the Personal Communications Services pursuant to part 24 of this chapter; the Satellite Communications Services pursuant to part 25 of this chapter; the Miscellaneous Wireless Communications Services pursuant to part 27 of this chapter; the Upper Microwave Flexible Use Service pursuant to part 30 of this chapter; the Maritime Services (ship earth station devices only) pursuant to part 80 of this chapter; the Specialized Mobile Radio Service, and the 3650 MHz Wireless Broadband Service pursuant to part 90 of this chapter; the 76-81 GHz Band Radar Service pursuant to part 95 of this chapter; and the Citizens Broadband Radio Service pursuant to part 96 of this chapter are subject to routine environmental evaluation for RF exposure prior to equipment authorization or use if:
  - (i) They operate at frequencies of 1.5 GHz or below and their effective radiated power (ERP) is 1.5 watts or more, or
  - (ii) They operate at frequencies above 1.5 GHz and their ERP is 3 watts or more.
- (2) Unlicensed personal communications service devices, unlicensed millimeter-wave devices, and unlicensed NII devices authorized under §§15.255(f), 15.257(g), 15.319(i), and 15.407(f) of this chapter are also subject to routine environmental evaluation for RF exposure prior to equipment authorization or use if their ERP is 3 watts or more or if they meet the definition of a portable device as specified in §2.1093(b) requiring evaluation under the provisions of that section.
- (3) All other mobile and unlicensed transmitting devices are categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use, except as specified in §§1.1307(c) and 1.1307(d) of this chapter.

#### 1.1.2 EUT technical information

---

Operational frequency	2112.5 – 2197.5 MHz - 5 MHz bandwidth 2115 - 2195 MHz – 10 MHz bandwidth 2120 - 2190 MHz – 20 MHz bandwidth 2007.5 MHz – 25 MHz bandwidth
Antenna type	The EUT is professionally installed
Antenna gain	Unknown (Depends of final client)
Number of antennas	4
Maximum transmitter conducted power	48.81 dBm (76032.62 mW) – 5 MHz bandwidth 48.80 dBm (75857.75 mW) – 10 MHz bandwidth 48.69 dBm (73960.52 mW) – 20 MHz bandwidth 46.81 dBm (47973.34 mW) – 25 MHz bandwidth
Maximum EIRP (Power across four ports)	54.81 dBm (302691.3 mW) – 5 MHz bandwidth 54.80 dBm (301995.1 mW) – 10 MHz bandwidth 54.69 dBm (294442.1 mW) – 20 MHz bandwidth 52.81 dBm (190985.3 mW) – 25 MHz bandwidth

## 1.1.3 MPE exemption calculations - based on worst case power output from worst case port

Fundamental transmit (prediction) frequency:	2155	MHz
Maximum measured conducted peak output power:	48.81	dBm
Cable and/or jumper loss:	0	dB
Maximum peak power at antenna input terminal:	48.81	dBm
Tx On time:	1.000	ms
Tx period time:	1.000	ms
Average factor:	100	%
Maximum calculated average power at antenna input terminal:	76032.628	mW
Single Antenna gain (typical):	20.4	dBi
Number of antennae:	4	
Total system gain:	26.42	dBi
<b>MPE limit for uncontrolled exposure at prediction frequency:</b>	<b>1.000000</b>	<b>mW/cm<sup>2</sup></b>
Minimum calculated prediction distance for compliance:	10.000000	W/m <sup>2</sup>
Typical (declared) distance:	1629	cm
<b>Average power density at prediction frequency:</b>	<b>0.998792</b>	<b>mW/cm<sup>2</sup></b>
		9.987917 W/m <sup>2</sup>
<b>Margin of Compliance:</b>	<b>0.01</b>	<b>dB</b>
Maximum allowable antenna gain:	26.43	dBi

## 1.1.4 Verdict

The calculation of EIRP is below the exemption limit; therefore, the product is compliant with the RF exposure exemption requirements.

**End of test report**