

# Assessment report

**REP088059-3R1ARFWL**

Date of issue: July 28, 2025

Applicant:

**Fujitsu Network Communications, Inc.**

Product:

**Single Band Radio Unit**

Model

**44R14-N77a**

FCC ID:

**CFD5GTRUSB**

Type of assessment:

**MPE Calculation Report**

Specifications:


- ◆ FCC 47 CFR Part 1 Subpart I, §§1.1307, 1.1310
- ◆ FCC 47 CFR Part 2 Subpart J, §2.1091
- ◆ KDB 447498 D01 General RF Exposure Guidance v06

---

**Lab and test locations**

---

Company name	Nemko USA, Inc.
Address	1110 Faraday Ave, Suite 150
City	Carlsbad
State	California
Postal code	92008
Country	USA
Telephone	+1 760 444 3500
Website	<a href="http://www.nemko.com">www.nemko.com</a>

Prepared by	Martha Espinoza, Wireless Test Engineer
Reviewed by	James Cunningham, EMC/MIL/WL Supervisor
Review date	July 28, 2025
Reviewer signature	

---

**Limits of responsibility**

---

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contained in this report are within Nemko USA's ISO/IEC 17025 accreditation.

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

---

**Copyright notification**

---

Nemko USA Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties.

Nemko USA Inc. accepts no responsibility for damages, if any, suffered by any third party because of decisions made or actions based on this report.

© Nemko USA Inc.

## Table of Contents

---

<b>Table of Contents .....</b>	<b>3</b>
<b>Section 1      Declaration .....</b>	<b>4</b>
<b>Section 2      Evaluation summary .....</b>	<b>5</b>
2.1    MPE exemption for stand-alone transmission .....	5

## Section 1 Declaration

---

RSS-102 Annex B - Declaration of RF exposure compliance:

**Attestation:**

I attest that the information provided in Annex A is correct; that the Technical Brief was prepared, and the information contained therein is correct; that the device evaluation was performed and/or supervised by me; that the applicable measurement methods and evaluation methodologies have been followed; and that the device meets the SAR and/or RF field strength limits of RSS-102.

Date of issue: **May 5, 2025**

---

Martha Espinoza, Wireless Test Engineer

Prepared by



Signature

## Section 2 Evaluation summary

### 2.1 MPE exemption for stand-alone transmission

#### 2.1.1 References, definition, and limits

FCC §2.1091(d)

(2) For operations within the frequency range of 300 kHz and 6 GHz (inclusive), the limits for maximum permissible exposure (MPE), derived from the whole-body SAR limits and listed in Table 1 in paragraph (e)(1) of this section, may be used instead of whole-body SAR limits as set forth in paragraphs (a) through (c) of this section to evaluate the environmental impact of human exposure to RF radiation as specified in §1.1307(b) of this part, except for portable devices as defined in §2.1093 of this chapter as these evaluations shall be performed according to the SAR provisions in §2.1093.

**Table 2.1-1: Table 1 to §1.1310(e)(1)—Limits for Maximum Permissible Exposure (MPE)**

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(i) Limits for Occupational/Controlled Exposure</b>				
0.3–3.0	614	1.63	*(100)	≤6
3.0–30	1842 / f	4.89 / f	*(900 / f <sup>2</sup> )	<6
30–300	61.4	0.163	1.0	<6
300–1500			f / 300	<6
1500–100000			5	<6
<b>(ii) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34	614	1.63	*(100)	<30
1.34–30	824 / f	2.19 / f	*(180 / f <sup>2</sup> )	<30
30–300	27.5	0.073	0.2	<30
300–1500			f / 1500	<30
1500–100000			1.0	<30

Notes: f = frequency in MHz. \* = Plane-wave equivalent power density.

Equation from Page 18 of OET Bulletin 64, Edition 97-01:

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density (mW/cm<sup>2</sup> or W/m<sup>2</sup>)

P = power input to the antenna (mW or W)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (cm or m)

## 2.1.2 EUT technical information

Operational frequency (Band n71)	3700 – 3980 MHz
Antenna type	Sector panel antenna
Antenna gain	17 dBi
Number of antennas	Maximum: 4
Maximum transmitter conducted power	45.73 dBm (37411.05883 mW)
Max power across four ports	51.75 dBm (149623.5656094 mW)

## 2.1.3 MPE exemption calculations

Fundamental transmit (prediction) frequency: 3830 MHz  
 Maximum measured conducted peak output power: 45.73 dBm  
 Cable and/or jumper loss: 0 dB  
 Maximum peak power at antenna input terminal: 45.73 dBm  
 Tx On time: 1.000 ms  
 Tx period time: 1.000 ms  
 Average factor: 100 %  
 μm calculated average power at antenna input terminal: 37411.059 mW  
 Single Antenna gain (typical): 17 dBi  
 Number of antennas: 4  
 Total system gain: 23.02 dBi

**FCC limit:**  
 Limit for uncontrolled exposure at prediction frequency: 1.000000 mW/cm<sup>2</sup>  
10.000000 W/m<sup>2</sup>  
 Minimum calculated prediction distance for compliance: 1200 cm  
 Typical (declared) distance: 1200 cm  
**Average power density at prediction frequency:** 0.414465 mW/cm<sup>2</sup>  
4.144648 W/m<sup>2</sup>  
**Margin of Compliance:** 3.83 dB

**Additional assessment with respect to transmitter power density to determine maximum allowable antenna gain:**  
 Fundamental transmit (prediction) frequency: 3830 MHz  
 Maximum measured conducted power density: 38.8 dBm/MHz  
 Cable and/or jumper loss: 0 dB  
 Maximum peak power at antenna input terminal: 38.8 dBm  
 Tx On time: 1.000 ms  
 Tx period time: 1.000 ms  
 Average factor: 100 %  
 μm calculated average power at antenna input terminal: 7585.7758 mW  
 Single Antenna gain (typical): 17 dBi  
 Number of antennas: 4  
 Total system gain: 23.02 dBi

**FCC limit:**  
 Limit for uncontrolled exposure at prediction frequency: 1.000000 mW/cm<sup>2</sup>  
10.000000 W/m<sup>2</sup>  
 Minimum calculated prediction distance for compliance: 1200 cm  
 Typical (declared) distance: 1200 cm  
**Average power density at prediction frequency:** 0.084040 mW/cm<sup>2</sup>  
0.840403 W/m<sup>2</sup>  
**Margin of Compliance:** 10.76 dB  
 Maximum allowable antenna gain: 33.78 dBi

**2.1.4 Verdict**

---

The calculation is below the limit; therefore, the product is compliant with the RF exposure requirements for the declared distance.

**End of test report**