

RADIATED EMISSIONS

<b>HONEYWELL SECURITY &amp; CUSTOM ELECTRONICS</b>		REV 07/23/2013-0
<b>2 Corporate Center Drive</b>		
<b>Melville, NY 11747</b>	EXHIBIT 5-3	FCC ID: CFS8DL5800C2W

Date : 9-Oct 2013	Tested by: BARTO	Approved by: K. Eskildsen
Test Sample (model): 5800C2W		
Test method: ANSI C63.4 - 2003		
Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 8		
Notes: (1) Fo: 344.94		
(2) Detector = Peak		
(3) Frequency range scanned to 4 GHz.		
(Emissions not reported were more than 20dB below the specified unit ).		
[(Meter reading + Cable/Amp factor + Antenna factor) / 20 ]]		
(4) Conv. Reading = 10		
(5) Corr. Reading = Conv. Reading X Duty Cycle		
(6) Six Highest Emissions Recorded		

Freq. (MHz):	Sense Antenna Polarity (V/H):	THE ORIENTATION OF THE UUT (V,H,O):	Meter Reading (dB uV):	Cable/Amp Factor (dB):	Antenna Factor (dB/m):	Conv. Reading (uW/M):	Duty Cycle (%):	Corr. Reading (uW/M):	Limit @ 3M (uW/M):
344.94	H	H	79.51	2.5	15.20	72,527.0	10.0%	7252.7	7,289
689.88	H	H	32.25	3.7	19.20	573.5	10.0%	57.3	729
1034.82	H	O	33.78	4.7	22.90	1,172.2	10.0%	117.2	500
1379.76	H	O	37.56	5.6	24.90	2,532.2	10.0%	253.2	500
1724.70	H	V	26.33	6.3	27.70	1,034.0	10.0%	103.4	729
2069.64	H	V	29.77	7.3	29.80	2,192.8	10.0%	219.3	729
2414.58	V	V	31.92	8.1	31.80	3,881.5	10.0%	388.2	729
2759.52	V	O	27.40	8.6	31.80	2,457.5	10.0%	245.8	500
3104.46	H	H	27.47	9.1	31.50	2,535.1	10.0%	253.5	729
3449.40	H	H	27.33	10.0	32.10	2,951.2	10.0%	295.1	729
4000				LAST CAL 15 MAR 13 CABLE D	LAST CAL 08-JULY-13 BICONILOG S/N:00029390				