

**HONEYWELL SECURITY & CUSTOM ELECTRONICS**

165 EILEEN WAY

SYOSSET, NY 11791

EXHIBIT 5-3

FCC ID # CFS8DL5800CO

Date : 02/27/2007

Tested by :Azadeh Solhjoo

Approved by :K.Addy

Test Sample (model) : 5800COLF

Test method: ANSI C63.4 - 2004

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20 ]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/m)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A"	BICONILOG S/N:00045682				729
345	h	78.90	1.3	14.60	54925.1	10.0%	5492.5	7292
690	h	53.50	1.7	18.87	5049.7	10.0%	505.0	729
1035	h	37.90	2.2	22.28	1315.6	10.0%	131.6	500
1380	v	33.20	2.5	25.97	1211.8	10.0%	121.2	500
1725	v	32.70	2.9	28.75	1650.0	10.0%	165.0	729
2070	h	37.80	3.2	29.81	3470.9	10.0%	347.1	729
2415	h	42.10	3.4	31.30	6920.5	10.0%	692.0	729
2760	h	32.70	3.5	31.94	2552.0	10.0%	255.2	500
3105	h	36.00	3.7	31.98	3837.6	10.0%	383.8	729
3450	h	25.00	3.9	32.35	1154.4	10.0%	115.4	729
4000			CABLE "A"	BICONILOG S/N:00045682				