

ALARM DEVICE MANUFACTURING COMPANY
165 EILEEN WAY
SYOSSET, NY 11791

FCC ID# _____

FEBRUARY, 06, 2001 GREG BARBATO KEN ADDY
DATE: _____ TESTED BY: _____ APPROVED BY: _____

TEST SAMPLE (model): _____ ADEMCO 5800GDO (RECEIVER)

TEST METHOD: ANSI C63.4-1992

TEST SPECIFICATION: FCC PART 15, SUBPART C.

NOTES: 1) L.O.: 355.7 MHZ
2) DETECTOR = PEAK.
3) FREQUENCY RANGE SCANNED TO 4 GHz.

$$4) \text{ CONVERTED READING} = 10 \left[\frac{(\text{METER READING} + \text{CABLE /AMP FACTOR} + \text{ANTENNA FACTOR})}{20} \right]$$

5) CORRECTED READING = CONVERTED READING X DUTY CYCLE

6) SIX HIGHEST EMISSIONS RECORDED.

Frequency (MHz)	Antenna Polarity (V-H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Converted Reading (uV/M)	Duty Cycle (%)	Corrected Reading (uV/M)	Limit @ 3 Meter (uV/M)
30	-----	-----	-----	-----	-----	-----	-----	100
355	H	15.26	1.5	15.1	39.2	NA	39.2	200
4000	-----	-----	-----	-----	-----	-----	-----	500

NOTES: