

HONEYWELL SECURITY & CUSTOM ELECTRONICS**165 EILEEN WAY****SYOSSET, NY 11791****EXHIBIT 5-3****FCC ID # CFS8DL58OOPIR-OD**

Date : 07/11/2008

Tested by :Y. Mohammed

Approved by :K. Eskildsen

Test Sample (model) : 5800PIR-OD

Test method: ANSI C63.4 - 2004

Test specification: FCC Part 15, Sub-part C and RSS20, Issue 7

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/m)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A"	BICONILOG				729
345	H	79.60	2.6	14.90	71614.3	10.0%	7161.4	7292
690	H	37.50	3.7	19.30	1059.3	10.0%	105.9	729
1035	H	30.40	4.7	22.70	776.2	10.0%	77.6	500
1380	H	25.20	5.5	25.80	668.3	10.0%	66.8	500
1725	H	41.20	6.3	28.00	5956.6	10.0%	595.7	729
2070	H	30.40	7.0	30.30	2426.6	10.0%	242.7	729
2415	H	27.20	7.6	32.00	2187.8	10.0%	218.8	729
2760	H	21.70	8.5	32.80	1412.5	10.0%	141.3	500
3105	H	20.90	9.0	32.50	1318.3	10.0%	131.8	729
3450	H	21.90	10.7	33.00	1905.5	10.0%	190.5	729
4000			CABLE "A"	BICONILOG (00029390)				