HONEYWELL SECURITY & CUSTOM ELECTRONICS **REV 08-21-2012-M**
2 Corporate Center Drive
Melville, NY 11747 **EXHIBIT 5-3** **FCC ID: CFS8DL** **5800PIRESAP**

Date : 29-Aug 2012 Tested by: G. BARBATO Approved by: K. Eskildsen
Test Sample (model): 5800PIRESAP
Test method: ANSI C63.4 - 2003
Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 8

PRESCAN:			
SENSE / UUT:	EL (cm):	AZ (deg):	Meter Reading (dB uV):
V/V			
H/V			
V/H			
H/H	100.0	0/360	77.10
V/O			
H/O			

Notes:
(1) Fo: 315.00
(2) Detector = Peak
(3) Frequency range scanned to 4 GHz.
(Emissions not reported were more than 20dB below the specified unit).
[(Meter reading + Cable/Amp factor + Antenna factor) / 20)]
(4) Conv. Reading = 10
(5) Corr. Reading = Conv. Reading X Duty Cycle
(6) Six Highest Emissions Recorded

Freq. (MHz):	Sense Antenna Polarity (V/H):	THE ORENTATION OF THE UUT	Meter Reading (dB uV):	Cable/Amp Factor (dB):	Antenna Factor (dB/m):	Conv. Reading (uV/M):	Duty Cycle (%):	Corr. Reading (uV/M):	Limit @ 3M (uV/M):
315.00	H	H	77.10	2.5	14.92	53,210.8	10.0%	5321.1	6,042
630.00	H	H	27.45	3.7	20.91	401.8	10.0%	40.2	604
945.00	H	H	21.99	4.7	23.93	339.6	10.0%	34.0	604
1260.00	H	H	23.28	5.6	26.91	616.6	10.0%	61.7	604
1575.00	H	H	30.82	6.3	28.80	1,967.9	10.0%	196.8	500
1890.00	H	H	27.82	7.3	30.64	1,929.7	10.0%	193.0	604
2205.00	H	H	26.97	8.1	31.32	2,077.3	10.0%	207.7	604
2520.00	H	H	22.46	8.6	31.90	1,407.7	10.0%	140.8	604
2835.00	H	H	23.40	9.1	32.41	1,762.0	10.0%	176.2	604
3150.00	H	H	23.46	10.0	32.87	2,065.4	10.0%	206.5	604
4000				LAST CAL 10 JUL 12 CABLE D	LAST CAL 27-JUN-12 BICONILOG S/N:00020971				