

HONEYWELL SECURITY & CUSTOM ELECTRONICS

REV 2011D

**2 Corporate Center Drive
Melville, NY 11747**

EXHIBIT 5-3

FCC ID: CFS8DL PIR-RES1

Date : 4-Aug 2011 Tested by: G. BARBATO Approved by K. Eskildsen
 Test Sample (model): 5800PIRRES1
 Test method: ANSI C63.4 - 2003
 Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 8
 Notes: (1) Fo: 344.94 (2) Detector = Peak (3) Frequency range scanned to 4 GHz.
 Emissions not reported were more than 20dB below the specified unit.
 [(Meter reading + Cable/Amp factor + Antenna factor) / 20]
 (4) Conv. Reading = 10
 (5) Corr. Reading = Conv. Reading X Duty Cycle
 (6) Six Highest Emissions Recorded

| Freq. (MHz): | Sense Antenna Polarity (V/H): | THE ORENTATION OF THE UUT | Meter Reading (dB uV): | Cable/Amp Factor (dB): | Antenna Factor (dB/m): | Conv. Reading (uV/M): | Duty Cycle (%): | Corr. Reading (uV/M): | Limit @ 3M (uV/M): |
|--------------|-------------------------------|---------------------------|------------------------|-------------------------------------|--|-----------------------|-----------------|-----------------------|--------------------|
| 344.94 | V | V | 79.29 | 2.3 | 14.64 | 64,788.8 | 10.0% | 6478.9 | 7292 |
| 689.88 | V | V | 21.59 | 3.2 | 19.91 | 171.8 | 10.0% | 17.2 | 729 |
| 1034.82 | V | H | 17.38 | 4.4 | 24.40 | 203.7 | 10.0% | 20.4 | 500 |
| 1379.76 | V | V | 16.07 | 4.9 | 27.84 | 275.7 | 10.0% | 27.6 | 500 |
| 1724.70 | V | O | 16.29 | 5.5 | 29.10 | 350.3 | 10.0% | 35.0 | 729 |
| 2069.64 | V | V | 16.37 | 6.4 | 33.92 | 683.1 | 10.0% | 68.3 | 729 |
| 2414.58 | V | V | 16.56 | 6.9 | 31.64 | 568.9 | 10.0% | 56.9 | 729 |
| 2759.52 | V | V | 16.37 | 7.4 | 33.16 | 702.3 | 10.0% | 70.2 | 500 |
| 3104.46 | V | V | 16.44 | 7.9 | 34.03 | 828.9 | 10.0% | 82.9 | 729 |
| 3449.40 | V | V | 16.15 | 9.2 | 32.12 | 747.3 | 10.0% | 74.7 | 729 |
| 4000 | | | | LAST CAL 05 FEB 11 CABLE C | LAST CAL 17-MAY-11 BICONILOG S/N:00029390 | | | | |