

HONEYWELL SECURITY & CUSTOM ELECTRONICS**165 EILEEN WAY****SYOSSET, NY 11791****EXHIBIT 5-3****FCC ID # CFS8DL5800RP**

Date : 4/02/2007

Tested by :Y. Mohammed

Approved by :K.Addy

Test Sample (model) : 5800RP

HI Power

Test method: ANSI C63.4 - 1992

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A"	BICONILOG				729
345	V	74.20	1.2	14.50	31260.8	15.8%	4939.2	7292
690	V	28.00	1.8	19.80	302.0	15.8%	47.7	729
1035	V	28.00	2.2	24.10	518.8	15.8%	82.0	500
1380	V	28.00	2.5	26.30	691.8	15.8%	109.3	500
1725	V	28.00	2.8	29.70	1059.3	15.8%	167.4	729
2070	V	28.00	3.0	29.60	1071.5	15.8%	169.3	729
2415	V	28.00	3.3	31.30	1349.0	15.8%	213.1	729
2760	V	28.00	3.7	31.50	1445.4	15.8%	228.4	729
3105	V	28.00	4.1	31.50	1513.6	15.8%	239.1	729
3450	V	28.00	4.4	33.30	1927.5	15.8%	304.5	729
4000			CABLE "A"	BICONILOG				