

HONEYWELL SECURITY & CUSTOM ELECTRONICS**165 EILEEN WAY****SYOSSET, NY 11791****EXHIBIT 5-3****FCC ID # CFS8DL5800RP**

Date : 4/05/2007

Tested by :Y. Mohammed

Approved by :K.Addy

Test Sample (model) : 5800RP

LO Power

Test method: ANSI C63.4 - 1992

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A"	BICONILOG				291.7
345	V	66.10	1.2	14.50	12302.7	22.8%	2805.0	2916.7
690	V	35.39	1.8	19.80	707.1	22.8%	161.2	291.7
1035	V	30.89	2.2	24.10	723.6	22.8%	165.0	291.7
1380	V	26.00	2.5	26.30	549.5	22.8%	125.3	291.7
1725	V	28.00	2.8	29.70	1059.3	22.8%	241.5	291.7
2070	V	18.00	3.0	29.60	338.8	22.8%	77.3	291.7
2415	V	18.00	3.3	31.30	426.6	22.8%	97.3	291.7
2760	V	18.00	3.7	31.50	457.1	22.8%	104.2	291.7
3105	V	15.00	4.1	31.50	338.8	22.8%	77.3	291.7
3450	V	16.00	4.4	33.30	484.2	22.8%	110.4	291.7
4000			CABLE "A"	BICONILOG				