

ALARM DEVICE MANUFACTURING COMPANY
165 EILEEN WAY
SYOSSET, NY 11791

CFS8DL5800STAT

FCC ID#_____

JULY, 10, 2001

GREG BARBATO

KEN ADDY

DATE:_____TESTED BY:_____APPROVED BY:_____

ADEMCO 5800STAT (TRANSMITTER)

TEST SAMPLE (model): _____

TEST METHOD: ANSI C63.4-1992

TEST SPECIFICATION: FCC PART 15, SUBPART C.

NOTES: 1) Fo= 345 MHZ

2) DETECTOR = PEAK.

3) FREQUENCY RANGE SCANNED TO 4 GHz.

4) CONVERTED READING = 10 $\left[\frac{(\text{METER READING} + \text{CABLE /AMP FACTOR} + \text{ANTENNA FACTOR})}{20} \right]$

5) CORRECTED READING = CONVERTED READING X DUTY CYCLE

6) SIX HIGHEST EMISSIONS RECORDED.

Frequency (MHz)	Antenna Polarity (V-H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Converted Reading (uV/M)	Duty Cycle (%)	Corrected Reading (uV/M)	Limit @ 3 Meter (uV/M)
30	H					10		291
345	V	72.33	1.7	15.1	28,608.8	10	2,860.9	2,910
690	V	43.0	2.3	20.6	1,972.4	10	197.2	291
1035	H	30.0	3.2	24.0	724.4	10	72.4	291
1380	H	32.0	3.5	27.9	1,479.1	10	147.9	291
1725	V	22.0	3.8	30.0	616.6	10	61.7	291
2070	H	25.0	4.3	28.0	732.8	10	73.3	291
2415	H	22.0	4.5	28.8	582.1	10	58.2	291
2760	H	22.0	4.6	30.0	676.1	10	67.6	291
3105	H	22.0	4.6	30.7	732.8	10	73.3	291
3450	H	22.0	5.1	31.1	812.8	10	81.3	291
4000	H	22.0				10		291