ALARM DEVICE MANUFACTURING COMPANY
165 EILEEN WAY **CFS8DL5800TSTAT**
SYOSSET, NY 11791 **FCC ID#_____**

DATE: April, 11, 2001 TESTED BY: GREG BARBATO APPROVED BY: KEN ADDY

TEST SAMPLE (model): ADEMCO 5800TSTAT (RECEVER)

TEST METHOD: ANSI C63.4-1992
TEST SPECIFICATION: FCC PART 15, SUBPART C.

NOTES: 1) DETECTOR = PEAK.
2) FREQUENCY RANGE SCANNED TO 4 GHz.

3) CONVERTED READING = $10^{\left[\frac{(\text{METER READING} + \text{CABLE /AMP FACTOR} + \text{ANTENNA FACTOR})}{20}\right]}$

4) CORRECTED READING = CONVERTED READING X DUTY CYCLE

5) SIX HIGHEST EMISSIONS RECORDED.

Frequency (MHz)	Antenna Polarity (V-H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Converted Reading (uV/M)	Duty Cycle (%)	Corrected Reading (uV/M)	Limit @ 3 Meter (uV/M)
355.7	H	15.0	2.3	15.1	41.69	-------	41.69	200