

Date : 02/08/2010 Tested by : G. Barbato Approved by : K. Eskildsen
 Test Sample (model) : 344.94 MHz 5804E-1
 Test method: ANSI C63.4 - 2004
 Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 7
 Notes: (1) Fo = 344.94 MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.
 Emissions not reported were more than 20dB below the specified unit.
 [(Meter reading + Cable/Amp factor + Antenna factor) / 20]
 (4) Conv. Reading = 10
 (5) Corr. Reading = Conv. Reading X Duty Cycle
 (6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/m)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			LAST CAL 16 FEB 09 CABLE C	LAST CAL 10 JUL 09 BICONILOG S/N:00045682				729
344.94	v	70.76	2.3	14.37	23523.4	14.3%	3363.8	7292
689.88	v	38.89	3.2	19.66	1223.2	14.3%	174.9	729
1034.82	v	27.61	4.4	25.22	726.9	14.3%	104.0	500
1379.76	v	21.22	* 4.9	26.35	420.2	14.3%	60.1	500
1724.70	v	22.31	* 5.5	27.49	582.1	14.3%	83.2	729
2069.64	v	24.14	* 6.4	31.34	1241.7	14.3%	177.6	729
2414.58	v	21.67	* 6.9	31.81	1044.7	14.3%	149.4	729
2759.52	v	20.70	* 7.4	31.56	961.6	14.3%	137.5	500
3104.46	v	20.98	* 7.9	32.34	1150.8	14.3%	164.6	729
3449.40	v	20.78	* 9.2	33.09	1424.0	14.3%	203.6	729
4000		NOTE: * = NOISE FLOOR	LAST CAL 16 FEB 09 CABLE C	LAST CAL 10 JUL 09 BICONILOG S/N:00045682				