

Date : 03/16/2010 Tested by : G.B. Approved by : K. Eskildsen
 Test Sample (model) : 344.94 MHz 5808W3XT
 Test method: ANSI C63.4 - 2004
 Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 7
 Notes: (1) Fo = 344.94MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.
 Emissions not reported were more than 20dB below the specified unit.
 [(Meter reading + Cable/Amp factor + Antenna factor) / 20]
 (4) Conv. Reading = 10
 (5) Corr. Reading = Conv. Reading X Duty Cycle
 (6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/m)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			LAST CAL 16 FEB 09 CABLE C	LAST CAL 10 JUL 09 BICONILOG S/N:00045682				729
344.94	h	75.59	2.3	15.35	45919.8	10.0%	4592.0	7292
689.88	h	43.42	3.2	20.02	2147.8	10.0%	214.8	729
1034.82	h	39.54	4.4	24.85	2751.1	10.0%	275.1	500
1379.76	h	28.62	4.9	25.93	938.6	10.0%	93.9	500
1724.70	h	26.61	5.5	26.96	898.5	10.0%	89.8	729
2069.64	h	26.14	6.4	31.36	1566.8	10.0%	156.7	729
2414.58	h	31.04	6.9	32.15	3195.2	10.0%	319.5	729
2759.52	h	24.48	7.4	32.37	1631.2	10.0%	163.1	500
3104.46	h	24.03	7.9	32.73	1710.0	10.0%	171.0	729
3449.40	h	22.71	9.2	33.00	1759.9	10.0%	176.0	729
4000			LAST CAL 16 FEB 09 CABLE C	LAST CAL 10 JUL 09 BICONILOG S/N:00045682				