

Date : 10/11/2010 Tested by : G. BARBATO Approved by : K. Eskildsen
 Test Sample (model) : 345.00 MHz 5811
 Test method: ANSI C63.4 - 2004
 Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 7
 Notes: (1) Fo = 344.94 MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.
 Emissions not reported were more than 20dB below the specified unit.
 [(Meter reading + Cable/Amp factor + Antenna factor) / 20]
 (4) Conv. Reading = 10
 (5) Corr. Reading = Conv. Reading X Duty Cycle
 (6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/m)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			LAST CAL 10 MAR 10 CABLE C	LAST CAL 28 APR 10 BICONILOG S/N:00029390				729
345.00	h	63.33	2.3	15.00	10752.3	10.0%	1075.2	7292
690.00	h	39.86	3.2	19.90	1406.0	10.0%	140.6	729
1035.00	h	25.22	4.4	22.80	417.8	10.0%	41.8	500
1380.00	h	18.21	4.9	26.50	302.3	10.0%	30.2	500
1725.00	h	37.50	5.5	28.70	3845.9	10.0%	384.6	729
2070.00	h	32.03	6.4	30.40	2763.8	10.0%	276.4	729
2415.00	h	28.61	6.9	32.40	2486.0	10.0%	248.6	729
2760.00	h	24.52	7.4	33.60	1888.0	10.0%	188.8	500
3105.00	h	24.70	7.9	33.00	1905.5	10.0%	190.5	729
3450.00	h	16.00	9.2	33.30	841.4	10.0%	84.1	729
4000			LAST CAL 10 MAR 10 CABLE C	LAST CAL 28 APR 10 BICONILOG S/N:00029390				