

HONEYWELL SECURITY & CUSTOM ELECTRONICS
2 Corporate Center Drive
Melville, NY 11747

REV K FEB 10

EXHIBIT 5-3

FCC ID: CFS8DL5816OD

Date : 06/28/2010 Tested by : G. BARBATO Approved by : K. Eskildsen
Test Sample (model) : 344.94 MHz 5816OD
Test method: ANSI C63.4 - 2004
Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 7
Notes: (1) Fo = 344.94 MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.
Emissions not reported were more than 20dB below the specified unit.
[(Meter reading + Cable/Amp factor + Antenna factor) / 20]]
(4) Conv. Reading = 10
(5) Corr. Reading = Conv. Reading X Duty Cycle
(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/m)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			LAST CAL 16 FEB 09 CABLE C	LAST CAL 10 JUL 09 BICONILOG S/N:00045682				729
344.94	v	79.21	2.3	14.37	62230.0	10.0%	6223.0	7292
689.88	v	36.15	3.2	19.66	892.3	10.0%	89.2	729
1034.82	v	28.34	4.4	25.22	790.7	10.0%	79.1	500
1379.76	v	28.29	4.9	26.35	948.4	10.0%	94.8	500
1724.70	v	20.92	5.5	27.49	496.0	10.0%	49.6	729
2069.64	v	24.20	6.4	31.34	1250.3	10.0%	125.0	729
2414.58	v	21.39	6.9	31.81	1011.6	10.0%	101.2	729
2759.52	v	22.20	7.4	31.56	1142.9	10.0%	114.3	500
3104.46	v	23.37	7.9	32.34	1515.3	10.0%	151.5	729
3449.40	v	24.31	9.2	33.09	2138.0	10.0%	213.8	729
4000			LAST CAL 16 FEB 09 CABLE C	LAST CAL 10 JUL 09 BICONILOG S/N:00045682				