

HONEYWELL SECURITY & CUSTOM ELECTRONICS

REV 2011C

**2 Corporate Center Drive
Melville, NY 11747**

EXHIBIT 5-3

FCC ID: CFS8DL 5818MNL

Date : 20-Jun 2011

Tested by: G. BARBATO

Approved by: K. Eskildsen

Test Sample (model): 5818MNL

Test method: ANSI C63.4 - 2004

Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 7

Notes: (1) Fo: 344.94 (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz):	Sense Antenna Polarity (V/H):	THE ORENTATION OF THE UUT (V,H,O):	Meter Reading (dB uV):	Cable/Amp Factor (dB):	Antenna Factor (dB/m):	Conv. Reading (uV/M):	Duty Cycle (%):	Corr. Reading (uV/M):	Limit @ 3M (uV/M):
344.94	H	O	60.53	2.3	13.81	6794.4	10.0%	679.4	7292
689.88	H	V	32.90	3.2	19.44	598.7	10.0%	59.9	729
1034.82	V	V	16.95	4.4	23.84	181.7	10.0%	18.2	500
1379.76	V	V	17.00	4.9	26.08	250.6	10.0%	25.1	500
1724.70	H	H	16.58	5.5	28.07	321.8	10.0%	32.2	729
2069.64	H	O	17.24	6.4	30.00	480.7	10.0%	48.1	729
2414.58	H	H	17.00	6.9	32.01	624.5	10.0%	62.4	729
2759.52	H	V	17.27	7.4	32.88	753.8	10.0%	75.4	500
3104.46	H	H	17.40	7.9	32.34	762.0	10.0%	76.2	729
3449.40	V	O	17.44	9.2	33.44	1008.8	10.0%	100.9	729
4000				LAST CAL 05 FEB 11 CABLE C	LAST CAL 09-SEP-10 BICONILOG S/N:0004568 2				