

HONEYWELL SECURITY & CUSTOM ELECTRONICS

REV 2011C

**2 Corporate Center Drive
Melville, NY 11747**

EXHIBIT 5-3

FCC ID: CFS8DL 5820L

Date : 27-Jun 2011

Tested by: G. BARBATO

Approved by: K. Eskildsen

Test Sample (model): 5820L

Test method: ANSI C63.4 - 2004

Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 8

Notes: (1) Fo: 344.94 (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz):	Sense Antenna Polarity (V/H):	THE ORENTATION OF THE UUT (V,H,O,):	Meter Reading (dB uV):	Cable/Amp Factor (dB):	Antenna Factor (dB/m):	Conv. Reading (uV/M):	Duty Cycle (%):	Corr. Reading (uV/M):	Limit @ 3M (uV/M):
344.94	V	H	58.80	2.3	14.80	6235.9	10.0%	623.6	7292
689.88	H	O	31.52	3.2	19.44	510.7	10.0%	51.1	729
1034.82	V	O	17.35	4.4	23.84	190.4	10.0%	19.0	500
1379.76	V	V	17.39	4.9	26.08	262.2	10.0%	26.2	500
1724.70	H	V	17.39	5.5	28.07	353.1	10.0%	35.3	729
2069.64	V	V	16.92	6.4	30.28	478.8	10.0%	47.9	729
2414.58	H	O	17.19	6.9	32.01	638.4	10.0%	63.8	729
2759.52	V	V	17.09	7.4	31.56	634.9	10.0%	63.5	500
3104.46	H	V	17.07	7.9	32.34	733.8	10.0%	73.4	729
3449.40	H	V	17.44	9.2	33.01	960.7	10.0%	96.1	729
4000				LAST CAL 05 FEB 11 CABLE C	LAST CAL 09-SEP-10 BICONILOG S/N:0004568 2				