

HONEYWELL SECURITY & CUSTOM ELECTRONICS

REV 10-17-2011-H

**2 Corporate Center Drive
Melville, NY 11747**

EXHIBIT 5-3

FCC ID: CFS8DL 58241

Date : 10-Jan 2012 Tested by: G. BARBATO Approved by: K. Eskildsen

Test Sample (model): 58241

Test method: ANSI C63.4 - 2003

Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 8

Notes: (1) Fo: 344.94

PRESCAN:			
SENSE / UUT:	EL (cm):	AZ (deg):	Meter Reading (dB uV):
V/V	146.3	270	59.7
H/V	100	360	51.81
V/H	150	135	35.37
H/H	100	270	58.86
V/O	146.5	265	34.27
H/O	100	300	36.87

(2) Detector = Peak

(3) Frequency range scanned to 4 GHz.

(Emissions not reported were more than 20dB below the specified unit).

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz):	Sense Antenna Polarity (V/H):	THE ORENTATION OF THE UUT	Meter Reading (dB uV):	Cable/Amp Factor (dB):	Antenna Factor (dB/m):	Conv. Reading (uV/M):	Duty Cycle (%):	Corr. Reading (uV/M):	Limit @ 3M (uV/M):
344.94	V	V	59.70	2.5	15.28	7,481.7	10.0%	748.2	7292
689.88	V	V	27.33	3.7	19.89	352.4	10.0%	35.2	729
1034.82	V	V	26.50	4.7	24.12	583.4	10.0%	58.3	500
1379.76	V	O	27.83	5.6	26.06	944.1	10.0%	94.4	500
1724.70	V	O	26.45	6.3	28.54	1,154.8	10.0%	115.5	729
2069.64	V	V	24.11	7.3	31.75	1,430.5	10.0%	143.1	729
2414.58	V	V	22.46	8.1	31.79	1,304.7	10.0%	130.5	729
2759.52	V	V	25.25	8.6	31.54	1,862.1	10.0%	186.2	500
3104.46	V	V	24.87	9.1	31.95	1,979.2	10.0%	197.9	729
3449.40	V	V	24.43	10.0	33.70	2,541.0	10.0%	254.1	729
4000				LAST CAL 17 OCT 11 CABLE D	LAST CAL 21-AUG-11 BICONILOG S/N:00045682				