

HONEYWELL SECURITY & CUSTOM ELECTRONICS

REV 2011D

**2 Corporate Center Drive
Melville, NY 11747**

EXHIBIT 5-3

FCC ID: CFS8DL 5831-3

Date : 29-Jul 2011 Tested by: G. Barbato Approved by K. Eskildsen
 Test Sample (model): 5831-3
 Test method: ANSI C63.4 - 2004
 Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 8
 Notes: (1) Fo: 344.94 (2) Detector = Peak (3) Frequency range scanned to 4 GHz.
 Emissions not reported were more than 20dB below the specified unit.
 [(Meter reading + Cable/Amp factor + Antenna factor) / 20]
 (4) Conv. Reading = 10
 (5) Corr. Reading = Conv. Reading X Duty Cycle
 (6) Six Highest Emissions Recorded

Freq. (MHz):	Sense Antenna Polarity (V/H):	THE ORENTATION OF THE UUT	Meter Reading (dB uV):	Cable/Amp Factor (dB):	Antenna Factor (dB/m):	Conv. Reading (uV/M):	Duty Cycle (%):	Corr. Reading (uV/M):	Limit @ 3M (uV/M):
344.94	H	H	61.53	2.3	14.92	8,659.6	10.0%	866.0	7292
689.88	H	H	18.17	3.2	20.12	118.7	10.0%	11.9	729
1034.82	H	H	16.46	4.4	22.89	154.0	10.0%	15.4	500
1379.76	H	H	17.26	4.9	25.71	247.3	10.0%	24.7	500
1724.70	H	H	16.77	5.5	28.58	348.9	10.0%	34.9	729
2069.64	H	H	16.56	6.4	32.39	585.4	10.0%	58.5	729
2414.58	H	H	16.53	6.9	30.49	496.3	10.0%	49.6	729
2759.52	H	H	16.34	7.4	32.33	636.2	10.0%	63.6	500
3104.46	H	H	16.34	7.9	32.63	697.2	10.0%	69.7	729
3449.40	H	H	16.41	9.2	31.94	753.8	10.0%	75.4	729
4000				LAST CAL 05 FEB 11 CABLE C	LAST CAL 17-MAY-11 BICONILOG S/N:00029390				