

HONEYWELL SECURITY & CUSTOM ELECTRONICS
2 Corporate Center Drive
Melville, NY 11747

EXHIBIT 5-3

FCC ID

CFS8DL5853-3

REV H AUG 08

Date : 02/11/2009 Tested by : Greg Barbato Approved by : K. Eskildsen
 Test Sample (model) : 5853-3 NEW FCC
 Test method: ANSI C63.4 - 2004
 Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 7
 Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.
 Emissions not reported were more than 20dB below the specified unit.
 [(Meter reading + Cable/Amp factor + Antenna factor) / 20]]
 (4) Conv. Reading = 10
 (5) Corr. Reading = Conv. Reading X Duty Cycle
 (6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/m)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			LAST CAL 04 Aug 08 CABLE C	LAST CAL 02 May 08 BICONILOG S/N:00045682				729
345	v	74.48	2.3	14.60	37068.1	10.0%	3706.8	7292
690	h	22.68	3.2	19.80	192.3	10.0%	19.2	729
1035	h	38.36	4.4	23.41	2034.7	10.0%	203.5	500
1380	h	31.99	4.9	25.74	1353.6	10.0%	135.4	500
1725	h	25.40	5.5	28.05	886.1	10.0%	88.6	729
2070	h	25.46	6.4	30.21	1269.1	10.0%	126.9	729
2415	h	23.91	6.9	32.21	1415.8	10.0%	141.6	729
2760	h	21.35	7.4	32.39	1140.2	10.0%	114.0	500
3105	h	22.82	7.9	32.29	1414.2	10.0%	141.4	729
3450	h	23.08	9.2	32.91	1817.6	10.0%	181.8	729
4000			LAST CAL 04 Aug 08 CABLE C	LAST CAL 02 May 08 BICONILOG S/N:00045682				