

Date :6/27/07 Tested by : Azadeh Solhjoo Approved by :K.Addy

Test Sample (model) : 5853-3

Test method: ANSI C63.4 - 2004

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/m)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A"	BICONILOG S/N:00029390				729
345	h	76.89	1.3	14.90	45133.6	10.0%	4513.4	7292
690	h	40.71	1.7	19.30	1217.6	10.0%	121.8	729
1035	h	43.09	2.2	22.70	2509.0	10.0%	250.9	500
1380	h	35.29	2.5	25.80	1511.8	10.0%	151.2	500
1725	h	44.99	2.9	28.00	6230.2	10.0%	623.0	729
2070	h	40.99	3.2	30.30	5302.7	10.0%	530.3	729
2415	h	27.79	3.4	32.00	1443.8	10.0%	144.4	729
2760	h	22.39	3.5	32.80	860.0	10.0%	86.0	500
3105	h	21.19	3.7	32.50	740.5	10.0%	74.0	729
3450	h	21.22	3.9	33.00	805.4	10.0%	80.5	729
4000			CABLE "A"	BICONILOG S/N:00029390				