

HONEYWELL SECURITY & CUSTOM ELECTRONICS**165 EILEEN WAY****SYOSSET, NY 11791****EXHIBIT 5-3****FCC ID # CFS8DL5870API**

Date : 3/14/2007

Tested by :Y. Mohammed

Approved by :K.Addy

Test Sample (model) : 5870API

Test method: ANSI C63.4 - 2004

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/m)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A"	BICONILOG				729
345	H	66.30	1.3	14.50	12735.0	10.0%	1273.5	7292
690	H	38.00	1.7	18.90	851.1	10.0%	85.1	729
1035	H	38.00	2.2	22.50	1364.6	10.0%	136.5	500
1380	H	30.00	2.5	25.40	785.2	10.0%	78.5	500
1725	H	28.00	2.9	27.70	851.1	10.0%	85.1	729
2070	H	28.00	3.2	29.90	1135.0	10.0%	113.5	729
2415	H	28.00	3.4	31.80	1445.4	10.0%	144.5	729
2760	H	28.00	3.5	32.40	1566.8	10.0%	156.7	500
3105	H	28.00	3.7	32.00	1531.1	10.0%	153.1	729
3450	H	28.00	3.9	32.60	1678.8	10.0%	167.9	729
4000			CABLE "A"	BICONILOG				