

HONEYWELL SECURITY & CUSTOM ELECTRONICS

REV 2011D

**2 Corporate Center Drive
Melville, NY 11747**

EXHIBIT 5-3

FCC ID: CFS8DL 5878-1

Date : 6-Sep 2011 Tested by: G. Barbato Approved by K. Eskildsen
 Test Sample (model): 5878-1
 Test method: ANSI C63.4 - 2004
 Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 8
 Notes: (1) Fo: 344.94 (2) Detector = Peak (3) Frequency range scanned to 4 GHz.
 Emissions not reported were more than 20dB below the specified unit.
 [(Meter reading + Cable/Amp factor + Antenna factor) / 20]
 (4) Conv. Reading = 10
 (5) Corr. Reading = Conv. Reading X Duty Cycle
 (6) Six Highest Emissions Recorded

Freq. (MHz):	Sense Antenna Polarity (V/H):	THE ORENTATION OF THE UUT	Meter Reading (dB uV):	Cable/Amp Factor (dB):	Antenna Factor (dB/m):	Conv. Reading (uV/M):	Duty Cycle (%):	Corr. Reading (uV/M):	Limit @ 3M (uV/M):
344.94	H	H	72.072	2.3	14.92	29,147.4	10.0%	2914.7	7288
689.88	H	H	34.523	3.2	20.12	780.1	10.0%	78.0	729
1034.82	H	H	15.792	4.4	22.89	142.6	10.0%	14.3	500
1379.76	H	H	16.209	4.9	25.71	219.3	10.0%	21.9	500
1724.70	H	H	16.392	5.5	28.58	333.9	10.0%	33.4	729
2069.64	H	H	16.982	6.4	32.39	614.6	10.0%	61.5	729
2414.58	H	H	16.342	6.9	30.49	486.0	10.0%	48.6	729
2759.52	H	H	16.396	7.4	32.33	640.2	10.0%	64.0	500
3104.46	H	H	16.606	7.9	32.63	719.1	10.0%	71.9	729
3449.40	H	H	15.982	9.2	31.94	718.0	10.0%	71.8	729
4000				LAST CAL 05 FEB 11 CABLE C	LAST CAL 17-MAY-11 BICONILOG S/N:00029390				