

Date : 05/11/2010 Tested by : G. Barbato Approved by : K. Eskildsen

Test Sample (model) : 344.94 MHz 6150RFT3

Test method: ANSI C63.4 - 2004

Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 7

Notes: (1) Fo = 344.94 MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/m)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			LAST CAL 16 FEB 09 CABLE C	LAST CAL 10 JUL 09 BICONILOG S/N:00045682				729
344.94	h	75.25	2.3	15.35	44157.0	15.0%	6623.6	7292
689.88	h	45.50	3.2	20.02	2729.0	15.0%	409.3	729
1034.82	h	38.13	4.4	24.85	2338.8	15.0%	350.8	500
1379.76	h	18.38	4.9	25.93	288.7	15.0%	43.3	500
1724.70	h	18.48	5.5	26.96	352.4	15.0%	52.9	729
2069.64	h	17.46	6.4	31.36	576.8	15.0%	86.5	729
2414.58	h	13.21	6.9	32.15	410.2	15.0%	61.5	729
2759.52	h	15.72	7.4	32.37	595.0	15.0%	89.2	500
3104.46	h	16.02	7.9	32.73	680.0	15.0%	102.0	729
3449.40	h	17.80	9.2	33.00	1000.0	15.0%	150.0	729
4000			LAST CAL 16 FEB 09 CABLE C	LAST CAL 10 JUL 09 BICONILOG S/N:00045682				