

HONEYWELL SECURITY & CUSTOM ELECTRONICS

REV 04-24-2012-J

2 Corporate Center Drive

Melville, NY 11747

EXHIBIT 5-3

FCC ID: CFS8DL

6160RF-2

Date : 5-Jul 2012 Tested by: G. BARBATO Approved by: K. Eskildsen

Test Sample (model): 6160RF-2

Test method: ANSI C63.4 - 2004

Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 8

Notes: (1) Fo: 344.94

PRESCAN:			
SENSE / UUT:	EL (cm):	AZ (deg):	Meter Reading (dB uV):
V/V	150.6	0/360	68.57
H/V	100.0	180.0	62.11
V/H	182.4	0/360	59.78
H/H	100.0	180.0	64.35
V/O	153.5	0/360	68.50
H/O	100.0	180.0	62.95

- (2) Detector = Peak
- (3) Frequency range scanned to 4 GHz.
- (Emissions not reported were more than 20dB below the specified unit).

$$[(\text{Meter reading} + \text{Cable/Amp factor} + \text{Antenna factor}) / 20]$$
- (4) Conv. Reading = 10
- (5) Corr. Reading = Conv. Reading X Duty Cycle
- (6) Six Highest Emissions Recorded

Freq. (MHz):	Sense Antenna Polarity (V/H):	THE ORENTATION OF THE UUT	Meter Reading (dB uV):	Cable/Amp Factor (dB):	Antenna Factor (dB/m):	Conv. Reading (uV/M):	Duty Cycle (%):	Corr. Reading (uV/M):	Limit @ 3M (uV/M):
344.94	H	H	68.57	2.5	15.47	21,232.4	15.2%	3227.3	7,289
689.88	V	V	28.89	3.7	19.89	421.7	15.2%	64.1	729
1034.82	V	V	23.57	4.7	24.12	416.4	15.2%	63.3	500
1379.76	V	V	22.07	5.6	26.06	486.4	15.2%	73.9	500
1724.70	V	V	20.89	6.3	28.54	608.8	15.2%	92.5	729
2069.64	V	V	23.88	7.3	31.75	1,393.2	15.2%	211.8	729
2414.58	V	V	22.09	8.1	31.79	1,250.3	15.2%	190.0	729
2759.52	V	V	22.13	8.6	31.54	1,300.2	15.2%	197.6	500
3104.46	V	V	23.37	9.1	31.95	1,665.3	15.2%	253.1	729
3449.40	V	V	23.57	10.0	33.70	2,301.4	15.2%	349.8	729
4000				LAST CAL 17 OCT 11 CABLE D	LAST CAL 21-AUG-11 BICONILOG S/N:00045682				