

Date : 09/01/2011 Tested by : G. BARBATO Approved by : K. Eskildsen
Test Sample (model) : 6280Z
Test method: ANSI C63.4 - 2004
Test specification: FCC Part 15.249, and RSS 210 , Issue 8
Notes: (1) Fo = 908.42 MHz. (2) Detector = Peak (3) Frequency range scanned to 10 GHz.
Emissions not reported were more than 20dB below the specified unit.
[(Meter reading + Cable/Amp factor + Antenna factor) / 20]]
(4) Conv. Reading = 10
(5) Corr. Reading = Conv. Reading X Duty Cycle
(6) Six Highest Emissions Recorded

Freq. (MHz)	USE FILTER:	Antenna Polarity (V/H)	UUT Orientation (V/H/O)	Meter Reading (dB uV)	Cable Loss & Amp Factor (dB)	Antenna Factor (dB/m)	Conv. Reading (uV/M)	Corr. Reading (mV/M)	Limit @ 3M
					VERIFY BEFORE USE	BICONOLOG Model: 3149 s/n: 00045682 CAL 21 Aug 11			
908.42	NONE	V	V	65.67	3.30	22.63	-----	38.0	50 mV/M
1,816.84	A	V	V	15.67	-27.60	26.19	5.2	-----	500 uV/M
2,725.26	A	V	O	27.50	-27.15	28.57	27.9	-----	500 uV/M
3,633.68	B	V	H	31.17	-27.10	30.82	55.5	-----	500 uV/M
4,542.10	C	V	V	17.17	-24.65	31.80	16.4	-----	500 uV/M
5,450.52	C	V	V	15.67	-23.92	33.99	19.4	-----	500 uV/M
6,358.94	C	V	V	14.57	-23.17	34.80	20.4	-----	500 uV/M
7,267.36	C	V	V	16.15	-22.33	36.12	31.4	-----	500 uV/M
8,175.78	D	V	V	11.23	-20.36	36.78	24.1	-----	500 uV/M
9,084.20	D	V	V	12.21	-20.12	37.63	30.6	-----	500 uV/M
with 0.9 inch antenna extension power set to: 0x29					VERIFY BEFORE USE	RGA 60 HORN S/N: 3127 LAST CAL 10 APR 11			