

DATA SHEET

DATE: 7/07/00 TESTED BY: J. Fitzgerald APPROVED BY: J
 TEST SAMPLE (model): ADEMCO Transmitter FA2602F
 TEST METHOD: ANSI C63.4 - 1992

TEST SPECIFICATION: _____

NOTES: 1) Fc = _____ MHz, 2) Detector = Peak, 3) Frequency range scanned to
 4 GHz. Emissions not reported were more than 20 dB below the specified limit.

4) Conv. reading = $10^{\frac{(\text{Meter reading} + \text{Cable/Amp factor} + \text{Antenna factor})}{20}}$

5) Corr. reading = _____

FREQUENCY (MHz)	POLARITY (V / H)	METER READING (dB μ V)	CABLE/AMP FACTOR (dB)	ANTENNA FACTOR (dB/M)	CONV. READING (μ V/M)	DUTY CYCLE (%)	CORR. READING (μ V/M)	LIMIT @ 3M (μ V/M)
	H					10%		
30			1					
345		78.5	1.1	16	6237.3		6237.3	7292
690		44.7	1.8	21.1	2398.8		239.88	729
1035		45.4	2.1	25.2	4315.2		431.5	500
1380		39.4	2.5	28.8	3427.6		342.76	500
1725		38.6	3.0	31.2	4365		436.5	729
4000								

®ADEMCO

Alarm Device Manufacturing Company
 A Division of Pittway Corporation
 165 Eileen way
 Syosset, NY 11791