

Date : 11/23/2009 Tested by : G. Barbato Approved by : K. Eskildsen
 Test Sample (model) : 344.94 MHz Classic Lynx
 Test method: ANSI C63.4 - 2004
 Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 7
 Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.
 Emissions not reported were more than 20dB below the specified unit.
 [(Meter reading + Cable/Amp factor + Antenna factor) / 20]
 (4) Conv. Reading = 10
 (5) Corr. Reading = Conv. Reading X Duty Cycle
 (6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/m)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			LAST CAL 16 FEB 09 CABLE C	LAST CAL 10 JUL 09 BICONILOG S/N:00045682				729
345	v	76.12	2.3	14.37	43601.4	15.0%	6540.2	7292
690	v	28.56	3.2	19.66	372.4	15.0%	55.9	729
1035	v	30.80	4.4	25.22	1049.5	15.0%	157.4	500
1380	v	26.84	4.9	26.35	802.6	15.0%	120.4	500
1725	v	26.17	5.5	27.49	907.8	15.0%	136.2	729
2070	v	24.56	6.4	31.34	1303.2	15.0%	195.5	729
2415	v	26.01	6.9	31.81	1721.9	15.0%	258.3	729
2760	v	24.52	7.4	31.56	1492.8	15.0%	223.9	500
3105	v	25.27	7.9	32.34	1885.8	15.0%	282.9	729
3450	v	24.92	9.2	33.09	2293.5	15.0%	344.0	729
4000			LAST CAL 16 FEB 09 CABLE C	LAST CAL 10 JUL 09 BICONILOG S/N:00045682				