HONEYWELL SECURITY & CUSTOM ELECTRONICS **REV 04-24-2012-J**
2 Corporate Center Drive
Melville, NY 11747 **EXHIBIT 5-3** **FCC ID: CFS8DL** **LYNXPLUS2**

Date : 10-Aug 2012 Tested by: G. BARBATO Approved by: K. Eskildsen
Test Sample (model): LYNXPLUS2
Test method: ANSI C63.4 - 2004
Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 8

PRESCAN:			
SENSE / UUT:	EL (cm):	AZ (deg):	Meter Reading (dB uV):
V/V			
H/V			
V/H			
H/H	100.0	0/360	74.65
V/O			
H/O			

Notes: (1) Fo: 344.94
(2) Detector = Peak
(3) Frequency range scanned to 4 GHz.
(Emissions not reported were more than 20dB below the specified unit).
[(Meter reading + Cable/Amp factor + Antenna factor) / 20)]
(4) Conv. Reading = 10
(5) Corr. Reading = Conv. Reading X Duty Cycle
(6) Six Highest Emissions Recorded

Freq. (MHz):	Sense Antenna Polarity (V/H):	THE ORENTATION OF THE UUT	Meter Reading (dB uV):	Cable/Amp Factor (dB):	Antenna Factor (dB/m):	Conv. Reading (uV/M):	Duty Cycle (%):	Corr. Reading (uV/M):	Limit @ 3M (uV/M):
344.94	H	H	74.65	2.5	15.47	42,756.3	15.0%	6413.4	7,289
689.88	H	H	36.35	3.7	19.36	936.5	15.0%	140.5	729
1034.82	H	H	19.70	4.7	22.72	227.0	15.0%	34.0	500
1379.76	H	H	13.45	5.6	25.47	168.5	15.0%	25.3	500
1724.70	H	H	11.62	6.3	27.64	188.8	15.0%	28.3	729
2069.64	H	H	14.62	7.3	29.85	385.5	15.0%	57.8	729
2414.58	H	H	13.25	8.1	31.89	457.1	15.0%	68.6	729
2759.52	H	H	14.44	8.6	32.83	622.3	15.0%	93.3	500
3104.46	H	H	13.78	9.1	32.63	597.0	15.0%	89.6	729
3449.40	H	H	15.58	10.0	33.14	860.0	15.0%	129.0	729
4000				LAST CAL 17 OCT 11 CABLE D	LAST CAL 21-AUG-11 BICONILOG S/N:00045682				