

## EXHIBIT 2

### Circuit Description.

#### **CFS8DLLYNXR**

The LYNX is constructed on a pair of PCBs interconnected via a ribbon cable.

The main PCB contains the RF transmitter and receiver circuitry as well as all control, display, keypad and annunciation circuitry.

The transmitter is a SAW resonator Colpitts oscillator, Q26, XTL4 etc. The transmitter is on-off keyed (AM) modulated by a control signal from the microcontroller U18 which turns PA Q30 on or off via Q28/Q29, thus modulating the output signal. The RF output signal is connected to two PCB mounted antennas via Helical filter L1 and diodes CR32/CR33.

The receiver is a superhet with a single intermediate frequency at 10.7MHz. Q31 etc. is the low noise amplifier which is connected to the PCB mounted antennas. Diodes CR32/CR33 under the control of a microcontroller are periodically switched to provide system antenna diversity. The IC U22 includes a balanced mixer which converts the incoming signal down from 345MHz to 10.7MHz. This IC also includes the required IF gain and detected output. FL1 is a ceramic IF filter. IC U19 performs video filtering and processing and provides a data signal. The local oscillator (XTL3/Q32) is a 59.28333 Mhz Xtal oscillator which outputs 355.7MHz to the mixer via multiplier L3/C115/C116.

