

ALARM DEVICE MANUFACTURING COMPANY
165 EILEEN WAY
SYOSSET, NY 11791

FCC ID# _____

JUNE 30, 2000

DATE: _____ TESTED BY: *[Signature]* APPROVED BY: _____

ADEMCO LYNXRU4 (TRANSMITTER)

TEST SAMPLE (model): _____

TEST METHOD: ANSI C63.4-1992

TEST SPECIFICATION: FCC PART 15, SUBPART C.

- NOTES: 1) F₀= 345 MHZ
 2) DETECTOR = PEAK.
 3) FREQUENCY RANGE SCANNED TO 4 GHz.

$$4) \text{ CONVERTED READING} = 10 \left[\frac{(\text{METER READING} + \text{CABLE /AMP FACTOR} + \text{ANTENNA FACTOR})}{20} \right]$$

5) CORRECTED READING = CONVERTED READING X DUTY CYCLE

6) SIX HIGHEST EMISSIONS RECORDED.

Frequency (MHz)	Antenna Polarity (V-H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Converted Reading (uV/M)	Duty Cycle (%)	Corrected Reading (uV/M)	Limit @ 3 Meter (uV/M)
30								729
345	H	77.0	1.3	15.1	46774	15.26	7138	7292
690	H	51.0	1.8	20.6	4677	15.26	714	729
1035	V	33.5	2.0	24.5	1000	15.26	153	500
1380	V	35.9	2.6	27.1	2089	15.26	319	500
1725	V	34.5	3.0	30.0	2371	15.26	362	729
2070	V	40.6	3.4	28.0	3981	15.26	608	729
4000								729

NOTES: