

Date : 10/04/2007

Tested by :G. BARBATO

Approved by :K.Addy

Test Sample (model) : LYNX-GSM

Test method: ANSI C63.4 - 2004

Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 7

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/m)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A" + "B"	03/12/2007 BICONILOG S/N:00029390				729
345	h	64.89	2.6	14.90	13167.4	15.0%	1975.1	7292
690	h	28.59	3.7	19.30	379.8	15.0%	57.0	729
1035	h	26.99	4.7	22.70	524.2	15.0%	78.6	500
1380	h	29.39	5.5	25.80	1082.7	15.0%	162.4	500
1725	h	34.69	6.3	28.00	2815.1	15.0%	422.3	729
2070	h	30.69	7.0	30.30	2509.0	15.0%	376.3	729
2415	h	21.59	7.6	32.00	1146.8	15.0%	172.0	729
2760	h	21.59	8.5	32.80	1394.8	15.0%	209.2	500
3105	h	21.59	9.0	32.50	1427.2	15.0%	214.1	729
3450	h	22.79	10.7	33.00	2111.1	15.0%	316.7	729
4000			CABLE "A" + "B"	03/12/2007 BICONILOG S/N:00029390				