

Date : 02/23/2011      Tested by : G. BARBATO      Approved by : K. Eskildsen  
 Test Sample (model) : 344.94 MHz L5000/LYNX TOUCH  
 Test method: ANSI C63.4 - 2004  
 Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 7  
 Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.  
 Emissions not reported were more than 20dB below the specified unit.  
 [(Meter reading + Cable/Amp factor + Antenna factor) / 20 ]  
 (4) Conv. Reading = 10  
 (5) Corr. Reading = Conv. Reading X Duty Cycle  
 (6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/m)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			LAST CAL 05 FEB 11 CABLE C	LAST CAL 28 APR 10 BICONILOG S/N:00029390				729
344.94	v	76.44	2.3	14.40	45394.2	15.22%	6910.6	7292
689.88	v	22.75	3.2	20.00	198.4	15.22%	30.2	729
1034.82	v	22.88	4.4	24.30	379.3	15.22%	57.7	500
1379.76	v	22.55	4.9	28.40	620.2	15.22%	94.4	500
1724.70	v	22.75	5.5	29.30	754.2	15.22%	114.8	729
2069.64	v	23.33	6.4	31.10	1100.3	15.22%	167.5	729
2414.58	v	22.73	6.9	32.50	1277.9	15.22%	194.5	729
2759.52	v	23.06	7.4	32.50	1406.0	15.22%	214.0	500
3104.46	v	22.49	7.9	32.60	1410.9	15.22%	214.7	729
3449.40	v	21.57	9.2	34.50	1834.4	15.22%	279.2	729
4000			LAST CAL 05 FEB 11 CABLE C	LAST CAL 28 APR 10 BICONILOG S/N:00029390				