



## !D Hand 2

### RFID Technology

THE !D HAND 2 IS A RFID HANDHELD READER IN A REVOLUTIONARY DESIGN. THE HANDHELD READER WAS DESIGNED WITH USERS IN MIND; WITH ONLY ONE BUTTON TO ACTIVATE AND OPERATE, YOU OFFER YOUR STAFF A UNIQUE AND USER-FRIENDLY APPLICATION. THE !D HAND 2 IS LIGHTWEIGHT, AND KNOWN FOR ITS PERFORMANCE WITH OUTSTANDING RFID READING AND WRITING CAPABILITIES.

#### SPECIFICATIONS

- Lightweight and superior ergonomics
- Optimal reading performance
- Single button user interface
- Vibration motor and beeper
- 2D imaging barcode scanner
- Can be charged wirelessly in a docking station
- Compatible with iPod, iPhone and iPad\*, and other Bluetooth-enabled devices
- Designed in collaboration with major retailers for optimum ease of use
- Open API available for integration by system integrators and/or retailers



**OPTIONS**

- Bumper to protect the !D Hand in rough environments
- Docking station to charge the !D Hand 2 wireless

**ORDERING INFORMATION**

Description	Article number
ASSY HH2 RFID R1 WHITE	9215441
ASSY HH2 RFID R2 WHITE	9565035

Region 1: Europe (ETSI EN 302 208), Armenia, Azerbaijan, Hong Kong, India, Jordan, Oman, Russia, Saudi Arabia, South Africa, Tunisia, United Arab Emirates and Vietnam

Region 2: United States (FCC Part 15.247), Australia, Brazil, Argentina, Canada, Chile, Colombia, Costa Rica, Dominican Republic, Israel, Mexico, New Zealand, Panama, Peru, Taiwan, Uruguay and Venezuela

**PACKAGE INCLUDES**

- !D Hand 2
- Micro USB charger

**TECHNICAL SPECIFICATIONS**

• Air interface protocol	EPCglobal UHF Class 1 Gen 2 / ISO 18000-6C
• Supported region	Region 1
• Radiated power	Europe (ETSI EN 302 208): 2W erp
• Antenna type	Cross-dipole
• Maximum tag throughput	200 labels per second
• Reading distance	1.5m - 3.0m / 4.92ft - 9.84ft (depending on label and orientation)
• Barcode reader	2D imaging (CMOS) barcode scanner
• Connectivity	Bluetooth, USB, Wireless charging (Qi)
• Battery life	Standby, when connected over Bluetooth: 36 hours. When reading: 4 hours. Not connected, standby: 1 month
• Dimensions	318 x 112 x 38mm 1.04ft x 4.41"ft x 1.5"
• Weight	264 gr / 0.58 lbs
• Mains	100 - 240V
• Operating temp.	0 .. 45°C, 0 .. 113°F

