

OPERATIONAL DESCRIPTION

DESCRIPTION OF EQUIPMENT

FCC Section 2.1033

- | | |
|--|---|
| 1) Type of Emission: (c)(4) | 64/256 QAM; 6M00D7W |
| 2) Frequency Range: (c)(5) | 2000-2700 MHz in select bands |
| 3) Operating Range: (c)(6) | 2 – 25 watts |
| 4) Power Rating: (c)(7) | 25 watts average |
| 5) Variation of output power (c)(6) | See calibration section, document #
DOC16-0057 of technical manual |
| 6) E & I on Final: (c)(8) | |
| Drain voltage | 10V |
| Drain current | 7A each |
| 7) Tune-up Procedures: (c)(9) | See calibration section, document #
DOC16-0057 of technical manual |
| 8) Function of Active Devices: (c)(10) | |

A list of active devices in the RF chains of the SD2500C transmitter can be found in the tune-up section. The relative position of each device may be found by referring to the block diagrams and schematics found in the technical manual.

- ❖ Frequency Stability Devices: See technical manual, document # DOC14-0038
- ❖ Spurious Suppression Circuits[k5]: Not applicable
- ❖ Describe Limiters:
 - Modulation: Not applicable
 - Power: See technical manual, document # DOC13-0177