



## Test Report - FCC Part 1.1310/ MPE

Applicant: HENSOLDT UK, a trading name of Kelvin  
Hughes Limited

This test report relates only to the items tested as identified and is not valid for any subsequent changes or modifications made to the equipment under test.

## Table of Contents

---

1. APPLICANT INFORMATION.....	3
2. LOCATION OF TESTING.....	3
2.1 TEST LABORATORY.....	3
2.2 TESTING WAS PERFORMED, REVIEWED BY .....	4
3. TEST SAMPLE(S) (EUT/DUT).....	5
3.1 DESCRIPTION OF THE EUT .....	5
4. TEST METHODS & APPLICABLE REGULATORY LIMITS.....	6
4.1 TEST METHODS/STANDARDS/GUIDANCE:.....	6
4.1.1 FCC Limits for Maximum Permissible Exposure (MPE) .....	6
4.2 EQUATIONS .....	7
5. RF EXPOSURE RESULTS .....	8
6. HISTORY OF TEST REPORT CHANGES.....	9

## 1. Applicant Information

**Applicant:** HENSOLDT UK, a trading name of Kelvin Hughes Limited  
**Address:** Voltage, Mollison Avenue  
Enfield, ESSEX, EN3 7XQ  
United Kingdom

## 2. Location of Testing

### 2.1 Test Laboratory


Timco Engineering Inc. is a subsidiary of Industrial Inspection & Analysis, Inc. ("IIA"). Testing was performed at IIA's permanent laboratory located at 13146 NW 86<sup>th</sup> Drive, Suite 400, Alachua, Florida 32615.

FCC test firm # 578780  
FCC Designation # US1070  
FCC site registration is under A2LA certificate # 0955.01  
ISED Canada test site registration # 2056A  
EU Notified Body # 1177  
For all designations see A2LA scope # 0955.01

## 2.2 Testing was performed, reviewed by

Dates of Testing: 01/16/2023 – 03/23/2023

Signature:

  
\_\_\_\_\_  
Sr. EMC Engineer  
EMC-003838-NE   
CERTIFIED  
iMARIE  
ENGINEERName & Title: Tim Royer, EMC EngineerDate of Signature 04/26/2023

### 3. Test Sample(s) (EUT/DUT)

The test sample was received: 01/16/2023

#### 3.1 Description of the EUT

A description as well as unambiguous identification of the EUT(s) tested. Where more than one sample is required for technical reasons (such as the use of connected units for the purpose of conducted output power testing where the product units will have integral antennas), each specific test shall identify which unit was tested.

Identification	
FCC ID:	CICPCV-A1
Brief Description	Mk5 Sharp Eye Radar
Model(s) #	Mk5 Sharp Eye
Firmware version	n/a
Software version	ZM-2924 Version 1.3

Technical Characteristics	
Frequency Range	9.1 – 9.5 GHz
RF O/P Power (Max.)	62.8 W/ Nominal peak output power into the antenna of 80 W
Modulation	FM Pulse/FM Chirp
Bandwidth & Emission Class	53M5PON
Number of Channels	14
Duty Cycle	6NM 4.26%, 12NM 7.90%, 24NM 7.59%
Antenna Connector	Flange
Voltage Rating (AC or Batt.)	28V DC

Antenna Characteristics			
Antenna	Frequency Range	Mode / BW	Antenna Gain
1	n/a	n/a	0 dBi

- Note: Information such as antenna gain, firmware/software numbers are provided by manufacturer and cannot be validated by the test lab.

## 4. Test methods & Applicable Regulatory Limits

### 4.1 Test methods/Standards/Guidance:

The following guidance FCC KDB 447498 D01 General RF Exposure Guidance v06 was used for RF exposure evaluation as per FCC Part 1.1310 and FCC Part 2.1091 and part 2.1093. Full test results are available in this report.

#### 4.1.1 FCC Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
<b>A Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
<b>B Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

## 4.2 Equations

### POWER DENSITY

$$E(V/m) = \text{SQRT} ( 30 * P * G ) / d$$

$$Pd(W/m^2) = E^2 / 377$$

$$S = \text{EIRP} / ( 4 * \pi * D^2 )$$

Where:

S = Power density, in mW/cm<sup>2</sup>

EIRP = Equivalent Isotropic Radiated Power, in mW

D = Separation distance in cm

Power density is converted from units of mW/cm<sup>2</sup> to units of W/m<sup>2</sup> by multiplying by 10.

### DISTANCE

$$D = \text{SQRT} ( \text{EIRP} / ( 4 * \pi * S ) )$$

Where:

D = Separation distance in cm

EIRP = Equivalent Isotropic Radiated Power, in mW

S = Power density in mW/cm<sup>2</sup>

**SOURCE-BASED DUTY CYCLE** (When applicable (for example, multi-slot mobile phone applications) A duty cycle factor may be applied.)

$$\text{Source-based time-average EIRP} = ( DC / 100 ) * \text{EIRP}$$

Where:

DC = Duty Cycle in % as applicable.

EIRP = Equivalent Isotropic radiated Power, in mW

## 5. RF Exposure Results

MPE									
Frequency Band	Evaluation Distance (cm)	Max Power + Tolerance (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	EIRP (W)	Power Density	Limit for Uncontrolled Exposure	Limit for Controlled Exposure	Distance Required to meet Uncontrolled Exposure Limit (cm)
9100-9500 MHz	20	38.98	0.00	8%	7.9000	1.572 mW/cm <sup>2</sup>	1 mW/cm <sup>2</sup>	5 mW/cm <sup>2</sup>	25.07

RESULT: Pass at DISTANCE 25.07 cm

## 6. History of Test Report Changes

Test Report #	Revision #	Description	Date of Issue
TR_6172-23_FCC 1.1310/ MPE_	1	Initial release	03/28/2023
	2	Updated Page 8	5/1/2024
	3	Updated Page 1	9/9/2024



13146 NW 86<sup>th</sup> Drive, Suite 400, Alachua, Florida 32615  
(352) 472-5500 / [testing@industrial-ia.com](mailto:testing@industrial-ia.com)

---

END OF TEST REPORT

---