



FCC RADIO TEST REPORT

Applicant's company	Toshiba Corporation
Applicant Address	2-9, Suehiro-Cho, Ome, 198-8710 Tokyo, Japan
FCC ID	CJ6-U66G
Manufacturer's company	Toshiba Corporation
Manufacturer Address	2-9, Suehiro-Cho, Ome, 198-8710 Tokyo, Japan

Product Name	2.4GHz Wireless Keyboard
Brand Name	Toshiba
Model Name	U66G
Test Rule Part(s)	47 CFR FCC Part 15 Subpart C § 15.249
Test Freq. Range	2403 ~ 2478MHz
Received Date	Feb. 07, 2013
Final Test Date	Mar. 14, 2013
Submission Type	Original Equipment



Statement

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2009** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Testing Laboratory
1190

Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION.....	3
3.1. Product Details	3
3.2. Accessories	3
3.3. Table for Carrier Frequencies	3
3.4. Table for Filed Antenna	4
3.5. Table for Test Modes	4
3.6. Table for Testing Locations.....	4
3.7. Table for Supporting Units	5
3.8. Test Configurations.....	6
4. TEST RESULT.....	8
4.1. Field Strength of Fundamental Emissions Measurement.....	8
4.2. 20dB Spectrum Bandwidth Measurement	13
4.3. Radiated Emissions Measurement.....	16
4.4. Band Edge Emissions Measurement.....	25
4.5. Antenna Requirements	27
5. LIST OF MEASURING EQUIPMENTS	28
6. TEST LOCATION.....	30
APPENDIX A. TEST PHOTOS.....	A1 ~ A4



History of This Test Report

Certificate No.: CB10203253

1. CERTIFICATE OF COMPLIANCE

Product Name : 2.4GHz Wireless Keyboard
Brand Name : Toshiba
Model Name : U66G
Applicant : Toshiba Corporation
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.249

Sportun International as requested by the applicant to evaluate the EMC performance of the product sample received on Feb. 07, 2013 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Reviewed By:

Sam Chen

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
-	15.207	AC Power Line Conducted Emissions	-	Note
4.1	15.249(a)	Field Strength of Fundamental Emissions	Complies	7.94 dB
4.2	15.215(c)	20dB Spectrum Bandwidth	Complies	-
4.3	15.249(a)/(d)	Radiated Emissions	Complies	7.25 dB
4.4	15.249(d)	Band Edge Emissions	Complies	12.08 dB
4.5	15.203	Antenna Requirements	Complies	-

Note: The EUT is a DC-powered (AA Battery) equipment; it's not necessary to apply for AC Power Line Conducted Emissions test.

Test Items	Uncertainty	Remark
Field Strength of Fundamental Emissions	$\pm 0.8\text{dB}$	Confidence levels of 95%
20dB Spectrum Bandwidth	$\pm 8.5 \times 10^{-8}$	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	$\pm 0.8\text{dB}$	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	$\pm 1.9\text{dB}$	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	$\pm 1.9\text{dB}$	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	$\pm 1.9\text{dB}$	Confidence levels of 95%
Temperature	$\pm 0.7^\circ\text{C}$	Confidence levels of 95%
Humidity	$\pm 3.2\%$	Confidence levels of 95%
DC / AC Power Source	$\pm 1.4\%$	Confidence levels of 95%

3. GENERAL INFORMATION

3.1. Product Details

Items	Description
Power Type	From AA Battery
Modulation	GFSK
Frequency Range	2403 ~ 2478MHz
Channel Number	76
Channel Band Width (99%)	1.88 MHz
Max. Field Strength	86.06 dBuV/m at 3m (Average)
Channel Bandwidth	1MHz
Carrier Frequencies	Please refer to section 3.3
Antenna	Please refer to section 3.4

3.2. Accessories


N/A

3.3. Table for Carrier Frequencies

Frequency Band	Channel No.	Frequency
2403 ~ 2478MHz	1	2403 MHz
	2	2404 MHz
	:	:
	39	2441 MHz
	40	2442 MHz
	41	2443 MHz
	:	:
	75	2477 MHz
	76	2478 MHz

3.4. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	-	-	PCB Antenna	N/A	3.24



3.5. Table for Test Modes

Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Channel	Antenna
Field Strength of Fundamental Emissions	CTX	1/40/76	1
20dB Spectrum Bandwidth			
Radiated Emissions 30MHz ~ 1GHz	Normal Link	-	-
Radiated Emissions 1GHz~10 th Harmonic	CTX	1/40/76	1
Band Edge Emissions	CTX	1/40/76	1

Note: CTX=continuously transmitting

3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D	-
TH01-CB	OVEN Room	Hsin Chu	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

Please refer section 6 for Test Site Address.


3.7. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
PC	DELL	OPTIPLEX 380	N/A
LCD Monitor	DELL	1704FPt	DoC
Modem	ACEEX	DM1414	IFAXDM1414
Printer	EPSON	LQ-300+	N/A
Mouse	Toshiba	M66GF	CJ6-M66GF
Dongle	Toshiba	D660	CJ6-D660
Connector	Dishhd Asia	UB-199	DoC

3.8. Test Configurations

3.8.1. Radiation Emissions Test Configuration

Test Configuration: 30MHz~1GHz



Item	Connection	Shield	Length
1	Power cable	No	1.8 m
2	VGA cable	No	1.8m
3	USB cable	No	1.5m
4	RS-232 cable	Yes	1.8m

Test Configuration: Above 1GHz



4. TEST RESULT

4.1. Field Strength of Fundamental Emissions Measurement

4.1.1. Limit

The field strength of fundamental emissions within these bands specified at a distance of 3 meters (measurement instrumentation employing an average detector) shall comply with the following table.

Frequency Band (MHz)	Fundamental Emissions Limit (dBuV/m) at 3m
2400-2483.5	94 (Average)
	114 (Peak)

4.1.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.


Power Meter Parameter	Setting
RB	1 MHz Peak / 3MHz Peak
VB	1 MHz Peak / 10Hz Average
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. For Fundamental emissions, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter

operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.

4.1.4. Test Setup Layout



4.1.5. Test Deviation

There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.1.7. Test Result of Field Strength of Fundamental Emissions

Temperature	26°C	Humidity	60%
Test Engineer	Andre Zhuo	Configurations	Channel 1
Test Date	Mar. 14, 2013		

Horizontal

Freq	Level	Limit		Over Limit	Read Level	Cable			Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
		Line	dB			dB	dB	dB/m						
1 p	2403.40	96.92	114.00	-17.08	66.16	2.92	0.00	27.84	Peak			134	100	HORIZONTAL
2 a	2403.40	84.35	94.00	-9.65	53.59	2.92	0.00	27.84	Average			134	100	HORIZONTAL

Vertical

Freq	Level	Limit		Over Limit	Read Level	Cable			Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
		Line	dB			dB	dB	dB/m						
1 p	2403.40	90.48	114.00	-23.52	59.72	2.92	0.00	27.84	Peak			85	122	VERTICAL
2 a	2403.40	77.91	94.00	-16.09	47.15	2.92	0.00	27.84	Average			85	122	VERTICAL

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

Temperature	26°C	Humidity	60%
Test Engineer	Andre Zhuo	Configurations	Channel 40
Test Date	Mar. 14, 2013		

Horizontal

Freq	Level	Limit		Over Limit	Read Level	Cable			Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m						
1 p	2441.60	98.63	114.00	-15.37	67.91	2.94	0.00	27.78	Peak			166	100	HORIZONTAL
2 a	2441.60	86.06	94.00	-7.94	55.34	2.94	0.00	27.78	Average			166	100	HORIZONTAL

Vertical

Freq	Level	Limit		Over Limit	Read Level	Cable			Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m						
1 p	2441.60	91.96	114.00	-22.04	61.24	2.94	0.00	27.78	Peak			134	100	VERTICAL
2 a	2441.60	79.39	94.00	-14.61	48.67	2.94	0.00	27.78	Average			134	100	VERTICAL

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

Temperature	26°C	Humidity	60%
Test Engineer	Andre Zhuo	Configurations	Channel 76
Test Date	Mar. 14, 2013		

Horizontal

Freq	Level	Limit		Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
		Line	dB									
MHz	dBuV/m	dBuV/m	dB		dBuV	dB	dB	dB/m		deg	cm	
1 p	2477.40	94.86	114.00	-19.14	64.17	2.96	0.00	27.73	Peak	170	100	HORIZONTAL
2 a	2477.40	82.29	94.00	-11.71	51.60	2.96	0.00	27.73	Average	170	100	HORIZONTAL

Vertical

Freq	Level	Limit		Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
		Line	dB									
MHz	dBuV/m	dBuV/m	dB		dBuV	dB	dB	dB/m		deg	cm	
1 p	2477.60	89.33	114.00	-24.67	58.64	2.96	0.00	27.73	Peak	82	188	VERTICAL
2 a	2477.60	76.76	94.00	-17.24	46.07	2.96	0.00	27.73	Average	82	188	VERTICAL

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

4.2. 20dB Spectrum Bandwidth Measurement

4.2.1. Limit

Intentional radiators must be designed to ensure that the 20 dB bandwidth of the emissions in the specific band (2403 ~ 2478MHz).

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 20dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 20dB below carrier.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of 20dB Spectrum Bandwidth

Temperature	23°C	Humidity	63%
Test Engineer	Wen Chao	Configurations	Channel 1/40/76


Frequency	20dB BW (MHz)	99% OBW (MHz)	Frequency range (MHz) $f_L > 2400\text{MHz}$	Frequency range (MHz) $f_H < 2483.5\text{MHz}$	Test Result
2403 MHz	1.59	1.62	2402.1360	-	Complies
2442 MHz	2.07	1.88	-	-	Complies
2478 MHz	1.82	1.70	-	2478.6480	Complies

20 dB/99% Bandwidth Plot on 2403 MHz




Date: 13.MAR.2013 11:22:57

20 dB/99% Bandwidth Plot on 2442 MHz



Date: 13.MAR.2013 11:17:47

20 dB/99% Bandwidth Plot on 2478 MHz



Date: 13.MAR.2013 11:27:18

4.3. Radiated Emissions Measurement

4.3.1. Limit

Harmonic emissions limits comply with below 54 dBuV/m at 3m. Other emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or comply with the radiated emissions limits specified in section 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.3.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 3MHz for Peak, 1 MHz / 10Hz for Average


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.3.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.3.4. Test Setup Layout

For radiated emissions below 1GHz



For radiated emissions above 1GHz



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	26°C	Humidity	60%
Test Engineer	Andre Zhuo	Configurations	Normal Link
Test Date	Mar. 14, 2013		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.


4.3.8. Results of Radiated Emissions (30MHz~1GHz)

Temperature	26°C	Humidity	60%
Test Engineer	Andre Zhuo	Configurations	Normal Link

Horizontal



Freq	Level	Limit	Over	Read	Cable			Preamp	Antenna	T/Pos	A/Pos	Pol/Phase
					Line	Limit	Level					
1	30.00	30.71	40.00	-9.29	37.95	0.83	27.97	19.90	QP	156	100	HORIZONTAL
2	299.66	34.69	46.00	-11.31	45.21	2.51	26.83	13.80	QP	212	103	HORIZONTAL
3	704.15	34.18	46.00	-11.82	37.08	4.16	27.08	20.02	QP	298	100	HORIZONTAL
4	709.97	34.10	46.00	-11.90	36.98	4.17	27.09	20.04	QP	189	124	HORIZONTAL
5	730.34	34.40	46.00	-11.60	37.19	4.19	27.10	20.12	QP	302	100	HORIZONTAL
6	772.05	32.08	46.00	-13.92	34.36	4.27	27.02	20.47	QP	248	107	HORIZONTAL

Vertical


Freq	Level	Limit	Over	Read	Cable			Antenna	T/Pos	A/Pos	Pol/Phase
					Line	Limit	dB				
MHz	dBuV/m	dBuV/m	dB	dB	dB	dB	dB	dB/m		deg	cm
1	31.94	29.89	40.00	-10.11	38.30	0.87	27.98	18.70 QP		109	100 VERTICAL
2	92.08	20.65	43.50	-22.85	37.37	1.42	27.86	9.72 QP		297	100 VERTICAL
3	299.66	25.82	46.00	-20.18	36.34	2.51	26.83	13.80 QP		162	103 VERTICAL
4	738.10	35.18	46.00	-10.82	37.94	4.20	27.11	20.15 QP		173	114 VERTICAL
5	807.94	34.73	46.00	-11.27	36.39	4.37	26.89	20.86 QP		259	100 VERTICAL
6 q	832.19	36.53	46.00	-9.47	37.96	4.41	26.90	21.06 QP		93	121 VERTICAL

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.3.9. Results for Radiated Emissions (1GHz~10th Harmonic)

Temperature	26°C	Humidity	60%
Test Engineer	Andre Zhuo	Configurations	Channel 1
Test Date			

Horizontal

Freq	Level	Limit		Over Limit	Read Level	Cable			Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB						
1 p	4805.58	52.42	74.00	-21.58	50.40	4.20	34.70	32.52	Peak			124	118	HORIZONTAL
2 a	4805.58	39.85	54.00	-14.15	37.83	4.20	34.70	32.52	Average			124	118	HORIZONTAL

Vertical

Freq	Level	Limit		Over Limit	Read Level	Cable			Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB						
1 p	4806.44	58.22	74.00	-15.78	56.20	4.20	34.70	32.52	Peak			11	101	VERTICAL
2 a	4806.44	45.65	54.00	-8.35	43.63	4.20	34.70	32.52	Average			11	101	VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Andre Zhuo	Configurations	Channel 40

Horizontal

Freq	Level	Limit		Over Limit	Read Level	Cable			Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
		Line	dBuV/m			dB	dBuV	dB						
1 p	4884.31	52.51	74.00	-21.49	50.30	4.22	34.67	32.66	Peak			281	100	HORIZONTAL
2 a	4884.31	39.94	54.00	-14.06	37.73	4.22	34.67	32.66	Average			281	100	HORIZONTAL

Vertical

Freq	Level	Limit		Over Limit	Read Level	Cable			Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
		Line	dBuV/m			dB	dBuV	dB						
1 p	4884.43	59.32	74.00	-14.68	57.11	4.22	34.67	32.66	Peak			3	100	VERTICAL
2 a	4884.43	46.75	54.00	-7.25	44.54	4.22	34.67	32.66	Average			3	100	VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Andre Zhuo	Configurations	Channel 76
Test Date	Mar. 14, 2013		

Horizontal

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	T/Pos	A/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB						
1 p	4955.59	54.53	74.00	-19.47	52.11	4.23	34.64	32.83	Peak			157	131	HORIZONTAL
2 a	4955.59	41.96	54.00	-12.04	39.54	4.23	34.64	32.83	Average			157	131	HORIZONTAL

Vertical

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	T/Pos	A/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB						
1 p	4955.51	58.10	74.00	-15.90	55.68	4.23	34.64	32.83	Peak			358	100	VERTICAL
2 a	4955.51	45.53	54.00	-8.47	43.11	4.23	34.64	32.83	Average			358	100	VERTICAL

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.4. Band Edge Emissions Measurement

4.4.1. Limit

Band edge emissions radiated outside of the specified frequency bands shall be attenuated by at least 50 dB below the level of the fundamental or comply with the radiated emissions limits specified in section 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.4.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1MHz / 3MHz for Peak, 1 MHz / 10Hz for Average

4.4.3. Test Procedures

1. The test procedure is the same as section 4.2.3, only the frequency range investigated is limited to 2MHz around bandedges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

4.4.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.2.4.

4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of Band Edge and Fundamental Emissions

Temperature	26°C	Humidity	60%
Test Engineer	Andre Zhuo	Configurations	Channel 1, 40, 76
Test Date	Mar. 14, 2013		

Channel 1

Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Pol/Phase
		Line	Limit	Level	Loss	Factor	Factor			
1	2389.80	54.31	74.00	-19.69	23.53	2.91	0.00	27.87	Peak	134
2	2389.80	41.74	54.00	-12.26	10.96	2.91	0.00	27.87	Average	134
3 p	2403.40	96.92			66.16	2.92	0.00	27.84	Peak	134
4 a	2403.40	84.35			53.59	2.92	0.00	27.84	Average	134

Item 3, 4 are the fundamental frequency at 2403 MHz.

Channel 40

Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Pol/Phase
		Line	Limit	Level	Loss	Factor	Factor			
1	2390.00	54.14	74.00	-19.86	23.36	2.91	0.00	27.87	Peak	166
2	2390.00	41.57	54.00	-12.43	10.79	2.91	0.00	27.87	Average	166
3 p	2441.60	98.63			67.91	2.94	0.00	27.78	Peak	166
4 a	2441.60	86.06			55.34	2.94	0.00	27.78	Average	166
5	2483.50	54.27	74.00	-19.73	23.58	2.96	0.00	27.73	Peak	166
6	2483.50	41.70	54.00	-12.30	11.01	2.96	0.00	27.73	Average	166

Item 3, 4 are the fundamental frequency at 2442MHz.

Channel 76

Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Pol/Phase
		Line	Limit	Level	Loss	Factor	Factor			
1 p	2477.40	94.86			64.17	2.96	0.00	27.73	Peak	170
2 a	2477.40	82.29			51.60	2.96	0.00	27.73	Average	170
3	2484.10	55.34	74.00	-18.66	24.65	2.96	0.00	27.73	Peak	170
4	2484.10	42.77	54.00	-11.23	12.08	2.96	0.00	27.73	Average	170

Item 1, 2 are the fundamental frequency at 2478 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5. Antenna Requirements

4.5.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.5.2. Antenna Connector Construction

Please refer to section 3.1 in this test report, antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Nov. 27, 2012	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 KHz - 30 MHz	Nov. 05, 2012*	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 27, 2012	Radiation (03CH01-CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Nov. 23, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 27, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Nov. 23, 2012	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26.5GHz ~ 40GHz	Jul. 31, 2012	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100056	9KHz~40GHz	Nov. 16, 2012	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESCS 30	100355	9KHz ~ 2.75GHz	Mar. 20, 2012	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N.C.R	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N.C.R	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-1	N/A	1 GHz - 26.5 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-2	N/A	1 GHz - 26.5 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
Signal analyzer	R&S	FSV40	100979	9KHz~40GHz	Oct. 08, 2012	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	Jun. 05, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	2 Way	0120A02056002D	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	3 Way	MDC2366	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	4 Way	0120A04056002D	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz - 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz - 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz - 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz - 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz - 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Nov. 28, 2012	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Nov. 27, 2012	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

** Calibration Interval of instruments listed above is two years.

N.C.R. means Non-Calibration required.



6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085