

Toshiba Corporation  
 FCC ID: CJ6UPA3233WL  
 Request for transmitter modular approval

Transmitter Module Characteristics

Product Category: Mobile Device ( Section 2.1091 of FCC rules )

Item	Requirements	EUT
<b>1</b>	Have its own RF shielding	<b>Device is equipped with Metal shielding to cover RF section. Refer to external photos</b>
<b>2</b>	Have buffered modulation/data inputs (if such inputs are provided),	<b>All inputs to the modules are buffered through logic or microprocessor inputs.</b>
<b>3</b>	Have its own power supply regulation	<b>Internal 2.5V power regulator. Refer to Theory of Operation</b>
<b>4</b>	Meet the antenna requirements of Section 15.203	<b>Device is equipped with unique antenna ( u.FL(v)-LP-040/u.FL-LP-062) connector. Refer to page 1 of external photos</b>
<b>5</b>	Be tested in a stand-alone configuration, i.e., the antenna, AC or DC power and data input/output lines must be connected to the module but, the module must not be inside another case during testing	<b>Device was tested outside the host computer as stand-alone configuration. Refer to setup photos.</b>
<b>6</b>	Be labeled with its own FCC ID number, <b>and</b> if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module.	<b>Two proposed FCC ID label format are included in the filing. One of label is to be placed on the module and the other label is to be placed on the outside of system. Refer to FCC ID label format and location file.</b>
<b>7</b>	Address compliance with the Commission's RF exposure limits in Sections 1.1310 and 2.1093. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF exposure compliance in accordance with Section 15.247(b)(4).	<b>Antenna will be installed on the top edge of LCD panel of notebook computer to provide at least 20cm separation distance to the body.</b>